

Operating Handles (Accepts 3 Padlocks)

	Description	For Use With	Color	Degree of Protection	Cat. No.
	Padlockable handle, standard	Bul. 194R disconnect switches up to 60 A	Black	Type 3R, 3, 12, 4, 4X	194R-PB
			Red/Yellow	Type 3R, 3, 12, 4, 4X	194R-PY
			Black	Type 3R, 3, 12, 4, 4X	194R-PBT
	Padlockable handle, test mode	Bul. 194R disconnect switches up to 60 A	Red/Yellow	Type 3R, 3, 12, 4, 4X	194R-PYT
	Operating Handle Standard orientation with defeater	- IEC Non-fused disconnect switches: 125...630 A - IEC Fused disconnect switches: 100...400 A - UL Disconnect switches: 100...400 A	Black	IP66 (Type 1, 3R, 12, 4, 4X)	194R-HM4
			Red/Yellow	IP66 (Type 1, 3R, 12, 4, 4X)	194R-HM4E
		- IEC Non-fused disconnect switches: 800...1250 A - IEC Fused disconnect switches: 630...1250 A - UL Non-fused disconnect switches: 600...1200 A - UL Fused disconnect switches: 600...800 A	Black with light grey cover	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4-L
			Red/Yellow	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4E-L
	Operating Handle Standard orientation without defeater	- IEC Non-fused disconnect switches: 800...1250 A - IEC Fused disconnect switches: 630...1250 A - UL Non-fused disconnect switches: 600...1200 A - UL Fused disconnect switches: 600...800 A	Black with light grey cover	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4-N2-L
			Red/Yellow	IP65 (Type 1, 3R, 12, 4, 4X)	194R-HM4E-N2-L

OSHA Lockout/Tag Out Compliance (LOTO)

OSHA CFR36 Section 1910 mandates that disconnect switches be able to be locked out while in the OFF position during servicing. All Bulletin 194R handles comply with this important safety requirement. Please see NFPA Article 430 for disconnect requirements of motor applications.



Operating Handles

Figure 18 - Cat. Nos. 194R-P.../140U-P...

