

Bulletin 800F
22.5 mm Push Buttons
 Product Selection

Momentary Push Button Operators, Non-Illuminated — Flush, Extended, Guarded



Flush Operator
 Cat. No. 800FP-F3



Extended Operator
 Cat. No. 800FM-E4



Guarded Operator
 Cat. No. 800FP-G6

Color	Flush		Extended		Pkg. Quantity
	Plastic	Metal	Plastic	Metal	
	Cat. No.	Cat. No.	Cat. No.	Cat. No.	
Black	800FP-F2	800FM-F2	800FP-E2	800FM-E2	1
Green	800FP-F3	800FM-F3	800FP-E3	800FM-E3	
Red	800FP-F4	800FM-F4	800FP-E4	800FM-E4	

800F **P** - **F** **3** -
 a *b* *c* *d*

a

Operator Construction	
Code	Description
P	Round plastic operator (IP66, Type 4/4X/13)
M	Round metal operator (IP66, Type 4/13)

b

Operator Type	
Code	Description
F	Flush
E	Extended
G	Guarded

c

Color Cap	
Code	Color
1	White
2	Black
3	Green
4	Red
5	Yellow
6	Blue
8	Gray*
9	No cap
X	Assortment pack*

d

Packaging	
Code	Description
Blank	1 per package
BP	10 per package

* Available in flush only.

* Assortment pack contains one cap of each color, not available in BP packaging.

Back-of-Panel Components

Contact Blocks with Latch

800F –

P	X	0	1	E
a	b	c	d	e



a

Style	
Code	Description
P	Plastic latch
M	Metal latch

b

Contact Block(s) Termination Style*	
Code	Description
X	Screw termination
Q	Spring-clamp termination

* Six circuits maximum allowable.

c

N.O. (Normally Open) Circuits	
Code	Description
0	No contact
1	1 N.O.
2	2 N.O.
3	3 N.O.
4	4 N.O.
5	5 N.O.
6	6 N.O.

d

N.C. (Normally Closed) Circuits	
Code	Description
0	No contact
1	1 N.C.
2	2 N.C.

Power Modules with Latch



‡ LED modules for use with all illuminated operators. Incandescent module for use with pilot lights, momentary push buttons, and momentary mushroom operators only.
§ Four circuits maximum allowable when power module is used. Do not stack contact block on power module.
♣ Only available for incandescent module.
➤ Only available for integrated LED module.
⚡ For best illumination results, LED color should match lens color.