

High-Performance Electronic Horns with Attached Strobe Beacons

855H – BC D12 E D R 3
 a *b* *c* *d* *e* *f*



Range "A" Horn with Beacon

a

Product Type	
Code	Description
BC	Electronic horn with Xenon strobe beacon, grey housing

b

Voltage	
Code	Description
D12	12V DC
D24	24V DC
A24	24V AC 50/60 Hz
A10	115V AC 50/60 Hz
A20	230V AC 50/60 Hz



Range "C" Horn with Beacon

c

Horn Type	
Code	Description
A	100 dB, 10 tone, 2-stage (DC)
	100 dB, 10 tone, 1-stage (AC)
B	104 dB, 32 tone, 3-stage (DC)
	104 dB, 32 tone, 3-stage (AC)
C	112 dB, 32 tone, 3-stage (DC)
	112 dB, 32 tone, 3-stage (AC)
D	119 dB, 45 tone, 3-stage (DC)
	119 dB, 45 tone, 3-stage (AC)
E	126 dB, 45 tone, 3-stage (DC)
	126 dB, 45 tone, 3-stage (AC)

d

Mount Option	
Code	Description
D	Standard base for surface or on-the-wall mounting with conduit openings and hole plugs



Range "E" Horn with Beacon

e

Illuminated Function	
Code	Description
R	5J strobe

f

Lens Color	
Code	Description
3	Green
4	Red
5	Amber
6	Blue
7	Clear
8	Yellow