







NEMA/EEMAC Terminal Blocks

Open Construction Blocks

1492-F1			1492-F2		1492-F3	
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.						
	<i>Terminal block, tubular screw with pressure plate.</i>		<i>Terminal block, tubular screw without pressure plate.</i>		<i>Terminal block, screw terminal with #6 screw.</i>	
	UL/CSA		UL/CSA		UL/CSA	
	300V AC/DC		300 V AC/DC		300 V AC/DC	
25 A		25 A		25 A		
#22...#14 AWG (0.5...2.5 mm ²)		#22...#14 AWG (0.5...2.5 mm ²)		#22...#14 AWG (0.5...2.5 mm ²)		
0.38 in. (9.7 mm)		0.38 in. (9.7 mm)		Prepared Conductors Only*		
4...10 lb•in (0.5...1.1 N•m)		6...10 lb•in (0.7...1.1 N•m)		6...10 lb•in (0.7...1.1 N•m)		
35 pcs/ft (115 pcs/m)		35 pcs/ft (115 pcs/m)		30 pcs/ft (98 pcs/m)		
-40...+221 °F (-40...+105 °C)		-40...+221 °F (-40...+105 °C)		-40...+221 °F (-40...+105 °C)		
Terminal Blocks			Terminal Blocks		Terminal Blocks	
Cat. No.			Cat. No.		Cat. No.	
Pkg Qty.			Pkg Qty.		Pkg Qty.	
Color:			Color:		Color:	
White			White		White	
Two 3 ft Rails White			Two 3 ft Rails White		Two 3 ft Rails White	
Red			Red		Red	
Blue			Blue		Blue	
Black			Black		Black	
Green			Green		Green	
Yellow			Yellow		Yellow	
Brown			Brown		Brown	
Violet			Violet		Violet	
Grey			Grey		Grey	
Orange			Orange		Orange	
Accessories (page 12-109)			Accessories (page 12-109)		Accessories (page 12-109)	
Cat. No.			Cat. No.		Cat. No.	
Pkg Qty.			Pkg Qty.		Pkg Qty.	
Mounting Rails:			Mounting Rails:		Mounting Rails:	
A-B Rail			A-B Rail		A-B Rail	
3 ft Rigid A-B Rail			3 ft Rigid A-B Rail		3 ft Rigid A-B Rail	
3 ft High-Rise A-B Rail			3 ft High-Rise A-B Rail		3 ft High-Rise A-B Rail	
Standoff Brackets (use every 12 in.)			Standoff Brackets (use every 12 in.)		Standoff Brackets (use every 12 in.)	
End Barrier			End Barrier		End Barrier	
End Anchors:			End Anchors:		End Anchors:	
A-B Rail			A-B Rail		A-B Rail	
A-B Rail — Retaining Clip — Light Duty			A-B Rail — Retaining Clip — Light Duty		A-B Rail — Retaining Clip — Light Duty	
Jumpers:			Jumpers:		Jumpers:	
2-pole Uninsulated			2-pole Uninsulated		2-pole Uninsulated	
50-pole Uninsulated			50-pole Uninsulated		50-pole Uninsulated	
Marking Systems*			Marking Systems*		Marking Systems*	

* 1 sheet, 20 strips.

	1492-F8		1492-CA1		1492-CA1L	
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.						
	Terminal block, screw terminal with wire clamp.		Terminal block, tubular screw with pressure plate.		Terminal block, screw with large head, pressure plate.	
	UL/CSA 300V AC/DC 25 A #22...#14 AWG (0.5...2.5 mm ²) 0.25 in. (6.4 mm) 6...14 lb•in (0.7...1.6 N•m) 30 pcs/ft (98 pcs/m) -40...+221 °F (-40...+105 °C)		UL/CSA 600V AC/DC 55 A #22...#8 AWG (0.5...10 mm ²) 0.38 in. (9.7 mm) 8...16 lb•in (0.9...1.8 N•m) 30 pcs/ft (98 pcs/m) -40...+221 °F (-40...+105 °C)		UL/CSA 600V AC/DC 55 A #22...#8 AWG (0.5...10 mm ²) 0.38 in. (9.7 mm) 8...16 lb•in (0.9...1.8 N•m) 30 pcs/ft (98 pcs/m) -40...+221 °F (-40...+105 °C)	
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Color: White	1492-F8	50	1492-CA1	50	1492-CA1L	50
Two 3 ft Rails White	1492-F8175 (88 pcs/rail)	1	1492-CA1175 (88 pcs/rail)	1	1492-CA1L175 (88 pcs/rail)	1
Red	1492-F8RE	50	1492-CA1RE	50	1492-CA1LRE	50
Blue	1492-F8B	50	1492-CA1B	50	1492-CA1LB	50
Black	1492-F8BL	50	1492-CA1BL	50	1492-CA1LBL	50
Green	1492-F8G	50	1492-CA1G	50	1492-CA1LG	50
Yellow	1492-F8Y	50	1492-CA1Y	50	1492-CA1LY	50
Brown	1492-F8BR	50	1492-CA1BR	50	1492-CA1LBR	50
Violet	1492-F8VT	50	1492-CA1VT	50	1492-CA1LVT	50
Grey	1492-F8GY	50	1492-CA1GY	50	1492-CA1LGY	50
Orange	1492-F1OR	50	1492-CA1OR	50	1492-CA1LOR	50
Accessories (page 12-109)	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.
Mounting Rails:						
A-B Rail	1492-N1	20	1492-N1	20	1492-N1	20
3 ft Rigid A-B Rail	1492-N22	20	1492-N22	20	1492-N22	20
3 ft High-Rise A-B Rail	1492-N44	2	1492-N44	2	1492-N44	2
Standoff Brackets (use every 12 in.)	1492-N25	2	1492-N25	2	1492-N25	2
End Barrier	1492-N18	50	1492-N16	50	1492-N16	50
End Anchors:						
A-B Rail	1492-N23	10	1492-N23	10	1492-N23	10
A-B Rail — Normal Duty	—	—	1492-N47	50	1492-N47	50
A-B Rail — Retaining Clip — Light Duty	1492-N2	50	1492-N2	50	1492-N2	50
Jumpers:						
2-pole Uninsulated	1492-N14	50	1492-N3	50	1492-N3	50
50-pole Uninsulated	—	—	1492-N30	50	1492-N30	50
Fanning Strip (12-pole can cut to desired length)	—	—	1492-N20	1	1492-N20	1
Marking Systems	* 1492-N5	1	1492-N45	20	1492-N45	20

* 1 sheet, 20 strips.