

* Usable for ISO 13849-1:2006 and IEC 62061. Data is based on the following assumptions:


- Mission time/Proof test interval of 20 years
- Functional test at least once within six-month period

Product Selection

Inputs	Safety Outputs	Auxiliary Outputs	Terminals	Reset Type	Power Supply	Cat. No.
1 N.C., 2 N.C., Light Curtain	3 N.O.	1 N.C.	Fixed	Auto. /Manual	24V AC/DC	440R-N23126
				Monitored Manual		440R-N23129
				Auto. /Manual	115V AC	440R-N23125
				Monitored Manual		440R-N23128
				Auto. /Manual	230V AC	440R-N23124
				Monitored Manual		440R-N23127
			Removable (Screw)	Auto. /Manual	24V AC/DC	440R-N23132
				Monitored Manual		440R-N23135
			Removable (Spring Clamp)	Auto. /Manual	24V AC/DC	440R-N23132S
				Monitored Manual		440R-N23135S
			Removable (Screw)	Auto. /Manual	115V AC	440R-N23131
				Monitored Manual		440R-N23134
				Auto. /Manual	230V AC	440R-N23130
				Monitored Manual		440R-N23133

Approximate Dimensions

Dimensions are shown in mm (in.). Dimensions are not intended to be used for installation purposes.



Block Diagram