




	1492-JG4				1492-JG4TW			1492-JG4Q		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Feed-through grounding terminal block				Single-level grounding terminal block with 3 connection points, 2 on one side			Single-level grounding terminal block with two connection points on each side		
Certifications		CSA	IEC	ATEX		CSA	IEC		CSA	IEC
Voltage Rating	—				—			—		
Maximum Current	Grounding				Grounding			Grounding		
Wire Range (Rated Cross Section)	#22...10 AWG		4 mm ²	4 mm ² (#20...12 AWG)	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4 mm ²
Wire Strip Length	0.39 in. (10 mm)				0.394 in. (10 mm)			0.394 in. (10 mm)		
Recommended Tightening Torque	9 lb•in (1.0 N•m)				6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)		
Mounting Torque - Center Screw	4.4...7.1 lb•in (0.5...0.8 N•m)				—			—		
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42									
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color: Green/Yellow	1492-JG4			100	1492-JG4TW		50	1492-JG4Q		50
Accessories	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7		2	1492-DR7		2
End Barrier Yellow	Not Required			—	1492-EBJ4TW-Y		50	1492-EBJ4Q-Y		50
End Anchors:										
Screwless End Retainer	1492-ERL35			20	1492-ERL35		20	1492-ERL35		20
DIN Rail - Normal Duty	1492-EAJ35			100	1492-EAJ35		100	1492-EAJ35		100
DIN Rail - Heavy Duty	1492-EAHJ35			50	1492-EAHJ35		50	1492-EAHJ35		50
Marking Systems:										
Snap-in marker cards	1492-M6X12 (120/card)			5	1492-MR6X12 (120/card)		5	1492-MR6X12 (120/card)		5
Snap-in marker cards	1492-M6X5 (200/card)			5	1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5