

## Cat. No.


The cat. no. used to identify custom-built Bulletin 800H push button stations will be cat. no. listed for enclosure only. The letter **W** is substituted for the letter **Z** and a station serial no. will be added.

## Request for Quote

Please submit your request for quote of a custom-built station to [racustomer@ra.rockwell.com](mailto:racustomer@ra.rockwell.com), including the following information:

1. Cat. no. of the enclosure.
2. Cat. no. of the control units.
3. Cat. no. of legend plates. Indicate text if custom marking is required.
4. Cat. no. of accessories (e.g., guards or locking attachments)
5. Specify vertical/horizontal mounting.
6. Specify desired operator mounting sequence. Inclusion of a sketch is recommended. If no information is given, standard configurations will be used.

## Enclosures (800H only)



**Stainless Steel**  
Cat. No. **800H-2HZ4**



**Rosite Glass Polyester**  
Cat. No. **800H-2HZ4R**



**Fiberglass**  
Cat. No. **800H-2HZ4Y**



**Thermoplastic Polyester**  
Cat. No. **800H-2HZ4C**

No. of Operator Openings	Conduit Hubs		Stainless Steel (#304) Type 4/4X/13*	Rosite Glass Polyester Type 4/4X/13	No. of Operator Openings	Conduit Openings		Fiberglass† Type 4/4X/13	Thermoplastic PolyesterΔ ♦ Type 4/4X
	No.	Dia. [in.]	Cat. No.	Cat. No.		No.	Dia. [in.]§	Cat. No.	Cat. No.
0♣	1	3/4	800H-0HZ4	—	1	1	3/4	800H-1HZ4Y	800H-1HZ4C
1	1	3/4	800H-1HZ4	800H-1HZ4R	2	1	1	800H-2HZ4Y	800H-2HZ4C
1	2	3/4	—	800H-1HZ4RM1	3	1	1	800H-3HZ4Y	800H-3HZ4C
1	1	1	—	800H-1HZ4RM2	4	—	—	—	800H-4HZ4C
2	1	3/4	800H-2HZ4	800H-2HZ4R	—	—	—	—	—
2	2	3/4	800H-2HZ4M1	800H-2HZ4RM1	—	—	—	—	—
2	1	1	800H-2HZ4M2	800H-2HZ4RM2	—	—	—	—	—
3	1	3/4	800H-3HZ4	800H-3HZ4R	—	—	—	—	—
3	2	3/4	800H-3HZ4M1	800H-3HZ4RM1	—	—	—	—	—

4	1	3/4	800H-4HZ4	800H-4HZ4R	—	—	—	—	—
4	2	3/4	800H-4HZ4M1	800H-4HZ4RM1	—	—	—	—	—
5	1	1	800H-5HZ4	—	—	—	—	—	—
6	1	1	800H-6HZ4	800H-6HZ4R	—	—	—	—	—
7	1	1	800H-7HZ4	—	—	—	—	—	—
8	1	1	800H-8HZ4	—	—	—	—	—	—

**Note:** Other combinations of conduit hub sizes are available upon request. Enclosure and conduit dimensions are detailed on **Die Cast Enclosures (Bul. 800T Only)**.

★ Grounding screw provided with stainless steel enclosure.

‡ Extra deep. Accommodates two levels of stackable sealed switch contact blocks.

§ Conduit hubs must be ordered separately. For 3/4 in. hub, order **Cat. No. 1490-N9**. For 1 in. hub, order **Cat. No. 1490-N10**.

♣ Identical to **Cat. No. 800H-1HZ4** but without mounting holes.

Δ No conduit openings provided.

◆ Yellow thermoplastic enclosures may be ordered by adding a Y to the cat. no. Example: **Cat. No. 800H-1HZ4C** becomes **Cat. No. 800H-1HZ4CY**.