

2-Position Selector Switch Operators, Illuminated §



Standard Knob
 Cat. No. 800FP-LSM26

Switching Angle



Target Table and Operator Position*		
Contact Type➤		
N.O.	O	X
N.C.	X	O

Note: X = Closed/O = Open

➤ Contact selection is limited to the following options, consult your local Rockwell Automation sales office or Allen-Bradley distributor for other options.

Color	Operator Type		Pkg. Quantity	Standard Knob	
				Plastic	Metal
				Cat. No.	Cat. No.
Green			1	800FP-LSM23	800FM-LSM23
Red				800FP-LSM24	800FM-LSM24
Yellow				800FP-LSM25	800FM-LSM25

* Target table for spring return from left is reversed from what is shown in the table.

800F **P** – **LS** **M2** **3**
 a **b** **c** **d** **e**

a

Operator Construction	
Code	Description*
P	Round plastic operator (IP66, Type 4/4X/13)
M	Round metal operator (IP66, Type 4/13)

b

Operator Type	
Code	Description
LS	Standard knob
LH	Knob lever♣

c

Operator Function	
Code	Type
M2	Maintained (60° switching angle)
L2	Spring return from left (60° switching angle)
R2	Spring return from right (60° switching angle)

d

Knob/Insert Color		
Code	Knob Color	Insert Color
0	Amber➤	White
3	Green	White
4	Red	White
5	Yellow➤	Black
6	Blue➤	White
7	Clear	Black

e

Orientation	
Code	Description
Blank	Standard
N	90° offset‡

* LED module required for illumination, can not use incandescent module.

‡ For use in vertical mount enclosures.

§ Crevices may exist on product that may be unsuitable for certain applications. Please consult your local Rockwell Automation sales office or Allen-Bradley distributor.

♣ Only available in clear.

➤ Use of a white LED is recommended.

Bulletin 800F
22.5 mm Push Buttons
Product Selection

Back-of-Panel Components, Continued
Power Modules with Contact Blocks and Latch — Composite

800F –

P	N	5	R	X	1	0	E
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>	<i>h</i>

Style	
Code	Description
P	Plastic latch
M	Metal latch

Power Module Type**	
Code	Description
D	Incandescent module, screw termination
N	Integrated LED module, screw termination
Q	Integrated LED module, spring-clamp termination

Voltage	
Code	Description
0	No bulb‡
1	6V AC/DC‡
2	12V AC/DC‡
3	24V AC/DC
4	48V AC/DC‡
5	120V AC
7	240V AC§

Lamp Color*	
Code	Description
C	Incandescent
R	Red LED
G	Green LED
Y	Amber LED
W	White LED
B	Blue LED

Contact Block(s) Termination Style	
Code	Description
X	Screw termination
Q	Spring-clamp termination

N.O. (Normally Open) Circuits	
Code	Description
0	No contact
1	1 N.O.
2	2 N.O.
3	3 N.O.
4	4 N.O.

N.C. (Normally Closed) Circuits	
Code	Description
0	No contact
1	1 N.C.
2	2 N.C.
3	3 N.C.
4	4 N.C.

Specialty Contact Block(s)	
Code	Description
Blank	Standard blocks
V	Low voltage — QuadCONNECT™
E	N.O. early make
L	N.C. late break
B	N.C. early break
S	N.C. self-monitoring

* Four circuits maximum allowable when power module is used. Contact blocks cannot be stacked on power module.
** LED modules for use with all illuminated operators. Incandescent module for use with pilot lights, push buttons, and momentary mushroom operators only.
‡ Only available for incandescent module.
§ Only available for integrated LED module.
♣ For best illuminated results, LED should match lens color. For yellow operator, select a white LED.