


Cable-Operated Disconnect Kits§ (for 20...63 A switches)

	Description	Cable Length	Cat. No.
	Cable-operated disconnect mechanism	3 ft.	194R-FC03
		4 ft.	194R-FC04
		6 ft.	194R-FC06
		10 ft.	194R-FC10

§ For additional information, please see Bulletin 194R-FC and 194R-LFC NFPA 79 Compliant IEC Cable-Operated Mechanism for Flange-Style Enclosures

Side-Mounted Disconnect Switch Kit‡ (for 20...63 A switches)

	Description	For Use With	Cat. No.
	Side-Mounted Kit (Disconnect Mechanism and Bracket)	All Bul. 194R 30/60 A disconnect switchess and Bul. 194R-PY handles	194R-SDK2

‡ For more information, please see Cat. No. 194R-SDK2 NFPA 79 Compliant IEC Fused and Non-Fused Disconnects, Side-Mounted Kit

Disconnect Switch Padlock Accessory (for 20...63 A switches)

	Disconnect Switch Dim Ref.	Pkg. Qty.	Cat. No.§
	A1, A2, B1, B2	1	194R-PLA1

§ For padlock with ø 3...6 mm

Replacement Mounting Hardware (for 20...63 A switches)

	Pkg. Qty.	Description	For Use With	Cat. No.
	2	(1) M4 x .7 set screw, (1) shaft clip and (2) M4 x .7 mounting screws	A1, A2	194R-30-HDWR
	4	(1) M4 x .7 set screw, (1) shaft clip and (4) M4 x .7 mounting screws	B1, B2	194R-60-HDWR

Auxiliary Contact Blocks△

Description	Contact Material	For Use With	Pkg. Quantity	Cat. No.
Contact Block Note: Sold only in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	N.O.	194R 30/60 A switches (all)	10	800F-X10