




1492-F8

1492-CA1

1492-CA1L

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications

Approvals	/CSA	/CSA	/CSA
Voltage Rating	300V AC/DC	600V AC/DC	600V AC/DC
Maximum Current	25 A	55 A	55 A
Wire Range (Rated Cross Section)	#22...#14 AWG (0.5...2.5 mm ²)	#22...#8 AWG (0.5...10 mm ²)	#22...#8 AWG (0.5...10 mm ²)
Wire Strip Length	0.25" (6.4 mm)	0.38" (9.7 mm)	0.38" (9.7 mm)
Recommended Tightening Torque	6...14 lb-in. (0.7...1.6 Nm)	8...16 lb-in. (0.9...1.8 Nm)	8...16 lb-in. (0.9...1.8 Nm)
Density	30 pcs./ft (98/m)	30 pcs./ft (98/m)	30 pcs./ft (98/m)
Insulation Temperature Range	-40...+221°F (-40...+105°C)	-40...+221°F (-40...+105°C)	-40...+221°F (-40...+105°C)

Terminal Blocks

	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Color: White	1492-F8	50	1492-CA1	50	1492-CA1L	50
Two 3' Rails White	1492-F8175 (88/Rail)	1	1492-CA1175 (88/Rail)	1	1492-CA1L175 (88/Rail)	1
Gold	1492-F8GL	50	1492-CA1GL	50	1492-CA1LGL	50
Red	1492-F8RE	50	1492-CA1RE	50	1492-CA1LRE	50
Blue	1492-F8B	50	1492-CA1B	50	1492-CA1LB	50
Black	1492-F8BL	50	1492-CA1BL	50	1492-CA1LBL	50
Green	1492-F8G	50	1492-CA1G	50	1492-CA1LG	50
Yellow	1492-F8Y	50	1492-CA1Y	50	1492-CA1LY	50
Brown	1492-F8BR	50	1492-CA1BR	50	1492-CA1LBR	50
Violet	1492-F8VT	50	1492-CA1VT	50	1492-CA1LVT	50
Gray	1492-F8GY	50	1492-CA1GY	50	1492-CA1LGY	50
Orange	1492-F8OR	50	1492-CA1OR	50	1492-CA1LOR	50

Accessories (page 185)

	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Mounting Rails:						
3' Scored A-B Rail	1492-N1	20	1492-N1	20	1492-N1	20
3' Rigid A-B Rail	1492-N22	20	1492-N22	20	1492-N22	20
3' High Rise A-B Rail	1492-N44	2	1492-N44	2	1492-N44	2
Standoff Brackets (Use Every 12")	1492-N25	2	1492-N25	2	1492-N25	2
End Barrier	1492-N18	50	1492-N16	50	1492-N16	50
End Anchors:						
A-B Rail — Heavy Duty	1492-N23	10	1492-N23	10	1492-N23	10
A-B Rail — Snap On	—	—	1492-N47	50	1492-N47	50
A-B Rail — Retaining Clip — Light Duty	1492-N2	50	1492-N2	50	1492-N2	50
Jumpers:						
2-pole Uninsulated	1492-N14	50	1492-N3	50	1492-N3	50
50-pole Uninsulated	—	—	1492-N30	10	1492-N30	10
Fanning Strip: (12-pole can cut to desired length)	—	—	1492-N20	1	1492-N20	1
Marking Systems	1492-N5 ①	1	1492-N45	20	1492-N45	20

① 1 sheet, 20 strips.