

	<div>Bulletin 194R-FC NFPA 79 Compliant IEC Fused and Non-Fused Disconnects with Cable-Operated Handle for Flange-Style Enclosures</div> <ul style="list-style-type: none">• Cable-operated disconnect kit with interlock• Open switches• Compatible with all Bulletin 194R 30 and 60 A Next Generation fused and non-fused disconnects (sold separately)• Uses Bulletin 1494F handles (sold separately)<ul style="list-style-type: none">– IP66 (Type 3R, 3, 12, 4, 4X)• Padlockable handle mounts to flange-styled enclosures• Cable options available in 3...10 ft. lengths• NFPA 2002 Compliant	<div>Table of Contents</div> <div>Product Selection this page</div> <div>Approximate Dimensions..... 2-497</div> <div>Standards Compliance for Disconnect Switch</div> <div>IEC 60947-4-1/EN60947-3</div> <div>BS EN60947-3</div> <div>VDE 0660</div> <div>CSA 22.2 No. 4</div> <div>NEMA KS-1</div> <div>UL 98</div> <div>Certifications</div> <div>UL Listed (File No. E 47426, Guide WHTY)</div> <div>CSA Certified (File No. LR1234)</div> <div>CE</div> <div>ASTA Certified</div> <div>LOVAG Certified</div>
---	--	--

The Bulletin 194R-FC cable-operated disconnect with interlock is another Rockwell Automation exclusive, providing a fully compliant solution to the 2002 changes in the National Fire Protection Association 79 (NFPA 79).

The new 194R-FC combines the small size of the 194R IEC next generation disconnect with the flexibility of a cable-operated mechanism to provide an NFPA 79 IEC solution for flange style enclosures. The 194R-FC bracketed mechanism for 194R 30 and 60 A devices attaches to the 194R next generation disconnect switch base and operates the ON-OFF action via cable to a standard 1494F handle.

The 194R-FC handle/interlock mechanism provides the ‘no-tools’ operation and the secondary interlock as required by NFPA 79 2002 changes. The 194R-FC cable-operated disconnect is offered in 3...10 ft cable lengths, allowing a variety of placement options for the 194R disconnect within the enclosure. The handle (ordered separately) is available in 3 different styles: plastic, stainless steel, or painted metal.

Product Selection

Description	Cable Length	Cat. No.
Cable-operated disconnect switch with handle	3 ft.	194R-FC03
	4 ft.	194R-FC04
	6 ft.	194R-FC06
	10 ft.	194R-FC010