

Bulletin 800F
22.5 mm Push Buttons
Product Selection

Alternate Action Operators — Non-Illuminated



Cat. No. 800FM-FA3

800F M FA 3
 a b c

Operator Construction	
Code	Description
P	Round plastic operator (IP66, Type 4/4X/13)
M	Round metal operator (IP66, Type 4/13)

Operator Type*	
Code	Description
FA	Non-illuminated, flush, alternate action

Color Cap*	
Code	Color
0	Orange
1	White
2	Black
3	Green
4	Red
5	Yellow
6	Blue
9	No cap
X	Assortment pack

* Must use N.O.E.M. or N.C. contacts.
* For custom laser-engraved legend cap, order "no cap" option plus custom laser-engraved cap on page 10-115.

Alternate Action Operators — Illuminated



Cat. No. 800FP-LFA3

800F P LFA 3
 a b c

Operator Construction	
Code	Description
P	Round plastic operator (IP66, Type 4/4X/13)
M	Round metal operator (IP66, Type 4/13)

Operator Type§*	
Code	Description
LFA	Illuminated, flush, alternate action

Color Cap>	
Code	Color
0	Amber%
3	Green
4	Red
5	Yellow%
6	Blue%
7	Clear
9	No lens

§ Must use N.O.E.M. or N.C. contacts.
* LED module required for illumination, can not use incandescent module.
> For custom laser-engraved operator, order operator with applicable lens cap color plus custom laser-engraved diffuser on page 10-115.
% Use of a white LED is recommended.

Bulletin 800F
22.5 mm Push Buttons
Product Selection

Back-of-Panel Components, Continued
Power Modules with Contact Blocks and Latch — Composite

800F –

P	N	5	R	X	1	0	E
<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e</i>	<i>f</i>	<i>g</i>	<i>h</i>

Style	
Code	Description
P	Plastic latch
M	Metal latch

Power Module Type**	
Code	Description
D	Incandescent module, screw termination
N	Integrated LED module, screw termination
Q	Integrated LED module, spring-clamp termination

Voltage	
Code	Description
0	No bulb‡
1	6V AC/DC‡
2	12V AC/DC‡
3	24V AC/DC
4	48V AC/DC‡
5	120V AC
7	240V AC§

Lamp Color*	
Code	Description
C	Incandescent
R	Red LED
G	Green LED
Y	Amber LED
W	White LED
B	Blue LED

Contact Block(s) Termination Style	
Code	Description
X	Screw termination
Q	Spring-clamp termination

N.O. (Normally Open) Circuits	
Code	Description
0	No contact
1	1 N.O.
2	2 N.O.
3	3 N.O.
4	4 N.O.

N.C. (Normally Closed) Circuits	
Code	Description
0	No contact
1	1 N.C.
2	2 N.C.
3	3 N.C.
4	4 N.C.

Specialty Contact Block(s)	
Code	Description
Blank	Standard blocks
V	Low voltage — QuadCONNECT™
E	N.O. early make
L	N.C. late break
B	N.C. early break
S	N.C. self-monitoring

* Four circuits maximum allowable when power module is used. Contact blocks cannot be stacked on power module.
** LED modules for use with all illuminated operators. Incandescent module for use with pilot lights, push buttons, and momentary mushroom operators only.
‡ Only available for incandescent module.
§ Only available for integrated LED module.
♣ For best illuminated results, LED should match lens color. For yellow operator, select a white LED.