



## Configuration Results

**Product:** 802B-CSADXSXD4

**Description:** 802B Compact, Precision and Small Precision, Compact, Top Push Roller, Side Mount, Standard, No LED Indicator ,11.77N (2.65lb) Torque to Operate , 1.8mm (0.071in) Travel to Operate, 5mm (0.197in) Maximum Travel, 0.2mm (0.008in) Travel to Reset, 4-pin DC Micro QD



Representative Photo Only (actual product may vary based on configuration selections)

**Selected Components**

Drawings

### Selected Components

| Catalog Number | Qty | Product Description                                                                                                                                                                                                                                                    | Supplementary Documents                                                                                                          |
|----------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 802B-CSADXSXD4 | 1   | 802B Compact, Precision and Small Precision, Compact, Top Push Roller, Side Mount, Standard, No LED Indicator ,11.77N (2.65lb) Torque to Operate , 1.8mm (0.071in) Travel to Operate, 5mm (0.197in) Maximum Travel, 0.2mm (0.008in) Travel to Reset, 4-pin DC Micro QD | <ul style="list-style-type: none"> <li>Product Details and Certifications</li> <li>Photo</li> <li>3D STEP Model (STP)</li> </ul> |

Contact your [Rockwell Automation Distributor or sales representative](#) for local pricing.

**Modify**

**Cancel**

**E Mail**