Industrial EtherNet Media♣

Description	Connector Type	Unshielded Cat. No.
M12, D-Code Patchcords and Cordsets		
	Straight male to straight male	1585D-M4TBDM-✳
	Straight male to right angle male	1585D-M4TBDE-✳
	Right angle male to right angle male	1585D-E4TBDE-✳
	Straight male to straight female	1585D-M4TBDF-✳
Front Mount Receptacle		
	Front mount female to RJ45	1585D-D4TBJM-✳
Transition Cable		
	Straight male to RJ45	1585D-M4TBJM-✳

Description	Conductors	Jacket Material	Cable Type	Jacket Color	Cat. No.
RJ45 Patchcords					
	4-pair	Riser PVC	Unshielded twisted pair	Teal	1585J-M8PBJM-✳
		High-flex TPE		Teal	1585J-M8TBJM-✳
M12 to RJ45 Bulkhead Adapter					
	• Transition from IP20 environment to IP67 environment • In-cabinet connectivity with RJ45 connector providing On-Machine solution with M12 D Code connector • Differential 100 Ω terminators used for unused pairs • Cat 5e				**1585A-DD4JD**

✳ Lengths available in 0.3, 0.6, 1, 2, 5, 10, 15, and additional increments of 5 m, up to 75 m.
♣ See On-Machine Connectivity Catalog for complete cable selection information.

www.ab.com/catalogs   Preferred availability cat. nos. are **bold**.
Publication A117-CA001A-EN-P

Allen-Bradley