

Auxiliary Contacts

	Description	 N.O.	 N.C.	Connection Diagrams	For Use With	Cat. No.	*	
 	Auxiliary Contact Blocks for Front Mounting ❶ 2- and 4-pole - Quick and easy mounting without tools - Electronic compatible contacts to 17V, 5mA - Mutual positive guidance to the main contactor poles (except for L types) - Models with equal function with several terminal numbering choices L = Late break / Early make	0	2	           	100-C all	100-FA02		
		1	1		100-C all	C09®10...C23®10	100-FA11	
		2	0		100-C all	C30®00...C85®00	100-FB11	
		1L	1L		100-C all	C09®01...C23®01	100-FC11	
		2	2		100-C all	C30®00...C85®00	100-FA20	
		3	1		100-C all	C30®00...C85®00	100-FBL11	
		4	0		100-C all	C09®10...C23®10	100-FA22	
		1+1L	1+1L		100-C all	C30®00...C85®00	100-FB22	
 	Auxiliary Contact Blocks for Side Mounting without Sequence Terminal Designations ❶ 1- and 2-pole - Two-way numbering for right or left mounting on the contactor - Quick and easy mounting without tools - Electronic compatible contacts to 17V, 5mA - Mutual positive guidance to the main contactor poles (except for L types) L = Late break/Early make	0	1	     	100-C all	100-SA01		
		1	0		100-C all	C09®10...C23®10	100-SA10	
		0	2		100-C all	C30®00...C85®00	100-SA02	
		1	1		100-C all	C09®01...C23®01	100-SA11	
		2	0		100-C all	C30®00...C85®00	100-SA20	
		L1	L1		100-C all	C09®10...C23®10	100-SAL11	
 	Auxiliary Contact Blocks for Side Mounting with Sequence Terminal Designations ❶ 1- and 2-pole - Two-way numbering for right or left mounting on the contactor - Quick and easy mounting without tools - Electronic compatible contacts to 17V, 5mA - Mutual positive guidance to the main contactor poles (except for L types) L = Late break/Early make	0	1	     	100-C all	100-SB01		
		1	0		100-C ❷	C09®10...C23®10	100-SB10	
		0	2		100-C ❷	C30®00...C85®00	100-SB02	
		1	1		100-C ❷	C09®01...C23®01	100-SB11	
		2	0		100-C ❷	C30®00...C85®00	100-SB20	
		L1	L1		100-C ❷	C09®10...C23®10	100-SBL11	

❶ Up to 8 auxiliary contacts may be mounted (a maximum of 4 N.C. contacts on the front of the contactor and a maximum of 2 N.O. contacts on each side).

❷ Double Numbering
Left side mounting only is recommended for Cat. No. 100-C09...100-C23 due to double numbering.

Product Selection— Page 4