




Screw Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-J3				1492-J4				1492-J6			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block				Feed-through terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	690V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	25 A	20 A	24 A	21 A	35 A	25 A	32 A	28 A	50 A	41 A	36 A	
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	#22...10 AWG	#26...10 AWG	4 mm ²	4 mm ² (#20...12 AWG)	#22...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				9.0 lb•in (1.0 N•m)				14.2 lb•in (1.6 N•m)			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				37 pcs/ft (123 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color:	Grey	1492-J3	100		1492-J4	100		1492-J6	100			
	Red	1492-J3-RE	100		1492-J4-RE	100		1492-J6-RE	100			
	Blue	1492-J3-B	100		1492-J4-B	100		1492-J6-B	100			
	Black	1492-J3-BL	100		1492-J4-BL	100		1492-J6-BL	100			
	Green	1492-J3-G	100		1492-J4-G	100		1492-J6-G	100			
	Yellow	1492-J3-Y	100		1492-J4-Y	100		1492-J6-Y	100			
	Orange	1492-J3-OR	100		1492-J4-OR	100		1492-J6-OR	100			
	Brown	1492-J3-BR	100		1492-J4-BR	100		1492-J6-BR	100			
	White	1492-J3-W	100		1492-J4-W	100		1492-J6-W	100			
	Violet	1492-J3-V	100		1492-J4-V	100		—	—		—	
Mounting Rails:	199-DR1		10		199-DR1		10		199-DR1		10	
1 m Symmetrical DIN (Steel)	1492-DR5		10		1492-DR5		10		1492-DR5		10	
1 m Symmetrical DIN (Aluminum)	1492-DR6		2		1492-DR6		2		1492-DR6		2	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barriers	Grey	1492-EBJ3	50		1492-EBJ3	50		1492-EBJ3	50		50	
	Blue	1492-EBJ3-B	50		1492-EBJ3-B	50		1492-EBJ3-B	50		50	
	Yellow	1492-EBJ3-Y	50		1492-EBJ3-Y	50		1492-EBJ3-Y	50		50	
End Anchors and Retainers:	1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
DIN Rail — Normal Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
DIN Rail — Heavy Duty	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
Screwless End Retainer	1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
Jumpers:*	1492-CJJ5-10		20		1492-CJJ6-10		20		1492-CJJ8-10		20	
Screw Center Jumper — 10-pole	1492-CJJ5-4		50		1492-CJJ6-4		50		1492-CJJ8-4		50	
Screw Center Jumper — 4-pole	1492-CJJ5-3		50		1492-CJJ6-3		50		1492-CJJ8-3		50	
Screw Center Jumper — 3-pole	1492-CJJ5-2		50		1492-CJJ6-2		50		1492-CJJ8-2		50	
Screw Center Jumper — 2-pole	1492-CJJ5-2		50		1492-CJJ6-2		50		1492-CJJ8-2		50	
Plug-in Center Jumper — 50-Pole	1492-CJLJ5-50		10		1492-CJLJ6-41 (41-pole)		10		—		—	
Plug-in Center Jumper — 10-Pole	1492-CJLJ5-10		20		1492-CJLJ6-10		20		—		—	
Plug-in Center Jumper — 9-Pole	1492-CJLJ5-9		20		—		—		—		—	
Plug-in Center Jumper — 8-Pole	1492-CJLJ5-8		20		—		—		—		—	
Plug-in Center Jumper — 7-Pole	1492-CJLJ5-7		20		—		—		—		—	
Plug-in Center Jumper — 6-Pole	1492-CJLJ5-6		20		—		—		—		—	
Plug-in Center Jumper — 5-Pole	1492-CJLJ5-5		20		—		—		—		—	
Plug-in Center Jumper — 4-Pole	1492-CJLJ5-4		60		1492-CJLJ6-4		60		—		—	
Plug-in Center Jumper — 3-Pole	1492-CJLJ5-3		60		1492-CJLJ6-3		60		—		—	
Plug-in Center Jumper — 2-Pole	1492-CJLJ5-2		60		1492-CJLJ6-2		60		—		—	
Insulated Side Jumper — 24-Pole	1492-SJ5B-24		50		—		—		—		—	
Insulated Side Jumper — 10-Pole	1492-SJ5B-10		50		—		—		—		—	
Screw Type Jumper Notching Tool	1492-T1		1		1492-T1		1		1492-T1		1	
Other Accessories:	1492-EBJ16		20		1492-EBJ16		20		1492-EBJ16		20	
Partition Plate	1492-TPS23		20		1492-TPS23L		50		1492-TPS23L		50	
Test Plug Socket	1492-TP23		20		1492-TP23		20		1492-TP23		20	
Test Plug	1492-TPJ5		25		1492-TPJ6		25		—		—	
Test Plug (Stackable)	1492-TPJ5		25		1492-TPJ6		25		—		—	
Electrical Warning Plate	1492-EWPJ5		25		1492-EWPJ5		25		1492-EWPJ8		50	
Marking Systems:	1492-M5X12 (144/card)		5		1492-M6X12 (120/card)		5		1492-MR8X12 (84/card)		5	
Snap-in Marker Cards	1492-M5X5 (200/card)		5		1492-M6X5 (200/card)		5		1492-M8X5 (160/card)		5	

* Use of center jumpers may affect spacings, requiring derating of terminal blocks. See page 12-83 for details.

Screw Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks




1492-JD3

1492-JD4

1492-JT3M




Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.






Specifications		Two-level, two-circuit feed-through terminal block				Two-level, two-circuit feed-through terminal block				Three-level, three-circuit terminal block with ground point		
Certifications			CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC
Voltage Rating		600V AC/DC	300V AC/DC	400V AC/DC	275V AC/DC	600V AC/DC	300V AC/DC	800V AC/DC	550V AC/DC	300V AC/DC		400V AC/DC
Maximum Current		20 A	10 A	24 A	21 A	35 A	30 A	32 A	28 A	10 A		24 A
Wire Range (Rated Cross Section)		#22...12 AWG	26...12 AWG	2.5 mm²	2.5 mm² (20...14 AWG)	#26...10 AWG		0.5...4 mm²	4 mm² (20...12 AWG)	#22...12 AWG	#26...10 AWG	0.5...2.5 mm²
Wire Strip Length		0.39 in. (10 mm)				0.315 in. (8 mm)				0.28 in. (7 mm)		
Recommended Tightening Torque		4.5...7.1 lb•in (0.5...0.8 N•m)				4.5 lb•in (0.5 N•m)				4.4 lb•in (0.5 N•m)		
Density		59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating		See page 12-42										
Terminal Blocks		Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Color:	Grey	1492-JD3			100	1492-JD4			100	1492-JT3M		50
	Red	1492-JD3-RE			100	1492-JD4-RE			100	—		—
	Blue	1492-JD3-B			100	1492-JD4-B			100	—		—
	Black	1492-JD3-BL			100	1492-JD4-BL			100	—		—
	Green	1492-JD3-G			100	1492-JD4-G			100	—		—
	Yellow	1492-JD3-Y			100	1492-JD4-Y			100	—		—
	Orange	1492-JD3-OR			100	1492-JD4-OR			100	—		—
	Brown	1492-JD3-BR			100	1492-JD4-BR			100	—		—
	White	1492-JD3-W			100	1492-JD4-W			100	—		—
Accessories		Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)		199-DR1			10	199-DR1			10	199-DR1		10
1 m Symmetrical DIN (Aluminum)		1492-DR5			10	1492-DR5			10	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6			2	1492-DR6			2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7			2	1492-DR7			2	1492-DR7		2
End Barrier	Grey	1492-EBJD3			20	1492-EBJD4			20	1492-EBJ3TM		20
	Blue	1492-EBJD3-B			20	1492-EBJD4-B			20	—		—
	Yellow	1492-EBJD3-Y			20	—			—	—		—
End Anchor and Retainers:												
Screwless End Retainer		1492-ERL35			20	—			—	—		—
DIN Rail — Normal Duty		1492-EAJ35			100	—			—	—		—
DIN Rail — Heavy Duty		1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35		50
Jumpers:												
Center Jumper — 41-pole		—			—	‡	1492-CJLJ6-41		10	—		—
Center Jumper — 10-pole		⌘	1492-CJJ5-10		20	‡	1492-CJLJ6-10		20	—		—
Center Jumper — 4-pole		⌘	1492-CJJ5-4		50	‡	1492-CJLJ6-4		60	—		—
Center Jumper — 3-pole		⌘	1492-CJJ5-3		50	‡	1492-CJLJ6-3		60	—		—
Center Jumper — 2-pole		⌘	1492-CJJ5-2		50	‡	1492-CJLJ6-2		60	—		—
Insulated Side Jumper — 50-Pole		—			—	—			—	1492-SJ6A-50		5
Insulated Side Jumper — 24-Pole		1492-SJ5A-24			50	—			—	—		—
Insulated Side Jumper — 10-Pole		1492-SJ5A-10			50	—			—	—		—
Screw Type Jumper Notching Tool		1492-T1			1	—			—	—		—
Other Accessories:												
Partition Plate		1492-PPJD3			20	1492-PPJD3			20	1492-PPJD3		20
Test Plug Socket		1492-TPS23			20	—			—	—		—
Test Plug		1492-TP23			20	—			—	—		—
Snap-in marker cards		1492-M5X5 (200/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)		5
Snap-in marker cards		1492-M5X8 (144/card)			5	1492-MR6X8 (120/card)			5	1492-MR6X8 (120/card)		5

⌘ Screw Center Jumpers, ‡ Plug-in Center Jumpers

1492-JDG3C					1492-JDG4				1492-JDG4C			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Two-level grounding terminal block with commoning bar				Two-circuit terminal block with one feed-through and one grounding				Two-level grounding terminal block with commoning bar			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—				600V AC/DC	300V AC/DC	800V AC/DC	550V AC/DC	—			
Maximum Current	Grounding				35 A	30 A	32 A	28 A	Grounding			
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²	4 mm ²	#26...10 AWG	4 mm ²	4 mm ²	
Wire Strip Length	0.39 in. (10 mm)				0.31 in. (8 mm)				0.31 in. (8 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				4.5...8.8 lb•in (0.5...1.0 N•m)				4.5...8.8 lb•in (0.5...1.0 N•m)			
Mounting Torque — Center Screw	—				—				—			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating												
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Color: Green/Yellow	1492-JDG3C			100	—			—	1492-JDG4C			100
Grey	—			—	1492-JDG4			100	—			—
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2
Screw Type 1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	—			—	—			—	—			—
End Barrier												
Grey	1492-EBJD4			20	1492-EBJD4			20	1492-EBJD4			20
Yellow	1492-EBJD4-Y			20	1492-EBJD4-Y			20	1492-EBJD4-Y			20
Jumpers:												
Screw Center Jumper — 41-pole	—			—	1492-CJLJ6-41			10	—			—
Center Jumper — 10-pole	—			—	1492-CJLJ6-10			20	—			—
Center Jumper — 4-pole	—			—	1492-CJLJ6-4			60	—			—
Center Jumper — 3-pole	—			—	1492-CJLJ6-3			60	—			—
Center Jumper — 2-pole	—			—	1492-CJLJ6-2			60	—			—
End Anchors and Retainers:												
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50
Marking Systems:												
Snap-in marker cards	1492-M5X8 (144/card)			5	1492-M6X5 (200/card)			5	1492-M6X5 (200/card)			5
Snap-in marker cards	1492-M5X5 (200/card)			5	1492-MR6X8 (120/card)			5	1492-MR6X8 (120/card)			5

Screw Connection Terminal Blocks

Isolation Blocks




1492-JKD3				1492-JKD3TP			1492-JKD4		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Feed through terminal block with knife disconnect			Feed-through terminal block with knife disconnect and test screws			Feed-through terminal block with knife disconnect		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC	600V AC/DC	300V AC/DC	400V AC/DC
Maximum Current	10 A		24 A	10 A		24 A	22 A	10 A	32 A
Wire Range (Rated Cross Section)	#22...12 AWG		2.5 mm²	#22...12 AWG		2.5 mm²	#22...10 AWG		0.05...4.0 mm²
Fuse Size (Dummy Fuse Supplied)	—			—			—		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.512 in. (13 mm)		
Recommended Tightening Torque	7.1 lb•in. (0.8 N•m)			7.1 lb•in. (0.8 N•m)			9.0 lb•in. (1.0 N•m)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color:	Grey	1492-JKD3	100	1492-JKD3TP	100		1492-JKD4	100	
	Blue	1492-JKD3-B	100	—	—		1492-JKD4-B	100	
with Test Points	Grey	—	—	—	—		1492-JKD4TP	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:		199-DR1	10	199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Steel)		1492-DR5	10	1492-DR5	10		1492-DR5	10	
1 m Symmetrical DIN (Aluminum)		1492-DR6	2	1492-DR6	2		1492-DR6	2	
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR7	2	1492-DR7	2		1492-DR7	2	
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	1492-DR7	2		1492-DR7	2	
End Barriers	Grey	1492-EBJ3	50	1492-EBJ3	50		1492-EBJ3	50	
	Yellow	—	—	—	—		1492-EBJ3-Y	50	
End Anchors:		1492-ERL35	20	1492-ERL35	20		1492-ERL35	20	
Screwless End Retainer		1492-EAJ35	100	1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Normal Duty		1492-EAHJ35	50	1492-EAHJ35	50		1492-EAHJ35	50	
DIN Rail — Heavy Duty		1492-EAHJ35	50	1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers:		1492-CJLJ5-50	10	1492-CJLJ5-50	10		—	—	
Plug-in Center Jumper — 50-Pole		—	—	—	—		1492-CJLJ6-41	10	
Plug-in Center Jumper — 41-Pole		1492-CJLJ5-10	20	1492-CJLJ5-10	20		1492-CJLJ6-10	20	
Plug-in Center Jumper — 10-Pole		1492-CJLJ5-9	20	1492-CJLJ5-9	20		—	—	
Plug-in Center Jumper — 9-Pole		1492-CJLJ5-8	20	1492-CJLJ5-8	20		—	—	
Plug-in Center Jumper — 8-Pole		1492-CJLJ5-7	20	1492-CJLJ5-7	20		—	—	
Plug-in Center Jumper — 7-Pole		1492-CJLJ5-6	20	1492-CJLJ5-6	20		—	—	
Plug-in Center Jumper — 6-Pole		1492-CJLJ5-5	20	1492-CJLJ5-5	20		—	—	
Plug-in Center Jumper — 5-Pole		1492-CJLJ5-4	60	1492-CJLJ5-4	60		1492-CJLJ6-4	60	
Plug-in Center Jumper — 4-Pole		1492-CJLJ5-3	60	1492-CJLJ5-3	60		1492-CJLJ6-3	60	
Plug-in Center Jumper — 3-Pole		1492-CJLJ5-2	60	1492-CJLJ5-2	60		1492-CJLJ6-2	60	
Plug-in Center Jumper — 2-Pole		1492-SJ5B-24	50	1492-SJ5B-24	50		—	—	
Insulated Side Jumper — 24-Pole		1492-SJ5B-10	50	1492-SJ5B-10	50		—	—	
Insulated Side Jumper — 10-Pole		—	—	—	—		—	—	
Uninsulated Side Jumper — 10-Pole		—	—	—	—		—	—	
Side Jumper — Insulating Sleeve		—	—	—	—		—	—	
Screw Type Jumper Notching Tool	1492-T1	1		1492-T1	1		—	—	
Other Accessories:		1492-EBJ16	20	1492-EBJ16	20		1492-EBJ16	20	
Partition Plate		—	—	1492-TP23	20		—	—	
Test Plug		—	—	1492-TP23	20		—	—	
Marking Systems:		1492-M5X12 (144/card)	5	1492-M5X12 (144/card)	5		1492-MR6X12 (120/card)	5	
Snap-in marker cards		1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5		1492-M6X12 (120/card)	5	
Snap-in marker cards		1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5		1492-M6X12 (120/card)	5	

1492-JKD4TW

1492-JKD4Q

1492-H7

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Feed-through terminal block with knife disconnect; 3 connection points, 2 on one side			Feed-through terminal block with knife disconnect; 2 connection points on each side			Handle-style isolating terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC	600V AC/DC		500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	25 A		30 A	25 A		30 A	15 A	15 A	15 A
Wire Range (Rated Cross Section)	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4 mm ²	#30...10 AWG		0.5...4.0 mm ²
Fuse Size (Dummy Fuse Supplied)	—			—			1/4 x 1-1/4 in.		
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.38 in. (9.7 mm)		
Recommended Tightening Torque	6.2 lb•in (0.7 N•m)			6.2 lb•in (0.7 N•m)			7.1 lb•in (0.8 N•m)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			33 pcs/ft (109 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-40...+221 °F (-40...+105 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Color:	Grey	1492-JKD4TW	50		1492-JKD4Q	50		—	—
With Test Points	Grey	1492-JKD4TWTP	50		1492-JKD4QTP	50		—	—
	Black	—	—		—	—		1492-H7	25
Accessories		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Mounting Rails:		—	—		—	—		1492-N1	20
3 ft Scored A-B Rail		—	—		—	—		1492-N22	20
3 ft Rigid A-B Rail		—	—		—	—		1492-N44	2
3 ft Rigid Rise A-B Rail		—	—		—	—		1492-N25	2
Standoff Brackets (use every 12 in.) 		—	—		—	—		1492-N25	2
1 m Symmetrical DIN (Steel)		199-DR1	10		199-DR1	10		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10		1492-DR5	10		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2		1492-DR6	2		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2		1492-DR7	2		1492-DR7	2
End Barrier	Grey	1492-EBJ4TW	50		1492-EBJ4Q	50		1492-N37	50
	Yellow	1492-EBJ4TW-Y	50		1492-EBJ4Q-Y	50		—	—
End Anchors and Retainers:		—	—		—	—		1492-N23	10
A-B Rail — Heavy Duty		—	—		—	—		1492-N47	50
A-B Rail — Normal Duty		—	—		—	—		1492-ERL35	20
Screwless End Retainer		1492-ERL35	20		1492-ERL35	20		1492-ERL35	20
DIN Rail - Normal Duty		1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100
DIN Rail - Heavy Duty		1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50
Jumpers:		1492-CJLJ6-41	10		1492-CJLJ6-41	10		—	—
Plug-in Center Jumper — 41-pole		1492-CJLJ6-10	20		1492-CJLJ6-10	20		—	—
Plug-in Center Jumper — 10-pole		1492-CJLJ6-4	60		1492-CJLJ6-4	60		—	—
Plug-in Center Jumper — 4-pole		1492-CJLJ6-3	60		1492-CJLJ6-3	60		—	—
Plug-in Center Jumper — 3-pole		1492-CJLJ6-2	60		1492-CJLJ6-2	60		—	—
Plug-in Center Jumper — 2-pole		—	—		—	—		1492-N49	10
Uninsulated Side Jumper — 10-Pole		—	—		—	—		1492-SJS	10
Side Jumper — Insulating Sleeve		—	—		—	—		—	—
Other Accessories:		—	—		—	—		—	—
Partition Plate		—	—		—	—		—	—
Marking Systems:		1492-MR6X12 (120/card)	5		1492-MR6X12 (120/card)	5		1492-MS8X12 (56/card)	5
Snap-in marker cards		1492-M6X12 (120/card)	5		1492-M6X12 (120/card)	5		1492-MS8X9 (56/card)	5
Snap-in marker cards		—	—		—	—		1492-ALHFB (50/sheet)	1
Adhesive Labels		—	—		—	—		—	—

* For use with 1492-N22 DIN rail only.

Screwless Center Jumpers



For Use With	Color	Pkg Qty.	Cat. No.
1492-L2..., L2T, L2Q, LD2, LD2C	Yellow	60	1492-CJL4-2
		60	1492-CJL4-3
		60	1492-CJL4-4
		60	1492-CJL4-5
		20	1492-CJL4-10
1492-LM3, LC3, LDC3, LDAG3, LDG3P, JKD3..., J3P..., J3, J3TW (see Note)	Yellow	60	1492-CJLJ5-2
	Red	60	1492-CJLJ5-2-R
	Blue	60	1492-CJLJ5-2-B
	Black	60	1492-CJLJ5-2-BL
	Yellow	60	1492-CJLJ5-3
	Red	60	1492-CJLJ5-3-R
	Blue	60	1492-CJLJ5-3-B
	Black	60	1492-CJLJ5-3-BL
	Yellow	60	1492-CJLJ5-4
		20	1492-CJLJ5-5
		20	1492-CJLJ5-6
		20	1492-CJLJ5-7
		20	1492-CJLJ5-8
		20	1492-CJLJ5-9
		20	1492-CJLJ5-10
	Red	20	1492-CJLJ5-10-R
	Blue	20	1492-CJLJ5-10-B
	Black	20	1492-CJLJ5-10-BL
	White	20	1492-CJLJ5-10-W
	Yellow	10	1492-CJLJ5-50
	Red	10	1492-CJLJ5-50-R
	Blue	10	1492-CJLJ5-50-B
	Black	10	1492-CJLJ5-50-BL
	White	10	1492-CJLJ5-50-W

For Use With	Pkg Qty.	Cat. No.
1492-RFB4	10	1492-CJR8-2
	10	1492-CJR8-3
	10	1492-CJR8-4
	10	1492-CJR8-5
	10	1492-CJR8-6
	10	1492-CJR8-7
	10	1492-CJR8-8
	10	1492-CJR8-9
	10	1492-CJR8-10
	10	1492-CJRA10-2
1492-RAFB4	10	1492-CJRA10-3
	10	1492-CJRA10-4
	10	1492-CJRA10-5

For Use With	Color	Pkg Qty.	Cat. No.
1492-J4, J4M (see Note)	Yellow	60	1492-CJLJ6-2
	Red	60	1492-CJLJ6-2-R
	Blue	60	1492-CJLJ6-2-B
	Black	60	1492-CJLJ6-2-BL
	Yellow	60	1492-CJLJ6-3
	Red	60	1492-CJLJ6-3-R
	Blue	60	1492-CJLJ6-3-B
	Black	60	1492-CJLJ6-3-BL
	Yellow	60	1492-CJLJ6-4
	Yellow	20	1492-CJLJ6-10
	Red	20	1492-CJLJ6-10-R
	Blue	20	1492-CJLJ6-10-B
	Black	20	1492-CJLJ6-10-BL
	Yellow	10	1492-CJLJ6-41
	Red	10	1492-CJLJ6-41-R
	Blue	10	1492-CJLJ6-41-B
	Black	10	1492-CJLJ6-41-BL
1492-L6, L6T, L16D	Yellow	60	1492-CJL8-2
		60	1492-CJL8-3
		60	1492-CJL8-4
		10	1492-CJL8-32
1492-L10	Yellow	25	1492-CJL10-2
1492-L16	Yellow	25	1492-CJL12-2
1492-L35	Yellow	10	1492-CJL16-2
1492-L3, L3T, L3Q, L3P, LD3, LD3C, LKD3, LTF3, LS2..., L16D	Yellow	60	1492-CJK5-2
		60	1492-CJK5-3
		60	1492-CJK5-4
		20	1492-CJK5-5
		20	1492-CJK5-6
		20	1492-CJK5-7
		20	1492-CJK5-8
		20	1492-CJK5-9
		20	1492-CJK5-10
		10	1492-CJK5-50
1492-L4, L4T, L4Q, LD4DF, LD4DR, LD4SS, LD4, LD4C, L16D	Yellow	60	1492-CJK6-2
		60	1492-CJK6-3
		60	1492-CJK6-4
		20	1492-CJK6-5
		20	1492-CJK6-6
		20	1492-CJK6-7
		20	1492-CJK6-8
		20	1492-CJK6-9
		20	1492-CJK6-10
		20	1492-CJK6-20