

	Description	Busbar [mm]	Pkg. Qty.	Cat. No.
	Supply Module 3-pole For use with Compact Busbar Supports, Cat. No. 141A-CTU3 6...50 mm² (10...1/0 AWG) round conductors and flat conductors up to 6 x 9 x 0.8 54 mm wide (meets feeder circuit spacings per UL 508A)	12 x 5 or 12 x 10	1	141A-CVN350
	Supply Module 3-pole For use with Compact Busbar Supports, Cat. No. 141A-CTU3 35...150 mm² (2 AWG...300 MCM) round conductors and flat conductors up to 10 x 20 x 1 90 mm wide (meets feeder circuit spacings per UL 508A)	12 x 5 or 12 x 10	1	141A-CVN3150
	Supply Module 3-pole 6...50 mm² (10...1/0 AWG) 54 mm wide (meets feeder circuit spacings per UL 508A)	12...30 x 5 or 12...30 x 10 or TT	1	141A-VN370
	Supply Module 3-pole 35...120 mm² (6 AWG...250 MCM) 81 mm wide (meets feeder circuit spacings per UL 508A)		1	141A-VN3120
	Supply Module 3-pole 95...185 mm² (3/0 AWG...350 MCM) 135 mm wide	20...30 x 5 or 20...30 x 10 or TT	1	141A-VN3185
	Supply Module 3-pole for round conductors 120...300 mm² (250...600 MCM) 135 mm wide		1	141A-VN3300R
	Supply Module 3-pole for flat conductors up to 32 x 20 mm equivalent to 625 mm² (1250 MCM) round conductor ampacity 135 mm wide		1	141A-VN3300F
	Supply Module 3-Pole (set of 3 terminals) for round conductors 120...300 mm² (250...600 MCM) 153 mm wide (3 single poles of 51 mm each) (meets feeder circuit spacings per UL 508A) Requires Cat. No. 141A-BK180 or 141A-BK228 terminal cover	20...30 x 5 or 20...30 x 10 or TT	1	141A-VU3300R
	Supply Module 3-Pole (set of 3 terminals) for flat conductors up to 32x20 mm equivalent to 625 mm² (1250 MCM) 153 mm wide (3 single poles of 51 mm each) (meets feeder circuit spacings per UL 508A) Requires Cat. No. 141A-BK180 or 141A-BK228 terminal cover		1	141A-VU3300F
	Single Terminals Single terminals for supplying busbars 2.5...16 mm² (#14...6 AWG)	12...30 x 5	25	141A-VS116
		12...30 x 10		141A-VS216
	Single Terminals Single terminals for supplying busbars 4...35 mm² (#12...2 AWG)	12...30 x 5		141A-VS135
		12...30 x 10		141A-VS235
	Single Terminals Single terminals for supplying busbars 16...70 mm² (#6...2/0 AWG)	12...30 x 5		141A-VS170
		12...30 x 10		141A-VS270
	Single Terminals Single terminals for supplying busbars 16...120 mm² (#6...250 MCM)	12...30 x 10		141A-VS2120

	Description	Max. Terminal Space (W x H) [mm]	Busbar [mm]	Pkg. Qty.	Cat. No.
	Brace Terminals 3-pole For the connection of flat or flexible copper busbars (meets feeder circuit spacings per UL508A)	55 x 28	30 x 10 or TT	1	141A-VB75528F
		68 x 28			141A-VB76828F
		105 x 28			141A-VB710528F