

Operating Levers

For use with 802T, 802M, 802MC, 802X, 802XR

Rod Levers

Type	Material	Dia.	Cat. No.
	Stainless Steel Rod 5" Long	0.13"	802T-W3 ②
	Stainless Steel Rod 8.5" Long	0.13"	802T-W3B ②
	Stainless Steel Rod 12" Long	0.13"	802T-NX50
	Stainless Steel Rod 11.5" Long	0.13"	802T-W3A
		0.08"	802T-W3F ⑤
	Stainless Steel Rod 14" Long	0.13"	802T-NX159
	Nylon Rod 12" Long	0.25"	802T-W3C 802T-NX142 ⑤
	Stainless Steel Rod 5" Long	0.06"	802T-W5 ②
	Stainless Steel Rod 5" Long One-Way	0.06"	802T-W8①
	Nylatron Looped Rod 6" Long 2" Wide Loop	0.18"	802T-W14
	Nylatron Looped Rod 9" Long 2" Wide Loop	0.18"	802T-NX119
	Steel Rod 9" Long	0.25"	802T-W16
	Nylon Rod 9" Long	0.25"	802T-W16A

Rod Levers—Corrosion-Resistant

Type	Material	Dia.	Cat. No.
	Type 316 stainless steel rod 5" long Block is cast aluminum protected with TUFRAM® ④	0.13"	802MC-W3
	Type 316 stainless steel rod 11.5" long Block is cast aluminum protected with TUFRAM® ④	0.08"	802MC-W3A
	Nylon Rod 12" long Block is cast aluminum protected with TUFRAM® ④	0.25"	802MC-W3C
	Nylon Rod Only	0.25"	WF25507

Approximate Dimensions—See page 5-133.

① Do not use on maintained contact limit switches.

② Recommended for use with low operating torque switches.

③ Not for use with 802M-NPY5 or 802M-ASY5 type switches.

④ TUFRAM® is a synergistic coating which combines the advantages of anodizing with a controlled infusion of PTFE for added corrosion resistance.

⑤ Recommended for high impact applications.