

	Counterclockwise				AMP
--	------------------	--	--	--	-----

Spring Return Neutral Position Models—Switch without Lever

Number of Circuits	Torque to Operate, Max. [N•m (lb•in)]		Travel to Operate Contacts [degrees]	Maximum Travel [degrees]	Travel to Reset Contacts [degrees]	Cat. No.
	Clockwise	Counterclockwise				
4	0.28 (2.5)	0.47 (4.2)	13 max.	75	7 max.	802T-NPTP

★ Fluorinated elastomer shaft seal is supplied with these devices.

‡ Low operating torque model.

§ From one maintained position to another.

Spring Return—Complete Switch

Number of Circuits	Operator Type	Force to Operate [N (lb)]	Travel to Operate Contacts, Max. [mm (in.)]	Maximum Travel [mm (in.)]	Travel to Reset Contacts [mm (in.)]	Cat. No.
2	Top Push Rod	13.8 (3.1)	1.4 (0.057) max.	6.0 (0.236)	0.9 (0.034) max.	802T-BP
	Adjustable Top Push Rod	13.8 (3.1)	1.4 (0.057) max.	6.0 (0.236)	0.9 (0.034) max.	802T-BAP
	Side Push Rod	16.4 (3.7)	3.3 (0.131) max.	5.7 (0.226)	1.9 (0.074) max.	802T-CP
						§ 802T-CGP
	Top Push Roller	13.8 (3.1)	1.4 (0.057) max.	6.0 (0.236)	0.9 (0.034) max.	802T-DP
						§ 802T-DGP
4	Side Push Vertical Roller	16.4 (3.7)	3.3 (0.131) max.	5.7 (0.226)	1.9 (0.074) max.	802T-KP
						§ 802T-KGP
4	Top Push Rod	22.2 (5.0)	1.4 (0.057) max.	6.0 (0.236)	0.9 (0.034) max.	802T-BTP
	Top Push Roller	22.2 (5.0)	1.4 (0.057) max.	6.0 (0.236)	0.9 (0.034) max.	802T-DTP

Spring Return Wobble Stick and Cat Whisker—Switch without Lever

Number of Circuits	Operator Type	Torque to Operate, Max. [N•m (lb•in)]‡	Travel to Operate Contacts [degrees]‡	Maximum Travel [degrees]★ ‡	Travel to Reset Contacts [degrees]★ ‡	Cat. No.
2	Nylon Wobble	0.51 (4.5) max.	9 max.	10	5 max.	802T-WSP