




Spring-Clamp Connection Terminal Blocks

Specialty Feed-Through Blocks

	1492-LD2C			1492-LD3C				1492-LD4C		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Two-level feed-through terminal block with commoning bar			Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar		
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	22 A	25 A	30 A	32 A
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#30...12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Grey	1492-LD2C	50		1492-LD3C	25			1492-LD4C	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2			1492-DR7	2	
End Barriers Grey	1492-EBLD2	50		1492-EBLD3	20			1492-EBLD4	20	
End Anchors and Retainers Screwless End Retainer	1492-ERL35	20		1492-ERL35	20			1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50			1492-EAHJ35	50	
Jumpers:										
Plug-in Center Jumper — 50-Pole	—	—		1492-CJK5-50	10			—	—	
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20		1492-CJK5-10	20			1492-CJK6-10	20	
Plug-in Center Jumper — 9-Pole	—	—		1492-CJK5-9	20			1492-CJK6-9	20	
Plug-in Center Jumper — 8-Pole	—	—		1492-CJK5-8	20			1492-CJK6-8	20	
Plug-in Center Jumper — 7-Pole	—	—		1492-CJK5-7	20			1492-CJK6-7	20	
Plug-in Center Jumper — 6-Pole	—	—		1492-CJK5-6	20			1492-CJK6-6	20	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60		1492-CJK5-5	20			1492-CJK6-5	20	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60		1492-CJK5-4	60			1492-CJK6-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60		1492-CJK5-3	60			1492-CJK6-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60		1492-CJK5-2	60			1492-CJK6-2	60	
Other Accessories:										
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100		1492-PSLS2-2	100			—	—	
Reducing Sleeves 22...20 AWG (0.13...0.2 mm ²) Grey	1492-PSL2-5	100		1492-PSLS2-5	100			—	—	
Test Plug	1492-TPL4	25		—	—			1492-TP23	20	
Electrical Warning Plate	1492-EWPL4	20		—	—			1492-EWPL6	20	
Marking Systems:										
Snap-In Marker Cards	1492-M3X12 (120/card)*	5		1492-M5X10 (144/card)	5			1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M3X5 (100/card)	5		1492-M5X5 (200/card)	5			1492-M6X5 (200/card)	5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Short-Circuit Current Ratings

Short-Circuit Current Ratings — Fuse Ratings

Cat. No.	Wire Cu [AWG]		Overcurrent Protection Fuse Required Class/Max. Amp Rating						Maximum Voltage	SCCR, RMS SYM [A]
	Line	Load	J	T	RK1	RK5	G	CC		
1492-L3	14...12	14...12	30	30	—	—	30	30	600	100,000
1492-L3Q										
1492-L3T										
1492-LD3										
1492-L3QS										
1492-LMJ3										
1492-LMJG3										
1492-LKD3										
1492-L3P										
1492-LG3T										
1492-LG3Q										
1492-LG3										
1492-LD3C										
1492-LDG3C										
1492-LDG3										
1492-LC3	14...12	14...12	30	30	—	—	30	30	300	100,000
1492-LDC3										
1492-LDG3P										
1492-LDG3ND										
1492-LDG3N										
1492-LD3N										
1492-LD31P										
1492-LD3Q2P										
1492-LG31P										
1492-LG3T1P										
1492-L3T1P										
1492-LDG3FB										
1492-L4	14...10	14...10	60	60	30	—	30	30	600	100,000
1492-L4Q										
1492-L4T										
1492-LD4										
1492-LD4C										
1492-LG4										
1492-LG4T										
1492-LG4Q										
1492-LD4DFX2										
1492-L6	14...8	14...8	60	60	30	—	60	30	600	100,000
1492-L6T										
1492-LG6										
1492-LG6T	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-LAFB6	14...8	14...8	60	60	30	—	60	30	300	100,000
1492-L10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-LG10	14...6	14...6	100	100	60	30	60	30	600	100,000
1492-L16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-LG16	14...4	14...4	100	100	60	30	60	30	600	100,000
1492-L35	12...2	12...2	200	200	100	30	60	30	600	100,000
1492-LG35	12...2	12...2	200	200	100	30	60	30	600	100,000

