








Adder Decks

	Description	No. of N.O. Contacts	No. of N.C. Contacts	Continuous Carrying Current (A)	Arrangement	Cat. No.
 Second Deck Cat. No. 700-PB40	Second Deck (2-pole)	2	—	10		700-PB20
		2	—	20		700-PKB20
	Second Deck (4-pole)	4	—	10		700-PB40
		4	—	20		700-PKB40
 Third Deck Cat. No. 700-PC40	Third Deck (2-pole)	2	—	10		700-PC20
		2	—	20		700-PKC20
	Third Deck (4-pole)	4	—	10		700-PC40
		4	—	20		700-PKC40

Contact Cartridges (Convertible from N.O. to N.C. and N.C. to N.O.)

	Description	Continuous Carrying Current (A)	Arrangement	Pkg. Quantity	Cat. No.
 Standard Contact Cartridge Cat. No. 700-CP1, -CP11Z	Standard Contact Cartridge AC Rating NEMA A600 DC Rating NEMA P600	10		1	700-CP1
	Overlap Contact Cartridges Overlapping Used in pairs. N.O. contact closes before N.C. contact opens on pick-up and vice versa on drop-out.⚡	AC Rating NEMA A600 DC Rating NEMA P150 125V DC, 138 VA Make and Break	10 5	2	700-CP11Z
 Master Contact Cartridge Cat. No. 700-CPM	Master Contact Cartridge AC Rating Twice NEMA A600 DC Rating Twice NEMA P600	20		1	700-CPM
 Logic Reed Cartridge Cat. No. 700-CPR	Logic Reed Cartridge for Low Energy Circuits 150V AC 500 mA 25 VA Max. 30V DC 200 mA 6 W Max.	Maximum 150V AC Maximum 30V DC	500 mA 200 mA	1	700-CPR
	Safety Contact Cartridge 10 A cartridge meeting IEC 947-5 Note: Use this cartridge when full compliance to IEC 947-5 is required. 700-P relays equipped with CPS cartridges fully meet the IEC 947-5 spec for mechanically linked contacts.	10		1	700-CPS

⚡ Not Direct Drive.

International Symbol for Mechanically Linked Contacts

