




Spring-Clamp Connection Terminal Blocks

Grounding Blocks

	1492-LG4				1492-LG4T				1492-LG4Q			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through grounding terminal block				Feed-through grounding terminal block with 2 points on one side				Feed-through grounding terminal block with 2 points on each side			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding			
Wire Range (Rated Cross Section)	#26...10 AWG	4 mm ²	4 mm ² (20...10 AWG)		#26...10 AWG	4 mm ²	4 mm ² (20...12 AWG)		#26...10 AWG	4 mm ²	4 mm ² (20...12 AWG)	
Wire Strip Length	0.47 in. (12 mm)				0.47 in. (12 mm)				0.47 in. (12 mm)			
Density	49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)				49 pcs/ft (163 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		
Color: Green/Yellow	1492-LG4	50			1492-LG4T	50			1492-LG4Q	50		
Accessories	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.		
Mounting Rails:												
1 m Symmetrical DIN (Steel)	199-DR1	10			199-DR1	10			199-DR1	10		
1 m Symmetrical DIN (Aluminum)	1492-DR5	10			1492-DR5	10			1492-DR5	10		
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2			1492-DR6	2			1492-DR6	2		
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2			1492-DR7	2			1492-DR7	2		
End Barrier Yellow	1492-EBL4-Y	50			1492-EBL4T-Y	50			1492-EBL4Q-Y	50		
End Anchors and Retainers												
Screwless End Retainer	1492-ERL35	20			1492-ERL35	20			1492-ERL35	20		
DIN Rail — Normal Duty	1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100		
DIN Rail — Heavy Duty	1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50		
Other Accessories:												
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²) White	1492-PSL4-2	100			1492-PSL4-2	100			1492-PSL4-2	100		
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL4-5	100			1492-PSL4-5	100			1492-PSL4-5	100		
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL4-10	100			1492-PSL4-10	100			1492-PSL4-10	100		
Test Plug	1492-TP23	20			1492-TP23	20			1492-TP23	20		
Test Plug (Stackable)	1492-TPL6	25			1492-TPL6	25			1492-TPL6	25		
Marking Systems:												
Snap-In Marker Cards	1492-M6X10 (120/card)	5			1492-M6X10 (120/card)	5			1492-M6X10 (120/card)	5		
Snap-In Marker Cards	1492-M6X5 (200/card)	5			1492-M6X5 (200/card)	5			1492-M6X5 (200/card)	5		
Hinged Marker Cards	1492-MH6X12 (80/card)	5			1492-MH6X12 (80/card)	5			1492-MH6X12 (80/card)	5		