




Spring-Clamp Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks

	1492-LD2			1492-LD3			1492-L3QS		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit feed-through terminal block			Two-circuit feed-through terminal block			Side-by-side two circuit terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	ATEX
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	20 A	25 A	27 A
Wire Range (Rated Cross Section)	#28... 16 AWG		1.5 mm ²	#30... 12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)		2.5 mm ² (20... 12 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-LD2	50	1492-LD3	25		1492-L3QS	50	
	Red	1492-LD2-RE	50	1492-LD3-RE	25		1492-L3QS-RE	50	
	Blue	1492-LD2-B	50	1492-LD3-B	25		1492-L3QS-B	50	
	Black	1492-LD2-BL	50	1492-LD3-BL	25		1492-L3QS-BL	50	
	Green	1492-LD2-G	50	1492-LD3-G	25		1492-L3QS-G	50	
	Yellow	1492-LD2-Y	50	1492-LD3-Y	25		1492-L3QS-Y	50	
	Orange	1492-LD2-OR	50	1492-LD3-OR	25		1492-L3QS-OR	50	
	Brown	1492-LD2-BR	50	1492-LD3-BR	25		1492-L3QS-BR	50	
	White	1492-LD2-W	50	1492-LD3-W	25		1492-L3QS-W	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers	Grey	1492-EBLD2	50	1492-EBLD3	20		1492-EBL3Q	50	
	Blue	1492-EBLD2-B	20	1492-EBLD3-B	20		1492-EBL3Q-B	50	
	Yellow	1492-EBLD2-Y	20	1492-EBLD3-Y	20		1492-EBL3Q-Y	50	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-in Center Jumper — 50-Pole	—	—		1492-CJK5-50	10		—	—	
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20		1492-CJK5-10	20		—	—	
Plug-in Center Jumper — 9-Pole	—	—		1492-CJK5-9	20		—	—	
Plug-in Center Jumper — 8-Pole	—	—		1492-CJK5-8	20		—	—	
Plug-in Center Jumper — 7-Pole	—	—		1492-CJK5-7	20		—	—	
Plug-in Center Jumper — 6-Pole	—	—		1492-CJK5-6	20		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60		1492-CJK5-5	20		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60		1492-CJK5-4	60		—	—	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60		1492-CJK5-3	60		—	—	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60		1492-CJK5-2	60		—	—	
Other Accessories									
Reducing Sleeves #28...24 AWG (0.13...0.2 mm ²)	1492-PSL2-2	100		1492-PSLS2-2	100		1492-PSL3-2	100	
Reducing Sleeves #22...20 AWG (0.25...0.5 mm ²)	1492-PSL2-5	100		1492-PSLS2-5	100		1492-PSL3-5	100	
Reducing Sleeves #18 AWG (0.75...1.0 mm ²)	—	—		—	—		1492-PSL3-10	100	
Test Plug	1492-TPL4	25		—	—		1492-TP23	20	
Electrical Warning Plate	1492-EWPL4	20		—	—		1492-TPL5	25	
	1492-M3X12 (120/card)*	5		1492-M5X10 (144/card)	5		1492-EWPL5	20	
Marking Systems									
Snap-In Marker Cards	1492-M3X5 (100/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	
Hinged Marker Cards	—	—		—	—		1492-MH5X10 (96/card)	5	

* May only be mounted in terminal block corner marking positions.