

Spring-Clamp Connection Terminal Blocks



Fuse Blocks

1492-RFB4...

1492-RAFB4...

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications			Single-circuit fuse terminal block with or without blown fuse indicator			Single-circuit fuse terminal block with or without blown fuse indicator		
Certifications				cUR	IEC		cUR	IEC
Maximum Current			15 A*	15 A*	15 A*	12 A	12 A	12 A
Wire Range (Rated Cross Section)			#22...12 AWG	#22...12 AWG	0.5...4 mm ²	#22...12 AWG	#22...12 AWG	0.5...4 mm ²
Voltage Rating			RFB4/RAFB4	300V AC/DC	500V AC/DC	RFB4/RAFB4	300V AC/DC	500V AC/DC
			RFB424/RAFB424	10...57V AC/DC		RFB424/RAFB424	10...57V AC/DC	
			RFB4250/RAFB4250	85...264V AC		RFB4250/RAFB4250	85...264V AC	
Indicator Type			RFB4/RAFB4	Non-indicating		RFB4/RAFB4	Non-indicating	
			RFB424/RAFB424	LED		RFB424/RAFB424	LED	
			RFB4250/RAFB4250	Neon		RFB4250/RAFB4250	Neon	
Leakage Current			RFB4/RAFB4	—		RFB4/RAFB4	—	
			RFB424/RAFB424	2 mA @ 24V		RFB424/RAFB424	2 mA @ 24V	
			RFB4250/RAFB4250	1 mA @ 264V		RFB4250/RAFB4250	1 mA @ 264V	
Fuse Size (Not Supplied)				5 x 20 mm			1/4 x 1 -1/4 in.	
Wire Strip Length				0.47 in. (12 mm)			0.47 in. (12 mm)	
Density				37 pcs/ft (125 pcs/m)			30 pcs/ft (100 pcs/m)	
Insulation Temperature Range				-4...+140 °F (-20...+60 °C)			-4...+221 °F (-40...+105 °C)	
Terminal Blocks			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color Black (Non-Indicating)			1492-RFB4	25		1492-RAFB4	25	
Black (10...57V LED)			1492-RFB424	25		1492-RAFB424	25	
Black (85...264V Neon)			1492-RFB4250	25		1492-RAFB4250	25	
Accessories			Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails								
1 m Symmetrical DIN (Steel)			199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)			1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)			1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)			1492-DR7	2		1492-DR7	2	
End Barrier			Not Required	—		Not Required	—	
End Retainers/Anchors								
Screwless End Retainer			1492-ERL35	20		1492-ERL35	20	
DIN Rail — Heavy Duty			1492-EAHJ35	50		1492-EAHJ35	50	
Plug-in Center Jumper, 10-Pole			1492-CJR8-10	10		—	—	
Plug-in Center Jumper, 9-Pole			1492-CJR8-9	10		—	—	
Plug-in Center Jumper, 8-Pole			1492-CJR8-8	10		—	—	
Plug-in Center Jumper, 7-Pole			1492-CJR8-7	10		—	—	
Plug-in Center Jumper, 6-Pole			1492-CJR8-6	10		—	—	
Plug-in Center Jumper, 5-Pole			1492-CJR8-5	10		1492-CJRA10-5	10	
Plug-in Center Jumper, 4-Pole			1492-CJR8-4	10		1492-CJRA10-4	10	
Plug-in Center Jumper, 3-Pole			1492-CJR8-3	10		1492-CJRA10-3	10	
Plug-in Center Jumper, 2-Pole			1492-CJR8-2	10		1492-CJRA10-2	10	
Center Jumper Link			1492-CJRL6	10		1492-CJRL5	10	
Marking Systems								
Snap-in Marker for Block			1492-MS8X12 (56/card)	5		1492-MS8X12 (56/card)	5	
Snap-in Marker for Handle			1492-MS6X9 (80/card)	5		1492-MS6X9 (80/card)	5	

* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.