

Frame Reference	G-Frame	H-Frame	I-Frame	J-Frame	K-Frame	M-Frame	N-Frame	NS-Frame	R-Frame
Rated Current I_n	125 A	125 A	225 A	250 A	400 A	800 A	1200 A	1200 A	3000 A
No. of Poles	3, 4	3, 4	3, 4	3, 4	3, 4	3, 4	3, 4	3, 4	3, 4
Interrupting Rating [kA]									
240V	50 65 100	65 100 150 200 200	50 65	65 100 150 200	100 150 200 200	100 200 200	65 100 150	65 100 150	125
480V	25 35 65	25 35 65 100 150	25 35	25 35 65 100	35 65 100 150	50 65 100	50 65 100	50 65 100	125
600Y/347V	10 14 25	—	10 10	—	—	—	—	—	—
600V	—	14 18 25 35	10 10	14 18 25 35	25 35 65 100	25 35 42	25 50 65	25 50 65	100
Breaking Capacity [I_{cu} (kA)]									
220...240V	65 85 100	65 85 100 150 200	65 85	65 85 100 150	85 100 200 200	85 100 200	85 100 200	85 100 200	130
415V	36 50 70	36 50 70 120 150	36 50	36 50 70 120	50 70 120 200	36 70 100	50 70 120	50 70 120	80
440V	36 50 65	36 50 65 100 150	25 40	36 50 65 100	40 65 100 180	35 50 65	50 65 100	50 65 100	80
690V	6 8 10	10 12 15 18 20	5 8	10 12 15 20	25 40 70 80	22 25 30	30 42 50	30 42 50	40
250V DC	36 50 70	36 50 70 85 100	36 50	36 50 70 85	—	36 50 65	—	—	—
500V DC	36 50 70	36 50 70 85 100	36 50	36 50 70 85	36 50 70 100	—	—	—	—
750V DC	—	—	—	—	25 36 70 70	16 36 50	—	—	—
Protection Type									
Thermal Magnetic	✓	✓	✓	✓	✓	✓	—	—	—
Electronic	—	✓	—	✓	✓	✓	✓	✓	✓
Molded Case Switch	✓	✓	✓	✓	✓	✓	✓	✓	✓
Internal Accessories									
Auxiliary Contact	✓	✓	✓	✓	✓	✓	✓	✓	✓
Alarm Contact	✓	✓	✓	✓	✓	✓	✓	✓	✓
AX/AL Combo	✓	✓	✓	✓	✓	✓	✓	✓	✓
Trip Unit Contact	—	✓	—	✓	—	—	✓	✓	✓
Shunt Trip	✓	✓	✓	✓	✓	✓	✓	✓	✓
Shunt Close	—	—	—	—	—	—	✓	✓	✓
UV Relay	✓	✓	✓	✓	✓	✓	✓	✓	✓
Field Installable	✓	✓	✓	✓	✓	✓	✓	✓	✓
External Accessories									
End Cap	STD	STD	STD	STD	STD	STD	STD	STD	—
25 mm Phase Barriers	STD	STD	STD	STD	STD	—	—	—	—
Insulators	STD	STD	STD	STD	STD	STD	—	—	—
Terminal Lugs	✓	✓	✓	✓	✓	✓	✓	✓	✓
Extended Terminal	✓	✓	✓	✓	✓	✓	✓	✓	—
Spreader Terminal	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear Terminal	—	—	—	—	—	—	✓	✓	✓
Phase barriers	✓	✓	✓	✓	✓	✓	✓	✓	✓
Terminal Cover	✓	✓	✓	✓	✓	✓	✓	✓	—
Direct Rotary	✓	✓	✓	✓	✓	✓	✓	—	—
Variable Depth (Door)	✓	✓	✓	✓	✓	✓	✓	—	—
Internal NFPA 79	✓	✓	✓	✓	✓	✓	✓	—	—
Flange Operator	✓	✓	✓	✓	✓	✓	✓	—	—
Flange Cable	✓	✓	✓	✓	✓	✓	✓	—	—
Motor Operator	✓	✓	✓	✓	✓	✓	—	✓	✓
Field Installable	✓	✓	✓	✓	✓	✓	✓	✓	✓

 <i>Cat. No. 140MG-H8P-D12</i>	Bulletin 140MG Motor Circuit Protectors • Current range 0.16...1200 A • UL Listed/Recognized for motor loads – Short-circuit protection – Overload protection must be provided separately • Visible trip indication • High current limiting • High switching capacity The Bulletin 140MG Motor Circuit Protectors provide short circuit protection for individual motor loads. Factory-installed internal accessories make installation and wiring easy. Your order must include: cat. no. of the Motor Circuit Protector or Motor Protection Circuit Breaker selected and, if required, cat. no. of any accessories.	Table of Contents Product Selection 43 Accessories..... 50 Specifications..... 64 Approximate Dimensions..... 68 Standards Compliance IEC 60947-2 UL489 CSA22.2, No. 5 Certifications CE Marked CSA Certified (File No. LR1234) UR Recognized (File No. E224135) CCC
--	--	---

General Information

Motor Circuit Protectors may provide the following protective and control functions.

- Disconnect for Motor Branch Circuit
- Branch-Circuit, Short-Circuit Protection (Magnetic Protection)
- Switching (Manual)

In North America, electrical codes require that an individual Motor Branch Circuit be protected by a UL/CSA Listed Fuse, Circuit Breaker or Self-Protected Combination Motor Controller.

140MG-G, H, I, J, K, M and N Frames:

The 140MG-G, H, I, J, K, M and N frame Motor Circuit Protectors are UL/CSA Recognized as Circuit Breakers. They are UL/CSA Recognized, rather than UL/CSA Listed, since they only provide short circuit protection and not thermal overload protection for the motor.

Motor Circuit Protectors

- Short-Circuit Protection — Magnetic Trip
- Overload Protection — None (Magnetic Trip Only)

Rated Operational Current (I_e) [A]	Magnetic Trip Current [A]									3-phase Hp Ratings★				Max. kW, 3-Phase — AC-3★				Cat. No.‡
	Cam Setting																	
	A	B	C	D	E	F	G	H	I	200V	230V	460V	575V	230V	400/415V	500V	690V	
G-Frame																		
3	9	12	15	18	21	24	27	30	33	0.5	0.5	1.5	2	0.6	0.75	1.1	1.5	140MG-G8P-B30
7	21	28	35	42	49	26	63	70	77	1.5	2	3	5	1.1	2.2	3	4	140MG-G8P-B70
15	45	60	75	90	105	120	135	150	165	3	3	10	10	3	5.5	7.5	11	140MG-G8P-C15
30	90	120	150	180	210	240	270	300	330	7.5	10	20	25	5.5	11	15	22	140MG-G8P-C30
50	150	200	250	300	350	400	450	500	550	15	15	30	40	11	22	22	37	140MG-G8P-C50
70	210	280	350	420	490	560	630	700	770	20	25	50	60	15	30	37	55	140MG-G8P-C70
80	240	320	400	480	560	640	720	800	880	25	30	60	75	22	45	55	75	140MG-G8P-C80
100	300	400	500	600	700	800	900	1000	1100	30	30	75	100	30	55	75	110	140MG-G8P-D10
125	375	500	625	750	875	1000	1125	1250	1375	40	40	100	125	22	45	55	90	140MG-G8P-D12
H-Frame																		
3	9	12	15	18	21	24	27	30	33	0.5	0.5	1.5	2	0.6	0.75	1.1	1.5	140MG-H8P-B30
7	21	28	35	42	49	26	63	70	77	1.5	2	3	5	1.1	2.2	3	4	140MG-H8P-B70
15	45	60	75	90	105	120	135	150	165	3	3	10	10	3	5.5	7.5	11	140MG-H8P-C15
30	90	120	150	180	210	240	270	300	330	7.5	10	20	25	5.5	11	15	22	140MG-H8P-C30
50	150	200	250	300	350	400	450	500	550	15	15	30	40	11	22	22	37	140MG-H8P-C50
70	210	280	350	420	490	560	630	700	770	20	25	50	60	15	30	37	55	140MG-H8P-C70
80	240	320	400	480	560	640	720	800	880	25	30	60	75	22	45	55	75	140MG-H8P-C80
100	300	400	500	600	700	800	900	1000	1100	30	30	75	100	30	55	75	110	140MG-H8P-D10
125	625	703	781	859	938	1016	1094	1172	1250	40	40	100	125	22	45	55	90	140MG-H8P-D12
I-Frame																		
100	600	675	750	825	900	975	1050	1125	1200	30	30	75	100	22	37	45	55	140MG-I8P-D10
110	660	743	825	908	990	1073	1150	1238	1320	30	40	75	100	22	45	55	90	140MG-I8P-D11
125	750	844	938	1031	1125	1219	1313	1406	1500	40	40	100	125	22	45	55	90	140MG-I8P-D12
150	900	1013	1125	1238	1350	1463	1575	1688	1800	50	50	100	150	30	55	75	110	140MG-I8P-D15
J-Frame																		
150	750	844	938	1031	1125	1219	1313	1406	1500	50	50	100	150	30	55	75	110	140MG-J8P-D15
175	875	984	1094	1203	1313	1422	1531	1641	1750	50	60	125	150	37	55	90	132	140MG-J8P-D17
200	1000	1125	1250	1375	1500	1625	1750	1875	2000	60	75	150	200	45	75	90	132	140MG-J8P-D20
225	1125	1266	1406	1547	1688	1828	1969	2109	2250	75	75	150	200	55	90	110	160	140MG-J8P-D22
250	1250	1406	1563	1719	1875	2031	2188	2344	2500	75	100	200	250	55	90	132	160	140MG-J8P-D25

★ The Hp and kW ratings shown are for reference only. They allow for a magnetic trip setting of at least up to 13X the motor FLA. However, the final selection of the MCP should be made based on motor full load current and the requirements of local electrical codes.

‡ The interrupting rating for MCPs is dependent upon the controller used. Please contact your local Rockwell Automation sales office or Allen-Bradley distributor for further information.

Rated Operational Current (<i>I</i> _e) [A]	Magnetic Trip Current [A]	3-phase Hp Ratings★				Max. kW, 3-Phase — AC-3★				Cat. No.‡
	I ₃ (adjustable) [A]	200V	230V	460V	575V	230V	400/415V	500V	690V	
K-Frame										
300	300...3000	75	75	150	200	55	110	160	200	140MG-K8P-D30
400	400...4000	100	100	250	300	90	160	200	250	140MG-K8P-D40
M-Frame										
600	600...6000	125	150	300	400	110	200	250	355	140MG-M8P-D60
800	800...8000	150	200	400	500	160	250	355	500	140MG-M8P-D80
N-Frame										
1200§	1200...12000	250	300	600	700	200	250	500	710	140MG-N8P-E12

★ The Hp and kW ratings shown are for reference only. They allow for a magnetic trip setting of at least up to 13X the motor FLA. However, the final selection of the MCP should be made based on motor full load current and the requirements of local electrical codes.

‡ The interrupting rating for MCPs is dependent upon the controller used. Please contact your local Rockwell Automation sales office or Allen-Bradley distributor for further information.

§ I_3 is adjustable between 1...10x motor FLA. Values based on 1200 A rating plug.

Motor Circuit Protectors

Catalog Number Explanation — 125A, G-Frame & 150 A, I-Frame

Complete Motor Circuit Protector Assemblies with Factory-Installed Options

Examples given in this section are not intended to be used for product selection. Use these configurations only to select all factory-installed options for shunt trips, undervoltage release units, auxiliary contacts, and alarm contacts. Use the codes from Table f to add on to the motor circuit protector cat. no. selected on the previous pages to form a complete cat. no. for a complete assembly with factory-installed options.

140MG – I 8 P – C70 – SD – KA
a
b
c
d
e
f



a

Bulletin No.	
Code	Description
140MG	Global Motor Circuit Protector

b

Frame/Rating	
Code	Description
G	125 A
I	150 A

c

Interrupting Rating/Breaking Capacity (based on I_c at 480V)	
Code	Description
8	High break

d

Protection Type	
Code	Description
P	Adjustable magnetic only (less than $13 \times I_n$)

e

Current Range	
Code	Description
B	e.g., D30 = 3 A
C	e.g., C30 = 30 A
D	e.g., D12 = 120 A

f

Factory-Installed Internal Options ♦	
Shunt Trip and Undervoltage Release Units	
Code	Description
SJ	Shunt Trip, 24...30V AC/DC
SK	Shunt Trip, 48...60V AC/DC
SD	Shunt Trip, 110...127V AC; 110...125V DC
SA	Shunt Trip, 220...240V AC; 220...250V DC
SB	Shunt Trip, 380...440V AC
SC	Shunt Trip, 480...525V AC
UJ	Undervoltage Release, 24...30V AC/DC
UR	Undervoltage Release, 48V AC/DC
UD	Undervoltage Release, 110...127V AC; 110...125V DC
UA	Undervoltage Release, 220...240V AC; 220...250V DC
UB	Undervoltage Release, 380...440V AC
UC	Undervoltage Release, 480...525V AC
No Digit	No Selection
Auxiliary and Alarm Contacts	
Code	Description
KA	1 Aux. Contact, 250V
TA	1 Alarm Contact, 250V
AA	1 Aux., 1 Alarm Contact, 250V
BA	2 Aux., 1 Alarm Contact, 250V
AJ	1 Aux., 1 Alarm Contact, 24V

♦ Select up to two internal options: 1 for left side mounting (shunt trip or undervoltage release), 1 for right (auxiliary or alarm contact). Consult your local Rockwell automation sales office or Allen-Bradley distributor for further assistance.

Molded Case Circuit Breakers

Accessories

Accessories Table of Contents

Description	Page	Description	Page
Internal Electrical Accessories			
Auxiliary/Alarm Contact (AX/AL).....	50	Undervoltage Release (UVR)	53
Shunt Trip (SNT).....	52	Residual Current Release Module.....	53
Shunt Close (SNC).....	52	Current Transformer for Neutral Current	54
Mechanical Accessories			
Terminal Lugs.....	54	Terminal Covers	56
Extended Terminals	55	Variable Depth Rotary Operating Kits	58
Spreader Terminals.....	55	Flex Cable Operators.....	59
Rear Terminals.....	56	Direct Rotary Operators.....	60
Phase Barriers	56	Motor Operators	60

Bulletin 1494V Variable Depth Flange-Mounted Circuit Breaker Operating Mechanism

Components	61
------------------	----

Additional Accessories.....	62
-----------------------------	----

Replacement Parts.....	63
------------------------	----

Internal Electrical Accessories

Auxiliary/Alarm Contact (AX/AL)

Auxiliary and alarm contacts are supplied in multiple variations for customer application.

- Auxiliary Contacts (AX) : Indicate ON/OFF status of the MCCB.
- Alarm Contacts (AL): Indicate trip status of the MCCB. Alarm trip can be initiated by pressing the test button on the molded case circuit breaker, a trip due to overcurrent, short circuit; or trip due to residual current, shunt, or undervoltage release signals.
- Thermal Trip Contacts (TU): Trips only when the MCCB has detected an overcurrent, short-circuit, or protection trip. H- and J-Frame MCCBs have a button to test this feature. Available only for H, J, N, NS, and R frames.

These contacts are installed by removing the MCCB cover and accessing right-side pockets within the breaker with snap-in mounting provisions. Frames G...M are supplied with pig tail wiring, with each terminal wire marked. Frames N, NS, and R are wired internal to the breaker and are terminated for connection using a 3-pin quick connector.





Description	Designation	Diagram	Frame Size	Cat. No.
(1) TU Alarm Contact 250V	TU AL	C	H, J	140G-H-EA1TA
(1) Auxiliary (1) Alarm Contact 250V	AX2/AL1	D	G, H, I, J	140G-G-EA1R1A
(2) Auxiliary (1) Alarm Contact 250V	AX1/AX2/AL1	E	G, H, I, J	140G-G-EA2R1A
(3) Auxiliary (1) Alarm Contact 250V	AX1/AX2/AX3/AL1	F	H, I, J	140G-H-EA3R1A
(3) Auxiliary (2) Alarm Contact 250V	AX1/AX2/AX3/AL1/AL2	G	H, J	140G-H-EA3R2A
(2) Auxiliary (2) Alarm (1) TU AL Contact 250V	AX2/AX3/AL1/AL2/TU AL	H	H, J	140G-H-EA2R2TA
(1) Auxiliary Contact 250V	AX2	A	G, H, I, J	140G-G-EA1A
(1) Auxiliary Contact 250V or (1) Alarm Contact 250V	AX2	A	G, H, I, J	140G-G-EA1AU★
	AL1	B		
(1) Auxiliary Contact 24V	AX2	A	G, H, I, J	140G-G-EA1J★
(1) TU Alarm Contact 24V	TU AL	C	H, J	140G-H-EA1TJ
(1) Auxiliary (1) Alarm Contact 24V	AX2/AL1	D	G, H, I, J	140G-G-EA1R1J
(3) Auxiliary (1) Alarm Contact, 24V	AX1/AX2/AX3/AL1	F	H, I, J	140G-H-EA3R1J
(1) Auxiliary (1) Alarm Contact, 400V	AX2/AL1	D	H, J	140G-H-EA1R1B
(2) Auxiliary Contact 400V	AX1/AX2	I	H, J	140G-H-EA2B
(1) Auxiliary (1) Alarm Contact 250V	AX1/AL1	J	K, M	140G-K-EA1R1A
(3) Auxiliary (1) Alarm Contact 250V	AX1/AX2/AX3/AL1	F	K, M	140G-K-EA3R1A
(3) Auxiliary (1) Alarm Contact 24V	AX1/AX2/AX3/AL1	F	K, M	140G-K-EA3R1J
(1) Auxiliary (1) Alarm Contact 400V	AX1/AL1	J	K, M	140G-K-EA1R1B
(2) Auxiliary Contact 400V	AX1/AX2	I	K, M	140G-K-EA2B
(1) Auxiliary (1) Alarm Contact 24V	AX2/AL1	D	N	140G-N-EA1R1J
(2) Auxiliary Contact 24V	AX1/AX2	I	N, NS	140G-N-EA2J
(1) Auxiliary (1) Alarm Contact 400V	AX2/AL1	D	N	140G-N-EA1R1B
(2) Auxiliary Contact 400V	AX1/AX2	I	N, NS	140G-N-EA2B
(1) TU Alarm Contact 250V	TU AL	C	N, NS	140G-N-EA1TA
(4) Auxiliary Contact 24V	AX1/AX2/AX3/AX4	K	R	140G-R-EA4J
(4) Auxiliary Contact 400V	AX1/AX2/AX3/AX4	K	R	140G-R-EA4A
(1) TU Alarm Contact 250V	TU AL	L	R	140G-R-EA1TA



Representative Photo

★ This contact is supplied with unmarked wires. Contact can function as either an auxiliary or alarm contact, depending on connection method.

Diagrams




Molded Case Circuit Breakers

Accessories

Shunt Trip (SNT)


- Allows for remote tripping of the MCCB by applying control voltage to the shunt trip coil.
- Frames G, H, I, J, K, and M are supplied with pig-tail wiring (each terminal wire is marked).
- Frame N, NS, and R are wired internal to the breaker and terminated for connection using a 3-pin quick connector.

Description		Diagram	Frame Size	Cat. No.	
 Representative Photo	12V DC		G, H, I, J	140G-G-SNR	
	24...30V AC/DC			140G-G-SNJ	
	48...60V AC/DC			140G-G-SNKY	
	110...127V AC/110...125V DC			140G-G-SND	
	220...240V AC/220...250V DC			140G-G-SNA	
	380...440V AC			140G-G-SNB	
 Representative Photo	480...525V AC				140G-G-SNC
	12V DC			K, M	140G-K-SNR
	24...30V AC/DC				140G-K-SNJ
	48...60V AC/DC				140G-K-SNKY
	110...127V AC/110...125V DC				140G-K-SND
	220...240V AC/220...250V DC				140G-K-SNA
380...440V AC			140G-K-SNB		
 Representative Photo	480...525V AC				140G-K-SNC
	24V AC/DC			N, NS	140G-N-SNJ
	48V AC/DC				140G-N-SNKY
	110...120V AC/DC				140G-N-SND
	220...240V AC/DC				140G-N-SNA
	380...400V AC				140G-N-SNB
	24V DC			R	140G-R-SNJ
	48V AC/DC				140G-R-SNKY
	110...120V AC/DC				140G-R-SND
	220...240V AC/DC				140G-R-SNA
	380...400V AC/DC				140G-R-SNB

Shunt Close (SNC)


- For use with motorized versions of the NS- and R-Frame MCCB.
- Allows for remote closing of the MCCB when the spring motor is charged.

The shunt close unit is wired internal to the MCCB and terminated for connection using a 3-pin quick connect.

Description	Diagram	Frame Size	Cat. No.
 Representative Photo		NS	140G-NS-SNCJ
			140G-NS-SNCKY
			140G-NS-SNCD
			140G-NS-SNCA
			140G-NS-SNCB
		R	140G-R-SNCJ
			140G-R-SNCKY
			140G-R-SNCD
			140G-R-SNCA
			140G-R-SNCB

Undervoltage Release (UVR)

- Opens the MCCB when supply voltage drops below 0.7 of the UV relay, with a trip rating from 0.7...0.35.
- The MCCB can be reset when the supply voltage is higher than 0.85 of the relay rating.
- When the UV is de-energized it is not possible to close the main contacts on the MCCB.
- R Resistor is supplied with the MCCB when reset is required.

Description		Diagram	Frame Size	Cat. No.
 Representative Photo	24...30V AC/DC		G, H, I, J	140G-G-UVJ
	48V AC/DC			140G-G-UVR
	60V AC/DC			140G-G-UVKY
	110...127V AC/110...125V DC			140G-G-UVD
	220...240V AC/220...250V DC			140G-G-UVA
	380...440 V AC			140G-G-UVB
 Representative Photo	480...525 V AC		K, M	140G-G-UVC
	24...30V AC/DC			140G-K-UVJ
	48V AC/DC			140G-K-UVR
	60V AC/DC			140G-K-UVKY
	110...127V AC/110...125V DC			140G-K-UVD
	220...240V AC/220...250V DC			140G-K-UVA
 Representative Photo	380...440 V AC		N, NS	140G-K-UVB
	480...525 V AC			140G-K-UVC
	24V AC/DC			140G-N-UVJ
	60V AC/DC			140G-N-UVKY
	110...120V AC/DC			140G-N-UVD
	220...240V AC/DC			140G-N-UVA
	380...400V AC	R	140G-N-UVB	
	415...440V AC		140G-N-UVC	
	24V DC		140G-R-UVJ	
	60V AC/DC		140G-R-UVKY	
	110...120V AC/DC		140G-R-UVD	
	220...240V AC/DC		140G-R-UVA	
	380...400V AC		140G-R-UVB	
	440...480V AC		140G-R-UVC	

Residual Current Release Module (IEC Only)

The residual current release module provides protection against low levels of earth (ground) fault currents. It continuously monitors the state of the insulation, with adjustability to provide protection from direct and indirect contact. Compliant with IEC 60947-2 annex B, IEC 61000 for protection against unwarranted tripping.

- Alarm & Trip indication
- 0.03 A with 0.0 s override
- Current adjustment: 0.5...10 A
- Time adjustment: 0.0...3 s
- Test

 Representative Photo	Frame Size	3-Pole Cat. No.	4-Pole Cat. No.
	G	140G-G-ELP1603	140G-G-ELP1604
	H	—	140G-H-ELP1604
	I	140G-I-ELP2503	140G-I-ELP2504
	J	—	140G-J-EP2504
	K	—	140G-K-ELP

Molded Case Circuit Breakers

Accessories

Current Transformer for Neutral Current



Representative Photo

Rated Current [A]	Frame Size	Cat. No.
300	K ★	140G-K-NCTD30
400	K ★	140G-K-NCTD40
600	M ★	140G-M-NCTD60
800	M ★	140G-M-NCTD80
400...1600	N, NS	140G-N-NCTE16
1000...3200	R	140G-R-NCTE30

★ Order with connector (Cat. No. 140G-K-CC).

Mechanical Accessories

Terminal Lugs

	Description	Frame Size	Cat. No. (Pkg. Qty. 3)	Cat. No. (Pkg. Qty. 4)
 Representative Photo	Cu wire, MCCB only (1) 14...1/0 AWG or 2.5...70 mm ²	G	140G-G-TLC13	140G-G-TLC14
	Cu wire, MCP only (1) 14...1/0 AWG or 1.5...70 mm ²		140G-G-TLC13A	—
	Multiple cable - Cu wire (6) 14...2 AWG or 2.5...35 mm ²		140G-G-MTL63	140G-G-MTL64
	Cu wire only (1) 14...1/0 AWG or 2.5...95 mm ²	H	140G-H-TLC13	140G-H-TLC14
	Multiple cable - Cu wire (6) 14...2 AWG or 2.5...35 mm ²		140G-H-MTL63	140G-H-MTL64
 Representative Photo	Al or Cu wire (1) 14...1/0 AWG or 2.5...50 mm ²	I	140G-I-TLA13	140G-I-TLA14
	Al or Cu wire (1) 4...300 MCM or 25...150 mm ²		140G-I-TLA1A3	140G-I-TLA1A4
	Cu wire only (1) 10...250 MCM or 6...185 mm ²		140G-I-TLC13	140G-I-TLC14
	Multiple cable - Cu wire (6) 12...2 AWG or 2.5...35 mm ²		140G-I-MTL63	140G-I-MTL64
 Representative Photo	Al or Cu wire (1) 14...1/0 AWG or 2.5...50 mm ²	J	140G-J-TLA13	140G-J-TLA14
	Al or Cu wire (1) 4...300 MCM or 25...150 mm ²		140G-J-TLA1A3	140G-J-TLA1A4
	Al or Cu wire (1) 6 (Al)/10 (Cu)...350 MCM or 2.5...185 mm ² (Al)		140G-J-TLA1B3	140G-J-TLA1B4
	Cu wire only (1) 10...350 MCM or 6...185 mm ²		140G-J-TLC13	140G-J-TLC14
	Multiple cable - Cu wire (6) 12...2 AWG or 2.5...35 mm ²		140G-J-MTL63	140G-J-MTL64
 Representative Photo	Al or Cu wire (1) 250...500 MCM or 120...240 mm ²	K	140G-K-TLA13	140G-K-TLA14
	Al or Cu wire (2) 2/0...250 MCM or 95...120 mm ²		140G-K-TLA23	140G-K-TLA24
	Cu wire only (1) 250...500 MCM or 120...240 mm ²		140G-K-TLC13	140G-K-TLC14
	Cu wire only (2) 2/0...250 MCM or 95...120 mm ²		140G-K-TLC23	140G-K-TLC24
	Multiple cable - Cu wire (6) 6...1/0 AWG or 16...50 mm ²		140G-K-MTL63	140G-K-MTL64
 Representative Photo	Al or Cu wire (2) 250...500 MCM or 120...240 mm ²	M	140G-M-TLA23	140G-M-TLA24
	Al or Cu wire (3) 2/0...400 MCM or 70...185 mm ²		140G-M-TLA33	140G-M-TLA34
	Cu wire only (2) 3/0...350 MCM or 85...185 mm ²		140G-M-TLC23	140G-M-TLC24
	Cu wire only (3) 2/0...350 MCM or 70...185 mm ²		140G-M-TLC33	140G-M-TLC34
 Representative Photo	Al or Cu wire (4) 4/0...500 MCM or 70...240 mm ²	N, NS	140G-N-TLA43	140G-N-TLA44
	Cu wire only (4) 4/0...500 MCM or 70...240 mm ²		140G-N-TLC43	140G-N-TLC44
	Al or Cu wire (6) 1/0...750 MCM or 50...400 mm ²	R	140G-R-TLA63	—
	Cu wire only (6) 1/0...750 MCM or 50...400 mm ²		140G-R-TLC63	—


Extended Terminals

 Representative Photo	Description	Frame Size	3-Pole Cat. No. (Pkg. Qty. 3)	4-Pole Cat. No. (Pkg. Qty. 4)
	Extended Terminals for busbar or ring type connection - G- & I-frame supplied with 100 mm phase barrier - H- & J-frame supplied with insulator, 100 mm phase barrier, and terminal cover - K- & N-/NS-frame supplied with insulator and 100 mm phase barrier - M-frame terminals only	G	140G-G-EXT3	140G-G-EXT4
		H	140G-H-EXT3	140G-H-EXT4
		I	140G-I-EXT3	140G-I-EXT4
		J	140G-J-EXT3	140G-J-EXT4
		K	140G-K-EXT3	140G-K-EXT4
		M	140G-M-EXT3	140G-M-EXT4
		N, NS	140G-N-EXT3	140G-N-EXT4

Spreader Terminals

Description		Frame Size	3-Pole Cat. No. (Pkg. Qty. 3)	4-Pole Cat. No. (Pkg. Qty. 4)
 <i>Representative Photo</i>	Spreader Terminals for busbar or ring type connection - G- & I-frame supplied with 200 mm phase barrier - H- & J-frame supplied with insulator, 100 mm phase barrier, and terminal cover - K- & N-/NS-frame supplied with insulator and 100 mm phase barrier - M- & R-frame terminals only	G	140G-G-EXS3	140G-G-EXS4
		H	140G-H-EXS3	140G-H-EXS4
		I	140G-I-EXS3	140G-I-EXS4
		J	140G-J-EXS3	140G-J-EXS4
		K	140G-K-EXS3	140G-K-EXS4
		M	—	140G-M-EXS4
		N, NS	—	140G-N-EXS4
		R	140G-R-EXS3	140G-R-EXS4
 <i>Representative Photo</i>	Top Spreader Terminals for busbar or ring type connection M-frame terminals only	M	140G-M-EXSLI3	—
		N, NS	140G-N-EXSLI3	—
	Bottom Spreader Terminals for busbar or ring type connection N/NS-frame supplied with insulator and 100 mm phase barrier	M	140G-M-EXSLO3	—
		N, NS	140G-N-EXSLO3	—

Rear Terminals

	Description	Frame Size	3-Pole Cat. No. (Pkg. Qty. 3)	4-Pole Cat. No. (Pkg. Qty. 4)
	Rear flat horizontal terminals	N, NS	140G-N-TLH3	140G-N-TLH4
	Rear flat vertical terminals	N, NS	140G-N-TLV3	140G-N-TLV4
		R ★	140G-R-TLV3	140G-R-TLV4

★ 2000 A and 2500 A MCCBs only.

Molded Case Circuit Breakers

Accessories


Phase Barriers

- Provides additional clearance when special connections that extend beyond the frame of the MCCB are used.
- Frames G, H, I, J, and K are supplied with 25 mm barriers as standard.

 Representative Photo	Frame Size	Length	3-Pole Cat. No. (Pkg. Qty. 4)	4-Pole Cat. No. (Pkg. Qty. 6)
	G, I	1 in. (25 mm)	140G-G-PB3M	140G-G-PB4M
		4 in. (100 mm)	140G-G-PB3L	140G-G-PB4L
		8 in. (200 mm)	140G-G-PB3H	140G-G-PB4H
	H, J	1 in. (25 mm)	140G-H-PB3M	140G-H-PB4M
		4 in. (100 mm)	140G-H-PB3L	140G-H-PB4L
		8 in. (200 mm)	140G-H-PB3H	140G-H-PB4H
	K, N, NS	4 in. (100 mm)	140G-K-PB3L	140G-K-PB4L
		8 in. (200 mm)	140G-K-PB3H	140G-K-PB4H
	M	4 in. (100 mm)	140G-M-PB3L	140G-M-PB4L
	R	4 in. (100 mm)	140G-R-PB3L	140G-R-PB4L
		8 in. (200 mm)	140G-R-PB3H	140G-R-PB4H

Terminal Covers

- Provide IP40 finger protection against accidental contact with live parts.
- Terminal covers are pre-punched to ease installation.
- Supplied as standard with the selection of multiple cable terminal lugs.

 Representative Photo  Representative Photo	Frame Size	Height	3-Pole Cat. No. (Pkg. Qty. 2)	4-Pole Cat. No. (Pkg. Qty. 2)
	G	0.08 in. (2 mm)	140G-G-TC3L	140G-G-TC4L
		2 in. (50 mm)	140G-G-TC3H	140G-G-TC4H
	H	0.08 in. (2 mm)	140G-H-TC3L	140G-H-TC4L
		2 in. (50 mm)	140G-H-TC3H	140G-H-TC4H
	I	0.08 in. (2 mm)	140G-I-TC3L	140G-I-TC4L
		2.36 in. (60 mm)	140G-I-TC3H	140G-I-TC4H
	J	0.08 in. (2 mm)	140G-J-TC3L	140G-J-TC4L
		2.36 in. (60 mm)	140G-J-TC3H	140G-J-TC4H
	K	0.08 in. (2 mm)	140G-K-TC3L	140G-K-TC4L
		2.36 in. (60 mm)	140G-K-TC3H	140G-K-TC4H
	M	0.08 in. (2 mm)	140G-M-TC3L	140G-M-TC4L
		2.36 in. (60 mm)	140G-M-TC3H	140G-M-TC4H
	N, NS	0.1 in. (2.5 mm)	140G-N-TC3L	140G-N-TC4L
		2.76 in. (70 mm)	140G-N-TC3H	140G-N-TC4H

Variable Depth Rotary Operating Kits

Rotary, Variable Depth Operators

- Supplied with external handle, operating shaft, and MCCB mounted operating mechanism.
- Refer to page 56 to select as components.
- Frames G, H, I, and J use a Bul. 140U P-style handle.
- Frames K, M, and N use a Bul. 140U medium style handle.

	Frame Size	Handle Color	Shaft Length	Cat. No.
 Representative Photo	G, I	Black	12 in. (30.48 mm)	140G-G-RVM12B
		Red/Yellow		140G-G-RVM12R
		Black	21 in. (53.34 mm)	140G-G-RVM21B
		Red/yellow		140G-G-RVM21R
	H, J	Black	12 in. (30.48 mm)	140G-H-RVM12B
		Red/yellow		140G-H-RVM12R
		Black	21 in. (53.34 mm)	140G-H-RVM21B
		Red/yellow		140G-H-RVM21R
 Representative Photo	K	Black	12.6 in. (320 mm)	140G-K-RVM12B
		Red/yellow		140G-K-RVM12R
		Black	22.8 in. (580 mm)	140G-K-RVM21B
		Red/yellow		140G-K-RVM21R
	M	Black	12.6 in. (320 mm)	140G-M-RVM12B
		Red/yellow		140G-M-RVM12R
		Black	22.8 in. (580 mm)	140G-M-RVM21B
		Red/yellow		140G-M-RVM21R
	N	Black	12.6 in. (320 mm)	140G-N-RVM12B
		Red/yellow		140G-N-RVM12R
		Black	22.8 in. (580 mm)	140G-N-RVM21B
		Red/yellow		140G-N-RVM21R

Rotary, Variable Depth Operators with Internal NFPA 79 Operating Handle

- Supplied with external handle, NFPA handle with operating shaft, support bracket, and MCCB mounted operating mechanism.
- Refer to page 58 to select as components.
- Frames G, H, I, and J use a Bul. 140U P-style handle.
- Frames K, M, and N use a Bul. 140U medium style handle.

	Frame Size	Handle Color	Shaft Length	Cat. No.
 Representative Photo	G, I	Black	12 in. (30.48 mm)	140G-G-NVM12B
		Red/yellow		140G-G-NVM12R
		Black	21 in. (53.34 mm)	140G-G-NVM21B
		Red/yellow		140G-G-NVM21R
	H, J	Black	12 in. (30.48 mm)	140G-H-NVM12B
		Red/yellow		140G-H-NVM12R
		Black	21 in. (53.34 mm)	140G-H-NVM21B
		Red/yellow		140G-H-NVM21R
 Representative Photo	K	Black	12.6 in. (320 mm)	140G-K-NVM12B
		Red/yellow		140G-K-NVM12R
		Black	22.8 in. (580 mm)	140G-K-NVM21B
		Red/yellow		140G-K-NVM21R
	M	Black	12.6 in. (320 mm)	140G-M-NVM12B
		Red/yellow		140G-M-NVM12R
		Black	22.8 in. (580 mm)	140G-M-NVM21B
		Red/yellow		140G-M-NVM21R
	N	Black	12.6 in. (320 mm)	140G-N-NVM12B
		Red/yellow		140G-N-NVM12R
		Black	22.8 in. (580 mm)	140G-N-NVM21B
		Red/yellow		140G-N-NVM21R

Molded Case Circuit Breakers

Accessories

Variable Depth Rotary Components

 Representative Photo	Description	Handle Color	Frame Size	Cat. No.
	- P-style handle for G, H, I, and J frames - Medium handles for K, M, and N frames - Rated 3/3R/4/4X/12 - Accepts 3 padlocks	Black/Grey	G, H, I, J	140U-PB
		Red/Yellow		140U-PY
		Black/Grey	K, M, N	140U-HM4
		Red/Yellow		140U-HM4E

 Representative Photo	Description	Shaft Length	Frame Size	Cat. No.
	Extension Shaft	12 in. (305 mm)	G, H, I, J	194R-S1
		21 in. (533 mm)		194R-S2
		12 in. (305 mm)	K, M, N	140U-R5
		21 in. (533 mm)		140U-R6

 Representative Photo	Description	Shaft Length	Frame Size	Cat. No.
	NFPA 79 internal operating handle with shaft Internal handle permits operation of the molded case circuit breaker when the door is open in compliance with NFPA 79.	12 in. (305 mm)	G, H, I, J	140G-N1
		21 in. (533 mm)		140G-N2
		12 in. (305 mm)	K, M, N	140G-N7
		21 in. (533 mm)		140G-N8

 Representative Photo	Description	Frame Size	Cat. No.
	Rotary, Variable Depth Operating Mechanism - Direct molded case circuit breaker mount - G, H, I, and J frame use 194R-S1 or 194R-S2 shafts (140G-N1 or 140G-N2 NFPA) - K, M, and N frames use 194R-R7 or 194R-R8 shafts (140G-R7 or 140G-R8 NFPA) - Shaft secured with set screw or cotter pin	G, I	140G-G-RMX
		H, J	140G-H-RMX
		K	140G-K-RMX
		M	140G-M-RMX
		N	140G-N-RMX

Description	Frame Size	Cat. No.
Support Bracket Supplied as standard with NFPA variable depth operator kits	G, H, I, J	140G-G-OSB
	K	140G-K-OSB
	M	140G-M-OSB
	N	140G-N-OSB

Auxiliary Contacts for Handle Mechanism Mounting

Suitable for:

- 140G-G-RMB, -RMY, RMX
- 140G-H-RMB, -RMY, RMX
- 140G-K-RMB, -RMY, RMX
- 140G-M-RMB, -RMY, RMX

 Representative Photo	Description	Pkg. Qty	Frame Size	Cat. No.
	Early Make Handle Auxiliary Contact Open 400V	2	G, H, I, J	140G-G-EAM1B
	Early Break Handle Auxiliary Contact Close 400V	2		140G-G-EAB1B
	Early Make Handle Auxiliary Contact Close 250V	2	K	140G-K-EAM1A
			M	140G-M-EAM1A

Direct Rotary Operators


- Mount with direct handle operation of the MCCB.
- Lockable in OFF position (three padlocks max.).

 Representative Photo  Representative Photo	Frame Size	Handle Color	Cat. No.
	G, I	Black	140G-G-RMB
		Red/yellow	140G-G-RMY
	H, J	Black	140G-H-RMB
		Red/yellow	140G-H-RMY
	K	Black	140G-K-RMB
		Red/yellow	140G-K-RMY
	M	Black	140G-M-RMB
		Red/yellow	140G-M-RMY
	N	Black	140G-N-RMB
		Red/yellow	140G-N-RMY

Motor Operators

- Remotely opens, closes, and resets the MCCB.
- Frame G & I motor operators are supplied with auto/manual selector, test feature, and special tool for local operation of the MCCB.
- Frames H, J, K, and M utilize a stored energy motor for local control of the motor without the use of special tools and include auto/manual/lock selection, lever to recharge the motor, and open & close push button operation.

Description	Frame Size	Cat. No.
 Representative Photo	24V DC	140G-G-EOPJ
	48...60V DC	140G-G-EOPKY
	110...125V AC/DC	140G-G-EOPD
	220...250V AC/DC	140G-G-EOPA
	380...440V AC	140G-G-EOPB
	480...525V AC	140G-G-EOPC
 Representative Photo	24V DC	140G-H-EOPJ
	48...60V DC	140G-H-EOPKY
	110...125V AC/DC	140G-H-EOPD
	220...250V AC/DC	140G-H-EOPA
	380...440V AC	140G-H-EOPB
	480...525V AC	140G-H-EOPC
 Representative Photo	24V DC	140G-K-EOPJ
	48...60V DC	140G-K-EOPKY
	110...125V AC/DC	140G-K-EOPD
	220...250V AC/DC	140G-K-EOPA
	380V AC	140G-K-EOPB
	24V DC	140G-M-EOPJ
	48...60V DC	140G-M-EOPKY
	110...125V AC/DC	140G-M-EOPD
	220...250V AC/DC	140G-M-EOPA
	380V AC	140G-M-EOPB

Description	Frame Size	Cat. No.
 Representative Photo	NS	140G-NS-SCMA
		140G-NS-SCMB
		140G-NS-SCMD
		140G-NS-SCMJ
		140G-NS-SCMKY
	R	140G-R-SCMA
		140G-R-SCMD
		140G-R-SCMJ
		140G-R-SCMKY

Molded Case Circuit Breakers

Accessories

Flex Cable Operators

- For use with NEMA-style flange enclosures.
- Includes handle, MCCB operator, cable, and necessary hardware.
- Pre-assembled for ease of installation.



Representative Photo

Frame Size	Handle Type	Cable Length	Cat. No.
G, I	Non-metallic Handle, Type 1/3/12/4/4X	4 ft (1.3 m)	140G-G-FCX04
		6 ft (1.9 m)	140G-G-FCX06
		10 ft (3.0 m)	140G-G-FCX10
	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-G-FCS04
		6 ft (1.9 m)	140G-G-FCS06
		10 ft (3.0 m)	140G-G-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-G-FMX04
		6 ft (1.9 m)	140G-G-FMX06
		10 ft (3.0 m)	140G-G-FMX10
H	Non-metallic Handle, Type 1/3/12/4/4X	4 ft (1.3 m)	140G-H-FCX04
		6 ft (1.9 m)	140G-H-FCX06
		10 ft (3.0 m)	140G-H-FCX10
	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-H-FCS04
		6 ft (1.9 m)	140G-H-FCS06
		10 ft (3.0 m)	140G-H-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-H-FMX04
		6 ft (1.9 m)	140G-H-FMX06
		10 ft (3.0 m)	140G-H-FMX10
J	Non-metallic Handle, Type 1/3/12/4/4X	4 ft (1.3 m)	140G-J-FCX04
		6 ft (1.9 m)	140G-J-FCX06
		10 ft (3.0 m)	140G-J-FCX10
	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-J-FCS04
		6 ft (1.9 m)	140G-J-FCS06
		10 ft (3.0 m)	140G-J-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-J-FMX04
		6 ft (1.9 m)	140G-J-FMX06
		10 ft (3.0 m)	140G-J-FMX10
K	Non-metallic Handle, Type 1/3/12/4/4X	4 ft (1.3 m)	140G-K-FCX04
		6 ft (1.9 m)	140G-K-FCX06
		10 ft (3.0 m)	140G-K-FCX10
	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-K-FCS04
		6 ft (1.9 m)	140G-K-FCS06
		10 ft (3.0 m)	140G-K-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-K-FMX04
		6 ft (1.9 m)	140G-K-FMX06
		10 ft (3.0 m)	140G-K-FMX10
M	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-M-FCS04
		6 ft (1.9 m)	140G-M-FCS06
		10 ft (3.0 m)	140G-M-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-M-FMX04
		6 ft (1.9 m)	140G-M-FMX06
		10 ft (3.0 m)	140G-M-FMX10
N	Stainless Steel Handle, Type 4/4X	4 ft (1.3 m)	140G-N-FCS04
		6 ft (1.9 m)	140G-N-FCS06
		10 ft (3.0 m)	140G-N-FCS10
	Painted Metal Handle, Type 1/12	4 ft (1.3 m)	140G-N-FMX04
		6 ft (1.9 m)	140G-N-FMX06
		10 ft (3.0 m)	140G-N-FMX10

Bulletin 1494V Variable Depth Flange-Mounted Circuit Breaker Operating Mechanism



Components

Circuit Breaker Operating Mechanism

The mechanism listed must be combined with a connecting rod, operating handle, and a circuit breaker (supplied by customer) to obtain a functional device.

3-Pole Circuit Breaker ★			Operating Mechanism
Brand	Frame Size [A]	Frame Designation	Cat. No.
Allen-Bradley	125, 225, 250	140G-G, H, I, J	1494V-M70
Allen-Bradley	400	140G-K	1494V-M71
Allen-Bradley	800, 1200	140G-M, N	1494V-M72

★ Circuit breakers to be provided by customer.

Connecting Rods

Approximate dimensions are in inches (millimeters). Approximate dimensions are not intended for manufacturing purposes.

Circuit Breaker Frame Size [A]	Enclosure Depth		Cat. No.
	Minimum	Maximum	
125, 150, 250, 400, 600, 800, 1200	6-3/4 (172)	9-1/8 (232)	1494V-RA3
	6-3/4 (172)	21-5/8 (549)	1494V-RA4

Operating Handle


Handle Type	Description	Circuit Breaker Frame Size [A]	Operating Handle
			Cat. No.
Type 1, 3R, 4, 4X, 12	Nonmetallic	125, 150, 250, 400	1494F-P1
Type 1, 3R, 4, 12	Painted Metal	125, 150, 250, 400	1494F-M1
Type 4, 4X	Stainless Steel	125, 150, 250, 400	1494F-S1
Type 1, 3R, 4, 12	Painted Metal	800, 1200	1494F-M2
Type 4, 4X	Stainless Steel	800, 1200	1494F-S2

Auxiliary Contacts

Description	For Use With	Contact Type	Cat. No.
Auxiliary Contact Kit for Circuit Breakers (includes contacts and adapter)	125...1200 A Allen-Bradley Bul. 140G Circuit Breakers	1 N.O.	1495-N85
		1 N.C.	1495-N86

Bulletin 140G
Molded Case Circuit Breakers
Accessories

Additional Accessories

	Description	Frame Size	Cat. No.	
 Representative Photo	Trip Test Unit Padlockable Handle Block Padlocking Hasp Lock-OFF only	All	140G-ELTT	
		G, I	140G-G-PL	
		H, J	140G-H-PL	
		N	140G-N-PL	
		NS	140G-NS-PL	
		R	140G-R-PL	
 Representative Photo	Direct Mechanical Lock to Door	N, NS	140G-N-SINT	
	Description	Frame Size	3-Pole Cat. No.	4-Pole Cat. No.
 Representative Photo	Replacement Mounting Hardware Metric threads	G, I	★ 140G-G-MH3	‡ 140G-G-MH4
		H, J	—	★ 140G-H-MH4
		K	—	§ 140G-K-MH4
		M	—	§ 140G-M-MH4
		N, NS	—	§ 140G-N-MH4
 Representative Photo	DIN Rail Adapter Adapts to 35 mm DIN Rail	G	140G-G-DRA	140G-G-DRA4
		H, J	140G-H-DRA	
		I	140G-I-DRA	140G-I-DRA4
 Representative Photo	Escutcheon Plates Finish Frame with Marking provision window. For flush mounted (to door) MCCB applications.	G	140G-G-EP3	140G-G-EP4
		H	140G-H-EP3	140G-H-EP4
		I	140G-I-MH3	140G-I-MH4
		J	140G-J-MH3	140G-J-MH4
		K	140G-K-MH3	
		M	140G-M-MH3	
		N, NS	140G-N-MH3	
		R	140G-R-MH3	
 Representative Photo	IP54 Door protection Transparent plastic cover flush mounted to the enclosure door. Mounted on hinges and provided with a keyed lock.	N, NS	140G-N-BC12	
		R	140G-R-BC12	

- ★ Pkg. Qty. 2
‡ Pkg. Qty. 3
§ Pkg. Qty. 4

Replacement Parts

	Description	Frame Size	3-Pole Cat. No.	4-Pole Cat. No.
	 Replacement End Cap Kits End Caps are supplied as standard for G, H, I, J, K, M, N & NS frames. Provide connections for ring type or bolt-on terminals.	G	140G-G-ECM	140G-G-ECM4
		H	140G-H-ECM	140G-H-ECM4
		I	140G-I-ECM	140G-I-ECM4
		J	140G-J-ECM	140G-J-ECM4
		K	140G-K-ECM	140G-K-ECM4
		M	140G-M-ECM	140G-M-ECM4
		N	140G-N-ECM	140G-N-ECM4
		H	140G-H-BP3	140G-H-BP4
	 Insulators Supplied as standard for G, H, I, J, K, and M frames. Provide insulating barrier for MCCB applications, required for all applications with a $U_e > 440V$. Pkg Qty 10.	J	140G-J-BP3	140G-J-BP4
		K	140G-K-BP3	140G-K-BP4
		M	140G-M-BP3	140G-M-BP4

Molded Case Circuit Breakers

Specifications — G- and H-Frame

		G-Frame				H-Frame†					
Max. Rated Current	[A]	125		160★		125				160★	
Rated insulation voltage, U _i , IEC	[V]	800				1000					
NEMA, UL, CSA											
Interrupting Rating Code		G2	G3	G6	G2 G3 G6	H2	H3	H6	H0	H15	H2 H3 H6 H0 H15
240V AC, 50/60Hz	[kA]	50	65	100	50 65 100	65	100	150	200	200	65 100 150 200 200
480V AC, 50/60Hz	[kA]	25	35	65	25 35 65	25	35	65	100	150	25 35 65 100 150
600Y/347V AC, 50/60Hz	[kA]	10	14	25	10 14 25	—	—	—	—	—	—
600V AC, 50/60 Hz	[kA]	—	—	—	—	14	18	25	35	42	14 18 35 35 42
IEC 60947-2											
Rated ultimate short-circuit breaking capacity, I _{cu}											
220/230/240V AC, 50/60Hz	[kA]	65	85	100	65 85 100	65	85	100	150	200	65 85 100 150 200
380V AC, 50/60Hz	[kA]	36	50	70	36 60 70	36	50	70	120	150	26 50 70 120 150
415V AC, 50/60Hz	[kA]	36	50	70	36 50 70	36	50	70	120	150	36 50 70 120 150
440V AC, 50/60Hz	[kA]	36	50	65	36 50 65	36	50	65	100	150	36 50 65 100 150
500V AC, 50/60Hz	[kA]	30	36	50	36 50 65	30	36	50	60	70	30 36 50 60 70
525V AC, 50/60Hz	[kA]	22	35	35	22 35 35	20	25	30	36	50	20 25 30 36 50
690V AC, 50/60Hz	[kA]	6	8	10	6 8 10	10	12	15	18	20	10 12 15 18 20
250V DC, 2 Poles in Series	[kA]	36	50	70	36 50 70	36	50	70	85	100	36 50 70 85 100
500V DC, 2 Poles in Series	[kA]	—	—	—	—	—	—	—	—	—	—
500V DC, 3 Poles in Series	[kA]	36	50	70	36 50 70	36	50	70	85	100	36 50 70 85 100
750V DC, 3 Poles in Series	[kA]	—	—	—	—	—	—	—	—	—	—
Rated service short-circuit breaking capacity, I _{cs}											
220/230/240V AC, 50/60Hz	[kA]	75% (50)	75%	75%	75% 75% 75%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
380V AC, 50/60Hz	[kA]	100%	100%	75%	100% 100% 75%	100%	100% 100%	100%	100%	100%	100% 100% 100% 100% 100%
415V AC, 50/60Hz	[kA]	100%	75%	50%	100% 75% 50%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
440V AC, 50/60Hz	[kA]	50%	50%	50%	50% 50% 50%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
500V AC, 50/60Hz	[kA]	50%	50%	50%	50% 50% 50%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
525V AC, 50/60Hz	[kA]	50%	50%	50%	50% 50% 50%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
690V AC, 50/60Hz	[kA]	75%	50%	50%	75 50 50%	100%	100%	100%	75%	75%	100% 100% 100% 75% 75%
250V DC, 2 Poles in Series	[kA]	100%	100%	75%	100% 100% 75%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
500V DC, 2 Poles in Series	[kA]	—	—	—	—	—	—	—	—	—	—
500V DC, 3 Poles in Series	[kA]	100%	100%	75%	100% 100% 75%	100%	100%	100%	100%	100%	100% 100% 100% 100% 100%
750V DC, 3 Poles in Series	[kA]	—	—	—	—	—	—	—	—	—	—
Mechanical Life	[No. Ops]	25 000				25 000					
	[Ops/hr]	240				240					
Electrical Life @ 415V AC	[No. Ops]	8000				8000					
	[Ops/hr]	120				120					
Ambient Temp. w/out derating	°F [°C]	104 °F [40 °C]				104 °F [40 °C]					
Storage Temperature	°F [°C]	-40...+176 °F [-40...+80 °C]				-40...+176 °F [-40...+80 °C]					
Dimensions	[mm]	3 poles: 76.2x70x130				3 poles: 90x82.5x130					
[Width/Depth/Height]	[mm]	4 poles: 101.6x70x130				4 poles: 120x82.5x130					

★ IEC version with a 160 A I_{cu} rating

† Cannot be reverse fed above 480V




Bulletin 140G

Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame

Dimensions are in millimeters. Dimensions are not intended to be used for manufacturing purposes.


Panel Mounted Molded Case Circuit Breaker



- ± Overall dimensions of optional wiring ducts
- § Required 25 mm insulating phase barriers provided

Description	No. of Poles	A
With flange	3...4	74
Without flange	3...4	71
	3...4	79






DIN Rail Mounted Molded Case Circuit Breaker



- ★ Mounting bracket
- ± Overall dimensions of optional wiring ducts
- § Required 25 mm insulating phase barriers provided
- ♣ Optional front cover for DIN Rail

Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame


Drilling Template for Molded Case Circuit Breaker Mounting**Cat. Nos. 140G-G-ECM, -ECM4 Terminals**

- ★ Mounting bracket
- ◆ Required 25 mm insulating phase barriers provided

Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame

Cat. Nos. 140G-G-EXT3, -EXT4 Extended Terminals




✚ Extended terminals

§ Optional Terminal covers with IP40 protection provided

△ Required 100 mm insulating phase barriers provided

▽ Internal insulating plate required with phase barriers (customer provided) when mounted through the enclosure door


Cat. Nos. 140G-G-EXS3, -EXS4 Spreader Terminals




♣ Extended spread terminals for busbar connection

◆ Required 200 mm insulating phase barriers provided


Cat. Nos. 140G-G-TLC13, 140G-G-TLC14 Terminals (Copper Only Lug)




Cat. No. 140G-G-MTL63, -MTL64 Terminal (Multi-Cable Terminal Lug)



Cat. No. 140G-G-RMB or 140G-G-RMY Direct Rotary Operating Handle




Cat. Nos. 140G-G-RVM...Variable Depth Rotary Mechanism with Door Mounted Handle



Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame

Cat. No. 140G-G-EOP... Motor Operator




- ♣ Motor operator
- △ Door drilling template (without flange)
- ◆ Door drilling template (with flange)
- ♣ Cable connection
- ▽ Required 25 mm insulating phase barriers provided

Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame

Cat. No. 140G-G-ELP1603 Residual Current Release Module for 3-Pole Molded Case Circuit Breakers




Description	No. of Poles	A
With flange	3	74
Without flange	3	71

- ★ Terminals for busbar connection
- ‡ IP40 terminal covers
- § Drilling template — door with direct rotary mechanism and flange
- ¶ Drilling template — door with direct rotary mechanism, without flange
- △ Drilling template — molded case circuit breaker mounting on mounting plate

Molded Case Circuit Breakers

Approximate Dimensions — 125 A, G-Frame

Cat. No. 140G-G-ELP1604 Residual Current Release Module for 4-Pole Molded Case Circuit Breakers



Description	No. of Poles	A
With flange	4	74
Without flange	4	71

- ★ Terminals for busbar connection
- ‡ IP40 terminal covers
- § Drilling template — door with direct rotary mechanism and flange
- ⌘ Drilling template — door with direct rotary mechanism, without flange
- △ Drilling template — molded case circuit breaker mounting on mounting plate