











Connection Systems

## Cordsets and Patchcords, Mini Style

16 AWG, STOOW PVC

### Pinout and Color Code

Color Code	Face View Pinout									
	2-Pin		3-Pin		4-Pin		5-Pin		6-Pin	
										
A (US)	1 White 2 Black		1 Green 2 Black 3 White		1 Black 2 White	3 Red 4 Green	1 White 2 Red 3 Green	4 Orange 5 Black	1 White 2 Red 3 Green	4 Orange 5 Black 6 Blue
B (Auto)	—		1 Green 2 Red/Black Tr 3 Red/White Tr		1 Red/Black Tr 2 Red/White Tr	3 Red 4 Green	1 Red/White Tr 2 Red 3 Green 4 Red/Yellow Tr 5 Red/Black Tr		—	
C (IEC)	—		—		1 Black 2 Blue	3 Brown 4 White	1 Black 2 Blue 3 Orange	4 Brown 5 White	1 Blue 2 Orange 3 Red	4 White 5 Brown 6 Black

### Product Selection

#### Cordsets

Pin Count	Assembly Rating	Color Code	Cat. No.			
			Straight Female	Right Angle Female	Straight Male	Right Angle Male
2-Pin	600V 13A	A	889N-F2AFC-*F	889N-R2AFC-*F	889N-U2AFC-*F	889N-V2AFC-*F
3-Pin		A	889N-F3AFC-*F	889N-R3AFC-*F	889N-U3AFC-*F	889N-V3AFC-*F
		B	889N-F3AFA-*F	889N-R3AFA-*F	889N-U3AFA-*F	889N-V3AFA-*F
4-Pin	600V 10A	A	889N-F4AFC-*F	889N-R4AFC-*F	889N-U4AFC-*F	889N-V4AFC-*F
		B	889N-F4AFA-*F	889N-R4AFA-*F	889N-U4AFA-*F	889N-V4AFA-*F
		C	889N-F4AF-*F	889N-R4AF-*F	889N-U4AF-*F	889N-V4AF-*F
5-Pin	600V 8A	A	889N-F5AFC-*F	889N-R5AFC-*F	889N-U5AFC-*F	889N-V5AFC-*F
		B	889N-F5AFA-*F	889N-R5AFA-*F	889N-U5AFA-*F	889N-V5AFA-*F
		C	889N-F5AF-*F	889N-R5AF-*F	889N-U5AF-*F	889N-V5AF-*F
6-Pin		C	889N-F6AFC-*F	889N-R6AFC-*F	889N-U6AFC-*F	889N-V6AFC-*F
		A	889N-F6AF-*F	889N-R6AF-*F	889N-U6AF-*F	889N-V6AF-*F

#### Patchcords

Pin Count	Assembly Rating	Cat. No.			
		Straight Female Straight Male	Straight Female Right Angle Male	Right Angle Female Straight Male	Right Angle Female Right Angle Male
2-Pin	16 AWG 600V 13 A	889N-F2AFNU-‡F	889N-F2AFNV-‡F	889N-R2AFNU-‡F	889N-R2AFNV-‡F
3-Pin		889N-F3AFNU-‡F	889N-F3AFNV-‡F	889N-R3AFNU-‡F	889N-R3AFNV-‡F
4-Pin	16 AWG 600V 10 A	889N-F4AFNU-‡F	889N-F4AFNV-‡F	889N-R4AFNU-‡F	889N-R4AFNV-‡F
5-Pin	16 AWG 600V 8 A	889N-F5AFNU-‡F	889N-F5AFNV-‡F	889N-R5AFNU-‡F	889N-R5AFNV-‡F
6-Pin		889N-F6AFNU-‡F	889N-F6AFNV-‡F	889N-R6AFNU-‡F	889N-R6AFNV-‡F

\* Replace symbol with 6 (6 ft), 12 (12 ft), or 20 (20 ft) for standard cable lengths.

‡ Replace symbol with 3 (3 ft), 6 (6 ft), 12 (12 ft), or 20 (20 ft) for standard cable lengths.

**Note:** Stainless steel connector versions may be ordered by adding an "S" to the bulletin number, e.g., 889NS-F3AFC-\*F.