






30.5 mm Push Buttons

Type 4/4X/13, Corrosion-Resistant/Watertight/Oiltight

Modifications and Accessories, Continued**Guards**

 <i>Protective Ring for 2-Position Push-Pull</i> <i>Cat. No. 800T-N310 and 800T-NX1320</i>	Description	Type of Finish	Cat. No.
	Protective Guard For Bulletin 800H 2-position push-pull illuminated or non-illuminated operators. Often used to avoid unintentional tripping of E-stop operators. Available for standard size operators (40 mm diameter).	Stainless Steel	800T-N310
		Black	800T-NX1320
 <i>Illuminated Push Button Unit with</i> <i>Cat. No. 800H-N152 Guard</i>	Description	Cat. No.	
	Illuminated Push Button Guard The guard provides additional protection against accidental operation of the push button unit. 1-1/2" (38.1 mm) guard for illumination units.	800H-N152	
 <i>Protective Ring for 2-Position Push-Pull</i> <i>Cat. No. 800T-N310J</i>	Jumbo Protected Guard Protective ring for 800T 2-position push-pull operators. Illuminated or non-illuminated. Often used to avoid unintentional tripping of E-stop operators. This guard is used with jumbo size cap (60 mm dia.)	800T-N310J	
 <i>Ramp Guard</i> <i>Cat. No. 800T-N339</i>	Ramp Guard For Bulletin 800T/800H 2- and 3-position illuminated and non-illuminated push-pull units. Standard size cap only. See page 10-55 for dimensions.	800T-N339	
 <i>Stainless Steel Guard</i> <i>Cat. No. 800H-N153</i>	Stainless Steel Guard Used on non-illuminated push buttons that have protective boots as shown on page 10-89.	800H-N153	