



1492-WTF3...

1492-WTS3...

Dimensions are not intended to be used for manufacturing purposes.

**Note:** Height dimension is measured from top of rail to top of terminal block.



| Specifications                   | Three-circuit terminal block.                                                     |            |                          | Three-level sensor block.                                                           |            |                           |
|----------------------------------|-----------------------------------------------------------------------------------|------------|--------------------------|-------------------------------------------------------------------------------------|------------|---------------------------|
| Certifications                   |  | <b>CSA</b> | <b>IEC</b>               |  | <b>CSA</b> | <b>IEC</b>                |
| Voltage Rating                   | 300V AC/DC                                                                        |            | 250V AC/DC               | 300V AC/DC                                                                          |            | 250V AC/DC                |
| Maximum Current                  | 10 A                                                                              |            | 24 A                     | 10 A                                                                                |            | 24 A                      |
| Wire Range (Rated Cross Section) | #26...14 AWG                                                                      |            | 0.5...2.5mm <sup>2</sup> | #26...14 AWG                                                                        |            | 0.5...2.5 mm <sup>2</sup> |
| Recommended Tightening Torque    | 4.2...4.6 lb•in (0.5 N•m)                                                         |            |                          | 4.2...4.6 lb•in (0.5 N•m)                                                           |            |                           |
| Density                          | 60 pcs/ft (197 pcs/m)                                                             |            |                          | 60 pcs/ft (197 pcs/m)                                                               |            |                           |
| Housing Temperature Range        | -40...+195 °F (-40...+90 °C)                                                      |            |                          | -40...+195 °F (-40...+90 °C)                                                        |            |                           |
| Indicator Type<br>WTF3/WTS3      | No indicator                                                                      |            |                          | No indicator                                                                        |            |                           |
| WTF3LP/WTS3LP                    | Red LED for PNP devices (10...50V)                                                |            |                          | Red LED for PNP devices (10...50V)                                                  |            |                           |
| WTF3LN/WTS3LN                    | Red LED for NPN devices (10...50V)                                                |            |                          | Red LED for NPN devices (10...50V)                                                  |            |                           |
| Leakage Current<br>WTF3/WTS3     | —                                                                                 |            |                          | —                                                                                   |            |                           |
| WTF3LP/WTS3LP                    | 2.69 mA @ 50V                                                                     |            |                          | 2.69 mA @ 50V                                                                       |            |                           |
| WTF3LN/WTS3LN                    | 2.69 mA @ 50V                                                                     |            |                          | 2.69 mA @ 50V                                                                       |            |                           |
| Wire Strip Length                | 0.31 in. (8 mm)                                                                   |            |                          | 0.31 in. (8 mm)                                                                     |            |                           |
| Short-Circuit Current Rating     | See page 12-42                                                                    |            |                          |                                                                                     |            |                           |

| Terminal Blocks                     |                      | Cat. No.                    | Pkg Qty. | Cat. No.                    | Pkg Qty. |
|-------------------------------------|----------------------|-----------------------------|----------|-----------------------------|----------|
| Color:                              | Grey                 | <b>1492-WTF3</b>            | 50       | <b>1492-WTS3</b>            | 50       |
|                                     | Blue                 | —                           | —        | <b>1492-WTS3-B</b>          | 50       |
|                                     | Grey for PNP devices | <b>1492-WTF3LP</b>          | 50       | <b>1492-WTS3LP</b>          | 50       |
|                                     | Grey for NPN devices | 1492-WTF3LN                 | 50       | <b>1492-WTS3LN</b>          | 50       |
| Accessories                         |                      | Cat. No.                    | Pkg Qty. | Cat. No.                    | Pkg Qty. |
| Mounting Rails:                     |                      |                             |          |                             |          |
| 1 m Symmetrical DIN (Steel)         |                      | <b>199-DR1</b>              | 10       | <b>199-DR1</b>              | 10       |
| 1 m Symmetrical DIN (Aluminum)      |                      | <b>1492-DR5</b>             | 10       | <b>1492-DR5</b>             | 10       |
| 1 m Hi-Rise Sym. DIN (Aluminum)     |                      | <b>1492-DR6</b>             | 2        | <b>1492-DR6</b>             | 2        |
| 1 m Angled Hi-Rise Sym. DIN (Steel) |                      | <b>1492-DR7</b>             | 2        | <b>1492-DR7</b>             | 2        |
| End Barrier                         |                      | <b>1492-EBTF3</b>           | 50       | <b>1492-EBTS3</b>           | 50       |
| End Anchors and Retainers:          |                      |                             |          |                             |          |
| Screwless End Retainer              |                      | <b>1492-ERL35</b>           | 20       | <b>1492-ERL35</b>           | 20       |
| DIN Rail — Normal Duty              |                      | <b>1492-EAJ35</b>           | 100      | <b>1492-EAJ35</b>           | 100      |
| DIN Rail — Heavy Duty               |                      | <b>1492-EAHJ35</b>          | 50       | <b>1492-EAHJ35</b>          | 50       |
| Jumpers:                            |                      |                             |          |                             |          |
| Center Jumper — 50-pole             |                      | <b>1492-CJT5-50</b>         | 5        | <b>1492-CJT5-50</b>         | 5        |
| Center Jumper — 10-pole             |                      | <b>1492-CJT5-10</b>         | 10       | <b>1492-CJT5-10</b>         | 10       |
| Center Jumper — 3-pole              |                      | 1492-CJT5-3                 | 10       | 1492-CJT5-3                 | 10       |
| Center Jumper — 2-pole              |                      | <b>1492-CJT5-2</b>          | 10       | <b>1492-CJT5-2</b>          | 10       |
| Center Jumper Link                  |                      | <b>1492-CJL5</b>            | 10       | <b>1492-CJL5</b>            | 10       |
| Center Jumper Cover — Red           |                      | <b>1492-CJCR5</b>           | 10       | <b>1492-CJCR5</b>           | 10       |
| Center Jumper Cover — Blue          |                      | <b>1492-CJCB5</b>           | 10       | <b>1492-CJCB5</b>           | 10       |
| Side — 20-pole Insulated Red        |                      | <b>1492-SJT5-20-R</b>       | 10       | <b>1492-SJT5-20-R</b>       | 10       |
| Side — 20-pole Insulated Blue       |                      | <b>1492-SJT5-20-B</b>       | 10       | <b>1492-SJT5-20-B</b>       | 10       |
| Other Accessories:                  |                      |                             |          |                             |          |
| Partition Plate                     |                      | <b>1492-PPTS3</b>           | 50       | <b>1492-PPTS3</b>           | 50       |
| Test Plug Adapter                   |                      | <b>1492-TA285</b>           | 10       | <b>1492-TA285</b>           | 10       |
| Electrical Warning Plate            | 4-Pole               | 1492-EWP5-4                 | 10       | 1492-EWP5-4                 | 10       |
|                                     | 1-Pole               | 1492-EWP5                   | 10       | 1492-EWP5                   | 10       |
| Marking Systems:                    |                      |                             |          |                             |          |
| Snap-in Marker Card                 |                      | <b>1492-MS5X9</b> (80/card) | 5        | <b>1492-MS5X9</b> (80/card) | 5        |