



## 140MT MPCBs and MCPs

### [140MT-D9E-B25](#)

MPCB, Standard Magnetic Trip (Fixed at 14 x Ie), for C36..C40 (12 x Ie), 1.6 - 2.5 A, High Performance, Frame Size D

### Product Details

| SYSTEM VOLTAGE DATA                              |   |
|--|---|
| Supply Voltage                                   | 480V 60Hz   |
| Maximum Available Fault Current (at the Breaker) | 0 kA  |
| CIRCUIT BREAKER                                  |   |
| Circuit Breaker Type                             | Motor Protection Circuit Breaker                                  |
| Adj. Thermal Current Range (A)                   | 1.6 - 2.5A  |
| Frame Size                                       | Frame Size D  |
| Breaking Capacity                                | High Breaking Capacity  |
| Application                                      | Standard Magnetic Trip (Fixed at 14 x Ie), for C36..C40 (12 x Ie) |
| ASSEMBLY   |   |
| Factory or User Assembled?                       | Factory Assembled   |
| OPTIONS  |   |
| Side Mount Shunt Trip and Undervoltage Release   | None  |
| Front Mount Auxiliary and Trip Contacts          | None  |
| Side Mount Auxiliary and Trip Contacts           | None  |

### Supporting Documentation and Downloads

- [Installation Instructions](#)