



1492-15T

1492-25T

Dimensions are not intended to be used for manufacturing purposes.



Specifications

High temperature 1-pole panel mount block, wire clamp. Gangable for multi-pole installation.

High temperature 1-pole panel mount block, wire clamp. Gangable for multi-pole installation.

Voltage Rating	600V AC/DC		600V AC/DC	
Maximum Current (per pole)	35 A		45 A	
Wire Range (Rated Cross Section)	#16...#12 AWG (1.5...4 mm ²)		#16...#10 AWG (1.5...6 mm ²)	
Wire Strip Length	0.38" (9.7 mm)		0.38" (9.7 mm)	
Recommended Tightening Torque	10...16 lb-in. (1.1...1.8 Nm)		10...16 lb-in. (1.1...1.8 Nm)	
Insulation Temperature Range	-40...+300°F (-40...+149°C)		-40...+300°F (-40...+149°C)	
Terminal Blocks	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Terminal Block	1492-15T	100	1492-25T	100
Accessories (page 185)	Cat. No.	Pcs./ Pkg.	Cat. No.	Pcs./ Pkg.
Anchor Unit: (required every 12th block)	1492-15A	10	1492-25A	10
End Piece	1492-15E	25	1492-25E	25