


Power Modules


Packaged in kit form for field installation. Lamps are listed on page 10-45.



Full Voltage Power Module  
Cat. No. 800T-N330



Transformer Power Module  
Cat. No. 800T-N326



Dual Input Power Modules  
Cat. No. 800T-N296 (Transformer)  
Cat. No. 800T-N290N (Diode)


| Full Voltage§  |           | Transformer§     |            | Dual Input   |            |            |
|----------------|-----------|------------------|------------|--------------|------------|------------|
| Lamp Voltage   | Cat. No.  | Voltage          | Cat. No.   | Type         | Voltage    | Cat. No.   |
| 6...130V AC/DC | 800T-N330 | 48V AC 50/60 Hz  | 800T-N325  | Transformer* | 120V AC    | 800T-N296  |
|                |           | 120V AC 50/60 Hz | 800T-N326  | Diode Type*  | 24V AC/DC  | 800T-N291N |
|                |           | 240V AC 50/60 Hz | 800T-N327  |              | 120V AC/DC | 800T-N290N |
|                |           | 277V AC 50/60 Hz | 800T-N327Y |              | —          | —          |
|                |           | 480V AC 50/60 Hz | 800T-N328  | —            | —          | —          |
| 240V AC/DC‡    | 800T-N331 | 600V AC 50/60 Hz | 800T-N329  | —            | —          | —          |

\* Transformer type dual input provides circuit isolation via a miniature type relay. This module is used in conjunction with a 120V transformer.


\* Diode type dual input provides circuit isolation via opposing diodes. Not recommended for use with solid-state outputs and neon indicators.

‡ 240V full voltage module contains 50% dropping resistors for use with a 120V incandescent lamp.

§ Specify Bulletin 800TC for finger-safe power modules. Example: Cat. No. 800T-N330 becomes Cat. No. 800TC-N330.



Resistor Power Module  
Cat. No. 800T-N332



Neon Power Module  
Cat. No. 800T-N333

| Resistor (10% Drop)➤ |           | Neon➤      |           |
|----------------------|-----------|------------|-----------|
| Voltage              | Cat. No.  | Voltage    | Cat. No.  |
| 120V AC/DC           | 800T-N332 | 120V AC/DC | 800T-N333 |
|                      |           | 240V AC/DC | 800T-N334 |

➤ Neon modules contain resistors.

➤ Specify Bulletin 800TC for finger-safe power modules. Example: Cat. No. 800T-N332 becomes Cat. No. 800TC-N332.

Universal LED Module



| Voltage         | Cat. No.   |
|-----------------|------------|
| 12...130V AC/DC | 800TC-N374 |

Trigger Action E-Stop Latches



Cat. No. 800T-N380



Cat. No. 800T-N379

| Description          | Cat. No.  |
|----------------------|-----------|
| Illuminated type     | 800T-N380 |
| Non-illuminated type | 800T-N379 |