




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L6				1492-L6T				1492-L10				
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.													
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block				
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX	
Voltage Rating	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	600V AC/DC			800V AC/DC	
Maximum Current	50 A			41 A	50 A			41 A	60 A			55 A	
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	#16...6 AWG		10 mm ²	10 mm ² (16...8 AWG)	
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)				
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft(123 pcs/m)				30 pcs/ft (99 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-78												
Terminal Blocks	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Color	Grey			1492-L6	50	1492-L6T			50	1492-L10			25
	Red			1492-L6-RE	50	1492-L6T-RE			50	1492-L10-RE			25
	Blue			1492-L6-B	50	1492-L6T-B			50	1492-L10-B			25
	Black			1492-L6-BL	50	1492-L6T-BL			50	1492-L10-BL			25
	Green			1492-L6-G	50	1492-L6T-G			50	1492-L10-G			25
	Yellow			1492-L6-Y	50	1492-L6T-Y			50	1492-L10-Y			25
	Orange			1492-L6-OR	50	1492-L6T-OR			50	1492-L10-OR			25
	Brown			1492-L6-BR	50	1492-L6T-BR			50	1492-L10-BR			25
	White			1492-L6-W	50	1492-L6T-W			50	1492-L10-W			25
Accessories	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	Cat. No.			Pkg Qty.	
Mounting Rails													
1 m Symmetrical DIN (Steel)	199-DR1			10	199-DR1			10	199-DR1			10	
1 m Symmetrical DIN (Aluminum)	1492-DR5			10	1492-DR5			10	1492-DR5			10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6			2	1492-DR6			2	1492-DR6			2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7			2	1492-DR7			2	1492-DR7			2	
End Barriers	Grey	1492-EBL6		50	Grey	1492-EBL6T		50	Grey	1492-EBL10		20	
	Blue	1492-EBL6-B		50	Blue	1492-EBL6T-B		50	Blue	1492-EBL10-B		20	
	Yellow	1492-EBL6-Y		50	Yellow	1492-EBL6T-Y		50	Yellow	1492-EBL10-Y		20	
End Anchors and Retainers													
Screwless End Retainer	1492-ERL35			20	1492-ERL35			20	1492-ERL35			20	
DIN Rail — Normal Duty	1492-EAJ35			100	1492-EAJ35			100	1492-EAJ35			100	
DIN Rail — Heavy Duty	1492-EAHJ35			50	1492-EAHJ35			50	1492-EAHJ35			50	
Jumpers													
Plug-in Center Jumper — 32-Pole	1492-CJL8-32			10	1492-CJL8-32			10	—			—	
Plug-in Center Jumper — 4-Pole	1492-CJL8-4			60	1492-CJL8-4			60	—			—	
Plug-in Center Jumper — 3-Pole	1492-CJL8-3			60	1492-CJL8-3			60	—			—	
Plug-in Center Jumper — 2-Pole	1492-CJL8-2			60	1492-CJL8-2			60	1492-CJL10-2			25	
Other Accessories													
Test Plug	—			—	—			—	1492-TP23			20	
Test Plug (Stackable)	1492-TPL8			25	1492-TPL8			25	—			—	
Electrical Warning Plate	1492-EWPL8			20	1492-EWPL8			20	1492-EWPL10			20	
Marking Systems													
Snap-In Marker Cards*	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	1492-M6X12 (120/card)			5	
Snap-In Marker Cards	1492-MR8X12 (84/card)			5	1492-M8X5 (160/card)			5	1492-M8X5 (160/card)			5	
Hinged Marker Cards	1492-MH6X12 (80/card)			5	1492-MH6X12 (80/card)			5	1492-MH5X15 (96/card)			5	

* May only be mounted in terminal block corner marking positions.