

Product Selection

Operator Type	Contact			Typical Force/Torque to Operate	Panel Mount	Contact Opening Characteristics □ Open ■ Closed ⊕ Positive Opening Point	Cat. No.	
	Safety	Auxiliary	Type				Bottom Cable Style	Side Cable Style
Roller Plunger	1 N.C.	1 N.O.	Snap Acting	10 (2.25)	No		440P-ARPS11C	440P-ARPS11CS
					Yes		440P-ARP1S11C	440P-ARP1S11CS
Dome Plunger	1 N.C.	1 N.O.	Snap Acting	10 (2.25)	No		440P-ADPS11C	440P-ADPS11CS
					Yes		440P-ADP1S11C	440P-ADP1S11CS
Cross Roller Plunger	1 N.C.	1 N.O.	Snap Acting	10 (2.25)	No		440P-ACRS11C	440P-ACRS11CS
					Yes		440P-ACR1S11C	440P-ACR1S11CS
Lever	1 N.C.	1 N.O.	Snap Acting	0.7 N•m (0.62 lb•in)	—		440P-ASLS11C	440P-ASLS11CS


Approximate Dimensions [mm (in.)]

Dimensions are not intended to be used for installation purposes.


	Nonpanel Mount	Panel Mount
Dome Plunger		
Roller Plunger		
Cross Roller Plunger		
Lever Type		

- Side cable style shows strain relief only. Units include a 2 m integral cable.
- Bottom cable style units have same dimensions as side cable style.
- Panel mount clearance hole = 13 mm (0.51 in.)

Countersink Hole



Typical Wiring Diagrams



Safety Switches

IEC Style Switches

22 mm Compact Metal Position Switches



Description

The 22 mm IEC style metal safety limit switches have been developed to provide a small metal case with a choice of actuator heads. All units are supplied with an integral 2 m cable. For safety applications it is important that upon actuation, the guard or other moving objects should not pass completely over the switch and allow the plunger or lever to return to its original position.

Features

- Rugged die cast enclosure
- Positive operation, forced disconnection of contacts (direct opening action)
- Snap-acting contact actuation
- Contacts 1 N.C. + 1 N.O.
- Pre-wired 2 m cable, bottom or side exit

Specifications

Safety Ratings						
Standards		EN 954-1, ISO 13849-1, IEC/EN 60204-1, NFPA 79, EN 1088, ISO 14119, IEC/EN 60947-5-1, ANSI B11.19, AS 4024.1				
Safety Classification		Cat. 1 Device per EN 954-1 Dual channel limit switch suitable for Cat. 3 or 4 systems when ganged together				
Certifications		UL Recognized, TÜV and CE Marked for all applicable directives				
Outputs						
Safety Contacts ❄		1 N.C. snap acting				
Auxiliary Contacts		1 N.O. snap acting				
Thermal Current		10 A				
Rated Insulation Voltage		300V AC				
Contact Rating						
Maximum AC Contact Rating Per Pole						
NEMA Rating	Max. Voltage	Amperes		Continuous Carrying Current (Amp.)	Volt Amperes	
		Make	Break		Make	Break
AC15/B300	120	30	3.0	5	3600	360
AC15/B300	240	15	1.5			
Maximum DC Contact Rating Per Pole						
DC13/Q300	240	0.27	0.27	2.5	69	69
Operating Characteristics						
Actuation Speed, Max.		250 mm/s				
Actuation Speed, Min.		100 mm/min				
Actuation Frequency, Max.		6000 operations per hr				
Mechanical Life		1 x 10 ⁷				
Environmental						
Enclosure Type Rating		NEMA 1, IP66/67				
Operating Temperature [C (F)]		2...70 ° (35.6...158 °)				
Pollution Degree		3				
Physical Characteristics						
Housing Material		Die-cast alloy				
Actuator Material		Various polymers and metals				
Mounting		2 x M14, any position				
Vibration		IEC 68-2-6 (10...55 Hz, 0.35 mm amplitude)				
Shock		IEC 68-2-7 (30 Gn 3 pulses per axis)				
Connection Type		2 m (6.5 ft) cable				
Color		Red body/black head				

* The safety contacts are described as normally closed (N.C.) i.e., with the guard closed, actuator in place (where relevant) and the machine able to be started.