

Color	Handles (Includes Legend Plate and Control Knob)			
Red/Yellow (Emergency Stop colors)	 <i>Type I (IP66, UL Type 3/3R/12)</i>	 <i>Type L (IP66, UL Type 3/3R/12) With Locking For One Padlock (Padlock Not Included)</i>	 <i>Type N (IP66, UL Type 3/3R/12)</i> S	Bulletin 194L handles are available in both screw fixing and 22.5 mm mounting hole style.
Black/Grey (Standard Operation colors)	 <i>Type A (IP66, UL Type 3/3R/12)</i>	 <i>Type E (IP66, UL Type 3/3R/12) With Locking For One Padlock (Padlock Not Included)</i>	 <i>Type G (IP66, UL Type 3/3R/12)</i> S	 <i>Type S (IP66, UL Type 3/3R/12)</i>

Cat. No.	Explanation
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

194L - HE 6 N - 175

Frequently Ordered 194L Handles — OFF-ON Base/Front-Mounted 3- and 6-Pole Switch Handles
(Switch Body listed on page 2-405)

Handle Type	Degree of Protection	Handle Color	Bezel Plate Size	For Use With	Legend Plate Marking	Cat. No.
E	IP66 (UL Type 1) (UL Type 3/3R/12)	Black/Grey	48 x 48 mm (1-57/64 x 1-57/64 in.)	194E-16...63 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	0-1	194L-HE4E-175
L		Red/Yellow	48 x 48 mm (1-57/64 x 1-57/64 in.)	194E-16...63 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	OFF-ON	194L-HE4E-175I
G		Black/Grey	54 x 54 mm (2-1/8 x 2-1/8 in.)	194E-16 A	0-1 OFF-ON	194L-HE4L-175
			67 x 67 mm (2-41/64 x 2-41/64 in.)	194E-25...100 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	0-1 OFF-ON	194L-HE4L-175
	88 x 88 mm (3-15/32 x 3-15/32 in.)		194E-40...100 A	0-1 OFF-ON	194L-HE8G-175	
N	IP66 (UL Type 3/3R/12)	Red/Yellow	54 x 54 mm (2-1/8 x 2-1/8 in.)	194E-16 A	0-1 OFF-ON	194L-HE4N-175
			67 x 67 mm (2-41/64 x 2-41/64 in.)	194E-25...100 A 194L-E12...40 A, -1753 194L-A12...40 A, -1753	0-1 OFF-ON	194L-HE6N-175
			88 x 88 mm (3-15/32 x 3-15/32 in.)	194E-40...100 A	0-1 OFF-ON	194L-HE8N-175
L	IP66 (UL Type 3/3R/12)	Red/Yellow	48 x 48 mm (1-57/64 x 1-57/64 in.)	194L-E12...40 A, -1753	0-1	194L-HC4L-175
					OFF-ON	194L-HC4L-175I