

Bulletin 800F
22.5 mm Push Buttons
Product Selection, Continued

3-Position Push-Pull Operators, Illuminated & Non-Illuminated — Mushroom



Illuminated 3-Position Push-Pull
Cat. No. 800FM-LMP44E3

Target Table and Operator Position*			
Contact Type			
	Out	Center	In
N.O.	O	O	X
N.C.E.B.	X	O	O
N.C.L.B.	X	X	O

Note: X = Closed/O = Open

Operator Function	Operator Type	Color	Cat. No.	Pkg. Quantity
Momentary Out, Maintained Center, Momentary In	Illuminated*	Amber‡	800FM-LMM40-E3	1
		Green	800FM-LMM43-E3	
		Red	800FM-LMM44-E3	
		Blue‡	800FM-LMM46-E3	
		Clear‡	800FM-LMM47-E3	
	Non-Illuminated	Black§	800FM-MM42-E3	
		Green	800FM-MM43-E3	
		Red	800FM-MM44-E3	
Momentary Out, Maintained Center, Maintained In	Illuminated*	Amber‡	800FM-LMP40-E3	1
		Green	800FM-LMP43-E3	
		Red	800FM-LMP44-E3	
		Blue‡	800FM-LMP46-E3	
		Clear‡	800FM-LMP47-E3	
	Non-Illuminated	Black§	800FM-MP42-E3	
		Green	800FM-MP43-E3	
		Red	800FM-MP44-E3	

800F **M** – **L** **MM** **4** **4** **E3**
 a b c d e f

a

Operator Construction	
Code	Description
M	Round metal operator (IP66, Type 4/13)

b

Operator Type	
Code	Description
L	Illuminated*
Blank	Non-Illuminated

c

Operator Function	
Code	Description
MM	Momentary Out, Maintained Center, Momentary In
MP	Momentary Out, Maintained Center, Maintained In

d

Cap Size	
Code	Description
4	40 mm Plastic

e

Cap Color	
Code	Description
0	Amber‡
2	Black§
3	Green
4	Red
6	Blue‡
7	Clear‡

f

Positions	
Code	Description
E3	3-Position

* Cannot use N.C. or N.O.E.M. contact blocks with 3-position push-pull operators. Must use N.O., N.C.E.B., or N.C.L.B. contact blocks.
* Available in integrated LED version only.
‡ Available in illuminated only.
§ Available in non-illuminated only.