





Bulletin 700-HG Power Relay

Product Selection

Power Relay with Screw Terminals #6-32 for Coil, #8-32 for Contacts

	Description SPST-NO-DM 1 Form X AgCdO Contacts	Contact Ratings 40 A (A600)	Wiring Diagrams 	Coil Voltage 24V AC 120V AC 240V AC 277V AC 480V AC 12V DC 24V DC 48V DC 110V DC	Cat. No.* ‡ 700-HG45A24 700-HG45A1 700-HG45A2 700-HG45A27 700-HG45A4 700-HG45Z12 700-HG45Z24 700-HG45Z48 700-HG45Z1
SPST-NO-DM					
	Description SPDT 1-pole 1 Form C AgCdO Contacts	Contact Ratings 40 A (A600)	Wiring Diagrams 	24V AC 120V AC 240V AC 12V DC 24V DC 48V DC 110V DC	700-HG46A24 700-HG46A1 700-HG46A2 700-HG46Z12 700-HG46Z24 700-HG46Z48 700-HG46Z1
SPDT					
	Description DPST-NO 2-pole 2 Form A AgCdO Contacts	Contact Ratings 40 A (A600)	Wiring Diagrams 	24V AC 120V AC 240V AC 480V AC 12V DC 24V DC 48V DC 110V DC	700-HG47A24 700-HG47A1 700-HG47A2 700-HG47A4 700-HG47Z12 700-HG47Z24 700-HG47Z48 700-HG47Z1
DPST-NO					
	Description DPDT 2-pole 2 Form C AgCdO Contacts	Contact Ratings 40 A (A600)	Wiring Diagrams 	24V AC 120V AC 240V AC 277 AC 12V DC 24V DC 48V DC 110V DC 220V DC 250V DC	700-HG42A24 700-HG42A1 700-HG42A2 700-HG42A27 700-HG42Z12 700-HG42Z24 700-HG42Z48 700-HG42Z1 700-HG42Z2 700-HG42Z25
DPDT					

* Auxiliary Snap Switch Option: Add suffix (-5) to the selected Bulletin 700-HG relay Cat. No., except for the 220V DC add (-5L).

‡ Magnetic Blowout Option: Add suffix (-6) to the selected Bulletin 700-HG relay Cat. No. (suppresses the arc when switching DC loads - ratings listed below).

Auxiliary Snap Action Switch

Contact	Material	Rating	Dielectric Withstand V (1 Min.)
SPDT (1 Form C)	Silver Cad. Ox.	10 A at 120 or 240 Resistive	1500V AC RMS Contact to Frame

Specifications