22.5 mm Monolithic Push Buttons

Product Overview/Selection



Bulletin 800FD Monolithic Push Buttons

With a single catalog number, you can now order a fully assembled product for easy stocking and installation. Designed to meet worldwide standards, the Bul. 800FD monolithic line includes Estops and pilot lights with either LED or incandescent options.

- · Ease of installation
- Low back-of-panel profile (45.7 mm)
- Aesthetic design complements the Bul. 800F modular line
- Anti-rotation tab provides accurate alignment and can be easily removed for use in panels without notches
- · Lowest cost of installation
- Made of industrial-grade thermoplastic for superior chemical resistance
- Designed to meet worldwide standards
- Compatible with Bul. 800F accessories and enclosures
- · Ring lug capability

Table of Contents

Push Buttons this page
Pilot Lights 10-141
Selector Switches 10-142
Mushroom/E-Stops 10-142
Accessories 10-143
Specifications 10-144
Approximate
Dimensions 10-145

Product Selection

Momentary Push Button Operators, Non-Illuminated



			Contact Configuration		
			1 N.O.	1 N.C.	1 N.O. & 1 N.C.
Operator Type	Cap Color	Pkg. Quantity	Cat. No.	Cat. No.	Cat. No.
	Black	1	800FD-F2X10	800FD-F2X01	800FD-F2X11
Flush	Green		800FD-F3X10	800FD-F3X01	800FD-F3X11
	Red		800FD-F4X10	800FD-F4X01	800FD-F4X11

800FD - $\frac{F}{a}$ $\frac{3}{b}$ $\frac{01}{c}$ $\frac{X}{d}$ $\frac{11}{e}$

a

	Operator Type
Code Description F Flush	

b

	~
	Color Cap
Code	Color
1	White
2	Black
3	Green
4	Red
5	Yellow
6	Blue

C

Legend Text∗∜			
Code	de Text		
_	No text (blank)		
01	START		
02	STOP		
05	0		
06	I		
08	\rightarrow		
09	FORWARD		
10	REVERSE		
11	R		

- * White and yellow caps have black text. All other color caps have white text.
- Valid color cap/legend text combinations are as follows:

d
Termination Style

Description

Standard screw

Ring lug

0

е			
	Contact Module		
Code	Number of N.O.	Number of N.C.	
01	0	1	
10	1	0	
11	1	1	
02	0	2	

	Text		
Color	Flush Caps	Extended Caps	
White	START, I, \rightarrow , FORWARD, REVERSE, R	→ , R	
Black	→, FORWARD, REVERSE, R	STOP, O,→, R‡	
Green	START, I, \rightarrow , FORWARD, REVERSE	\rightarrow	
Red	→, FORWARD, REVERSE	STOP, O,→‡	
Yellow	→, FORWARD, REVERSE	\rightarrow	
Blue	→, FORWARD, REVERSE, R	→ , R	

Code

Χ

R

20

^{‡ &}quot;STOP" or "O" color cap/legend text are not available for "10" or "20" contact modules.

