

Bulletin 800F 22.5 Mm Push Buttons

Introduction	Standards Compliance and Certifications	Quick Selection	Momentary Push Button Operators	Alternate Action Operators	Pilot Light Operators	
Selector Switch Operators	Key-Operated Selector Switch Operators	Emergency Stop Operators	Momentary Mushroom Operators	Multi-Function Operators	Reset Operators	
Single Turn Potentiometer	Selector Push Button Operators	Toggle Switch Operators	Back-of-Panel Components	Plastic and Metal Enclosures	Assembled Stations	
Pendant Stations	Accessories	Legend Plates	Specifications	Approximate Dimensions		

Plastic and Metal Enclosures

Plastic Enclosures (Latch or Base Mounting)

- Accepts two-piece snap-in legends
- One-hole enclosure accepts 60 mm emergency stop legends
- UL Listed, CSA Certified



Plastic Enclosure
Cat. No. 800F-3PM



Metal Enclosure
Cat. No. 800F-5MM

Metal Enclosures (Latch or Base Mounting)

- Feed-through design
- Accepts two-piece snap-in legends
- Includes base mount adapter

Type	Pkg. Quantity	Enclosures							
		Plastic (IP66, 4/4X)				Metal – Die Cast (IP66, 4/13)‡			
		PG Conduit Knockouts		Metric Conduit Knockouts		PG Conduit Openings		Metric Conduit Openings	
		Cat. No.		Cat. No.		Cat. No.		Cat. No.	
1-hole	1	* \$	800F-1PP	* \$	800F-1PM	Δ	800F-1MP	Δ	800F-1MM
2-hole		* \$	800F-2PP	* \$	800F-2PM	Δ	800F-2MP	Δ	800F-2MM
3-hole		* \$	800F-3PP	* \$	800F-3PM	Δ	800F-3MP	Δ	800F-3MM
4-hole		* \$	800F-4PP	* \$	800F-4PM	–	–	–	–
5-hole		–	–	–	–	♦	800F-5MP	♦	800F-5MM
6-hole		* ♣	800F-6PP	* ♣	800F-6PM	–	–	–	–
1-hole (yellow)		*	800F-1YP	*	800F-1YM	Δ	800F-1MYP	Δ	800F-1MYM
1-hole (yellow) latch only		–	–	–	–	Δ	800F-1LYP	Δ	800F-1LYM
1-hole (yellow)		‡	800F-1YPD	‡	800F-1YMD	–	–	–	–

dual circuit

* Can only use single deep contact block.

‡ Can stack contact blocks two deep or one dual circuit contact block.

§ Knockouts: PG (PG11/16), Metric (M16/20)

♣ Knockouts: PG (PG16), Metric (M25)

△ Openings: PG (PG16), Metric (M20)

◆ Openings: PG (PG16), Metric (M32)