

These tables provide ordering information for some of our most popular products. For more details and to see our full range of signaling solutions, visit the Allen-Bradley Industrial Controls online catalog at www.ab.com/catalogs.

Control Tower Tower Lights

	Bulletin	854J	855E	854K	855T
	Diameter	40 mm	50 mm	60 mm	70 mm
Mounting Bases	Surface mount	854J-BSFC	855E-BCBC	854K-BSFC	855T-BCBC
	Vertical mount	854J-BVMC	855E-BVMC	854K-BVMC	855T-BVMC
	Pole mount – 10 cm	854J-BPM10C	855E-BPM10C	854K-BPM10C	855T-BPM10C
	Pole mount – 25 cm	854J-BPM25C	855E-BPM25C	854K-BPM25C	855T-BPM25C
	Quick release – 10 cm	854J-BQ10C	855E-BMM10C	854K-BQ10C	855T-BMM10C
	Quick release – 25 cm	854J-BQ25C	855E-BMM25C	854K-BQ25C	855T-BMM25C
	Double sided	854J-BDSC	—	854K-BDSC	—
Light Modules	LED steady	854J-TL	855E-TL	854K-TL	855T-BTL
	LED flashing	854J-GL	855E-GL	854K-GL	855T-BGL
	Strobe	854J-BL	855E-BR	854K-BL	855T-BBR
Sounders	Piezo electric – single tone	854J-B*SA3	855E-B*SA3	854K-B*SA3	855T-B*SA3
	Piezo electric – dual tone	—	855E-B*TA3	—	855T-B*TA3
	Transducer – single tone	—	—	—	855T-B*SA1
	Transducer – dual tone	—	—	—	855T-B*TA1

* Voltage Code: 24=24V AC/DC, 10=120V AC, 20=240V AC

= see lens color options

90 mm Round LED Beacons

	Steady/flashing	Strobe	Multicolor (green/amber/red)
Surface mount	855BS-SSL	855BS-SBL	855BS-SML345
Half-inch NPT mount	855BS-NSL	855BS-NBL	855BS-NML345
Tube mount	855BS-TSL	855BS-TBL	855BS-TML345

Voltage Code: 35=24V AC/DC, 45=120/240V AC/DC

Voltage Code: 35=24V AC/DC, 10=120V AC, 20=240V AC

Voltage Code: 24=24V AC/DC, 10=120V AC, 20=240V AC

= see lens color options

Electronic Industrial Horns

	Bulletin 855H	Output dB(A) 1 m	Cat. No.
GP Horn	3 tones – 1 circuit	108	855H-SGGPA
	3 tones – 2 circuits	113	855H-SGGPE
	32 tones – 3 circuits	104	855H-BBD
	32 tones – 3 circuits	112	855H-BCD
	45 tones – 3 circuits	119	855H-BDD
High Performance	45 tones – 3 circuits	126	855H-BED
	45 tones – 4 circuits	101 voice, 110 tones	855H-RAC
	45 tones – 4 circuits	111 voice, 126 tones	855H-RAE
	45 tones – 4 circuits	111 voice, 126 tones	855H-RAF
Recordable			

Voltage Code: 24=24V AC/DC, 10=120V AC, 20=240V AC

Voltage Code: 30=24V DC, 45=120/240V AC

Voltage Code: D30=24V DC, A10=120V AC, A20=240V AC

Panel Mount Alarms

	30 mm	45 mm	65 mm
Sounders	855P-B*SH22	855P-B*ME22	855P-B*LE22
Beacons	855PB-BSE 22	855PB-BME 22	855PB-BLE 22
Combo light and sound	—	855PC-BME 22	855PC-BLE 22
Dual circuit – light half lens	855PD-BSEH 22	855PD-BMEH 22	855PD-BLEH 22
Dual circuit combo – light and sound	—	855PD-BMEC1 22	855PD-BMEC1 22

* Voltage Code: 30=24V DC, 10=120V AC, 20=240V AC

Voltage Code: 24=24V AC/DC, 10=120V AC, 20=240V AC

= see lens color options

Lens Color Options



3 – Green



4 – Red



5 – Amber



6 – Blue



7 – Clear



8 – Yellow

Follow ROKAutomation on Facebook & Twitter.



Connect with us on LinkedIn.

Allen-Bradley, Control Tower, Integrated Architecture, Listen. Think. Solve., PartnerNetwork and Rockwell Software are trademarks of Rockwell Automation, Inc.

www.rockwellautomation.com

Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846