





Connection Systems
Cordsets and Patchcords, DC Micro Style
 18 AWG & 22 AWG, PUR, TPE, or TPR

Pinout and Color Code

Color Code	Face View Pinout							
	4-Pin		5-Pin		8-Pin			
	 Female		 Male		 Female		 Male	
A	1 Brown 2 White 3 Blue	4 Black 5 NA	1 Brown 2 White 3 Blue	4 Black 5 Grey	1 Red 2 Blue 3 Green 4 Yellow	5 Black 6 White 7 N.C. 8 Grey		
B	—		—		1 White 2 Brown 3 Green 4 Yellow	5 Grey 6 Pink 7 Blue 8 Red		

Product Selection

Cordsets

Pin Count	Cable Type	Assembly Rating	Color Code	Cat. No.			
				Straight Female	Right Angle Female	Straight Male	Right Angle Male
4-Pin	TPE	18 AWG, 250V, 4 A	A	889D-F4HJ-*	889D-R4HJ-*	889D-M4HJ-*	889D-E4HJ-*
			A	889D-F4HL-*	889D-R4HL-*	889D-M4HL-*	889D-E4HL-*
	PUR	22 AWG, 250V, 4 A	A	889D-F4UC-*	889D-R4UC-*	889D-M4UC-*	889D-E4UC-*
			A	889D-F5UC-*	889D-R5UC-*	889D-M5UC-*	889D-E5UC-*
8-Pin	TPR	24 AWG 300V AC/ 36V DC 1.5 A	A	889D-F8AC-*	—	—	—
	PUR		B	889D-F8AB-*	889D-R8AB-*	889D-M8AB-*	—

Patchcords

Pin Count	Cable Type	Assembly Rating	Cat. No.			
			Straight Female Straight Male	Straight Female Right Angle Male	Right Angle Female Straight Male	Right Angle Female Right-Angle Male
4-Pin	TPE	18 AWG, 250V, 4 A	889D-F4HJDM-‡	889D-F4HJDE-‡	889D-R4HJDM-‡	889D-R4HJDE-‡
			889D-F4HLDM-‡	889D-F4HLDE-‡	889D-R4HLDM-‡	889D-R4HLDE-‡
	PUR	22 AWG, 250V, 4 A	889D-F4UCDM-‡	889D-F4UCDE-‡	889D-R4UCDM-‡	889D-R4UCDE-‡
			889D-F5UCDM-‡	889D-F5UCDE-‡	889D-R5UCDM-‡	889D-R5UCDE-‡
8-Pin	PUR	24 AWG 300V AC/ 36V DC 1.5 A	889D-F8ABDM-‡	—	—	—

* Replace symbol with 2 (2 m), 5 (5 m), or 10 (10 m) for standard cable lengths.

‡ Replace symbol with 0M3 (1 ft), 1 (1 m), 2 (2 m), 5 (5 m) or 10 (10 m) for standard lengths.

Note: Stainless steel connectors may be ordered by adding an "S" to the bulletin number (e.g. 889DS-F4HJ-*)