

Bulletin 800F 22.5 Mm Push Buttons

| | | | | | | |
|---------------------------|---|--------------------------|---------------------------------|-------------------------------------|-----------------------|---|
| Introduction | Standards Compliance and Certifications | Quick Selection | Momentary Push Button Operators | Alternate Action Operators | Pilot Light Operators |  |
| Selector Switch Operators | Key-Operated Selector Switch Operators | Emergency Stop Operators | Momentary Mushroom Operators | Multi-Function Operators | Reset Operators | |
| Single Turn Potentiometer | Selector Push Button Operators | Toggle Switch Operators | Back-of-Panel Components | Plastic and Metal Enclosures | Assembled Stations | |
| Pendant Stations | Accessories | Legend Plates | Specifications | Approximate Dimensions | | |

Plastic and Metal Enclosures

Plastic Enclosures (Latch or Base Mounting)

- Accepts two-piece snap-in legends
- One-hole enclosure accepts 60 mm emergency stop legends
- UL Listed, CSA Certified



Plastic Enclosure
Cat. No. 800F-3PM



Metal Enclosure
Cat. No. 800F-5MM

Metal Enclosures (Latch or Base Mounting)

- Feed-through design
- Accepts two-piece snap-in legends
- Includes base mount adapter

| Type | Pkg. Quantity | Enclosures | | | | | | | |
|----------------------------|---------------|----------------------|-----------|--------------------------|-----------|--------------------------------|-----------|-------------------------|-----------|
| | | Plastic (IP66, 4/4X) | | | | Metal – Die Cast (IP66, 4/13)‡ | | | |
| | | PG Conduit Knockouts | | Metric Conduit Knockouts | | PG Conduit Openings | | Metric Conduit Openings | |
| | | Cat. No. | | Cat. No. | | Cat. No. | | Cat. No. | |
| 1-hole | 1 | * \$ | 800F-1PP | * \$ | 800F-1PM | Δ | 800F-1MP | Δ | 800F-1MM |
| 2-hole | | * \$ | 800F-2PP | * \$ | 800F-2PM | Δ | 800F-2MP | Δ | 800F-2MM |
| 3-hole | | * \$ | 800F-3PP | * \$ | 800F-3PM | Δ | 800F-3MP | Δ | 800F-3MM |
| 4-hole | | * \$ | 800F-4PP | * \$ | 800F-4PM | – | – | – | – |
| 5-hole | | – | – | – | – | ◆ | 800F-5MP | ◆ | 800F-5MM |
| 6-hole | | * ♣ | 800F-6PP | * ♣ | 800F-6PM | – | – | – | – |
| 1-hole (yellow) | | * | 800F-1YP | * | 800F-1YM | Δ | 800F-1MYP | Δ | 800F-1MYM |
| 1-hole (yellow) latch only | | – | – | – | – | Δ | 800F-1LYP | Δ | 800F-1LYM |
| 1-hole (yellow) | | ‡ | 800F-1YPD | ‡ | 800F-1YMD | – | – | – | – |

dual circuit

* Can only use single deep contact block.

‡ Can stack contact blocks two deep or one dual circuit contact block.

§ Knockouts: PG (PG11/16), Metric (M16/20)

♣ Knockouts: PG (PG16), Metric (M25)

△ Openings: PG (PG16), Metric (M20)

◆ Openings: PG (PG16), Metric (M32)