
Bulletin	1492-J, -W	1492-L
Type	Screw Type Terminal Blocks	Spring-Clamp Terminal Blocks
Technology	Screw terminations are a time-proven method of wire connection. Their greatest advantage is the ability to land multiple wires to a single terminal, potentially saving panel space. Screw type blocks can often accept up to five solid or stranded wires per terminal. They also typically provide the best visual indication of the wire connection.	Compared to screw type terminations, spring clamp terminations can be a significantly faster method of connection and can often reduce wire connection time by 30...50%. Because the wire is under constant tension from the spring clamp, spring type terminations also produce very favorable results in high vibration applications.
Certifications	UR, CSA	UR, CSA
Standards Compliance	IEC, CE	IEC, CE
Product Types	• Mini blocks • Feed-through blocks • Multi-conductor blocks • Plug-in style blocks • Grounding blocks • Fuse blocks • Two level terminal blocks • Three-Level Sensor blocks • Electrical Component blocks • Isolation blocks	• Mini blocks • Fuse blocks • Feed-through blocks • Grounding blocks • Multi-circuit blocks • Plug-in style blocks • Isolation blocks • Sensor blocks • Electrical component blocks
Product Selection	Page 12-6	Page 12-47

Certifications

Allen-Bradley terminal blocks generally have been designed to meet the requirements of one or more regulatory bodies. Most products have also been tested per additional standards. The following is a listing of some of the regulatory bodies and standards which apply to Allen-Bradley terminal block products. See the particular product description for information on specific certifications and ratings.



(Underwriters Laboratories) — Devices in this catalog with one of these ratings have been tested by Underwriters Laboratories and meet the requirements of one or more of the following United States Standards:

- UL 467 — Grounding and Bonding Equipment
- UL 486E — Equipment Wiring Terminals for Use with Aluminum and/or Copper Conductors
- UL 1059 — Standard for Terminal Blocks

Reference UL files E34648, E40735, E160646



(Underwriters Laboratories) — Devices in this catalog with this rating have been tested by Underwriters Laboratories and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference UL file E40735



(Canadian Standards Association) — Devices in this catalog with this rating have been tested by the Canadian Standards Association and meet the requirements of the following Canadian Standard:

- CSA 22.2 No. 158 — Terminal Blocks

Reference CSA files LR67896



Terminal blocks listed in this catalog meet the requirements of the Low Voltage Directive put forth by the European Union. Devices have been tested and comply with one or more of the following European Norms:

- EN 60947-1 — Low Voltage Switchgear and Controlgear: General Rules
- EN 60947-7-1 — Low Voltage Switchgear and Controlgear: Terminal Blocks for Copper Conductors
- EN 60947-7-2 — Low Voltage Switchgear and Controlgear: Protective Conductor Terminal Blocks for Copper Conductors
- EN 60947-7-3 — Low Voltage Switchgear and Controlgear: Safety Requirements for Fuse Terminal Blocks



ATEX — Devices listed in this catalog with “ATEX” ratings meet the following European Norms per DEMKO or KEMA, Approval Certification Bodies for the European Union:

- EN 60079-7 — Electrical Apparatus for Potentially Explosive Atmospheres — General Requirements
- EN 60079-0 — Electrical Apparatus for Potentially Explosive Atmospheres — Increased Safety “e”

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.



Screw Connection Terminal Blocks

Certifications/Introduction

Ex e II — Many 1492-J, 1492-K, 1492-L, and 1492-W terminal blocks in this catalog meet the following Canadian Standards per Underwriters Laboratories:

CAN/CSA E 60079-7 — Electrical Apparatus for Explosive Atmospheres — Part 0 — General Requirements

CAN/CSA E 60079-0 — Electrical Apparatus for Explosive Atmospheres — Part 7 — Increased Safety “e”

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Allen-Bradley distributor for more information.

AEx e II — Devices listed in this catalog with an “AEx e II” rating meet the following United States Standard per Underwriters Laboratories:

- ANSI/UL 60079-0 and 60079-7 — Standard for Electrical Equipment for Use in Class I, Zone 0, 1, and 2 Hazardous (Classified) Locations

These products are suitable for Class I, Zone 1 Hazardous Locations. Reference UL file E187022. Contact your local Rockwell Automation sales office or Allen-Bradley distributor for more information.

Lloyd's Register — Many 1492-H, 1492-J, 1492-L, and 1492-W terminal blocks in this catalog have been certified for use in marine, off-shore, and industrial installations per the following standard:

- Lloyd's Register Test Specification No. 1:1996

Contact your local Rockwell Automation sales office or Allen-Bradley distributor for a copy of the certificate.

The Allen-Bradley Line of IEC Terminal Blocks... International Products for a Worldwide Marketplace

The Allen-Bradley Bulletin 1492-J line of internationally approved IEC style terminal blocks offers a wide range of features and benefits ideally suited for many industrial applications. The 1492-J line has been designed to meet the tough requirements of almost every industrial application. Functional, internationally approved, finger-safe, and cost-effective — the Allen-Bradley Bulletin 1492-J line.

Products Available in the Bulletin 1492 Screw Terminal Block Line




Our family of IEC terminal blocks consists of many different types of blocks, from general feed-through terminal blocks for control wiring to specialty blocks for grounding and isolating. We even offer thermocouple terminal blocks, specifically designed for temperature-dependent process control applications.

Products offered within the Bulletin 1492 Screw Terminal Block line include:

- **Feed-Through Blocks**, capable of accommodating #30...2/0 AWG (0.2...70 mm²) wire
- **Grounding Blocks** for grounding a given circuit to the DIN Rail
- **Mini Blocks** for applications where panel space is at a premium
- **Two-Level Blocks** that double circuit wiring density
- **Multi-Conductor Blocks** that allow splitting or joining of control circuits
- **Three-Level Sensor Blocks** for coordination of three-wire sensor groups
- **Isolation Blocks** for circuit isolation during testing and troubleshooting
- **Fuse Blocks**, with and without blown fuse indication, for easily integrated overcurrent protection
- **Electrical Component Blocks** that allow the insertion of fixed components into control circuits. Available components include resistors, diodes, surge suppression circuits, and shunt bars.




Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L3				1492-L3T				1492-L3Q					
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.														
Specifications	Feed-through terminal block				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 2 points on each side					
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX		
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC		
Maximum Current	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A	25 A	27 A	24 A	21 A		
Wire Range (Rated Cross Section)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)	#30... 12 AWG	#26... 12 AWG	2.5 mm ²	2.5 mm ² (20...12 AWG)		
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.39 in. (10 mm)					
Density	59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating (SCCR)	See page 12-78													
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Color	Grey		1492-L3		100		1492-L3T		100		1492-L3Q		100	
	Red		1492-L3-RE		100		1492-L3T-RE		100		1492-L3Q-RE		100	
	Blue		1492-L3-B		100		1492-L3T-B		100		1492-L3Q-B		100	
	Black		1492-L3-BL		100		1492-L3T-BL		100		1492-L3Q-BL		100	
	Green		1492-L3-G		100		1492-L3T-G		100		1492-L3Q-G		100	
	Yellow		1492-L3-Y		100		1492-L3T-Y		100		1492-L3Q-Y		100	
	Orange		1492-L3-OR		100		1492-L3T-OR		100		1492-L3Q-OR		100	
	Brown		1492-L3-BR		100		1492-L3T-BR		100		1492-L3Q-BR		100	
	White		1492-L3-W		100		1492-L3T-W		100		1492-L3Q-W		100	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.			
Mounting Rails	1 m Symmetrical DIN (Steel)		199-DR1		10		199-DR1		10		199-DR1		10	
	1 m Symmetrical DIN (Aluminum)		1492-DR5		10		1492-DR5		10		1492-DR5		10	
	1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6		2		1492-DR6		2		1492-DR6		2	
	1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7		2		1492-DR7		2		1492-DR7		2	
End Barriers	Grey	1492-EBL3	50	1492-EBL3T	50	1492-EBL3Q	50	1492-EBL3	50	1492-EBL3T	50	1492-EBL3Q	50	
	Blue	1492-EBL3-B	50	1492-EBL3T-B	50	1492-EBL3Q-B	50	1492-EBL3-B	50	1492-EBL3T-B	50	1492-EBL3Q-B	50	
	Yellow	1492-EBL3-Y	50	1492-EBL3T-Y	50	1492-EBL3Q-Y	50	1492-EBL3-Y	50	1492-EBL3T-Y	50	1492-EBL3Q-Y	50	
End Anchors and Retainers	Screwless End Retainer		1492-ERL35		20		1492-ERL35		20		1492-ERL35		20	
	DIN Rail — Normal Duty		1492-EAJ35		100		1492-EAJ35		100		1492-EAJ35		100	
	DIN Rail — Heavy Duty		1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Jumpers	Plug-in Center Jumper — 50-Pole		1492-CJK5-50		10		1492-CJK5-50		10		1492-CJK5-50		10	
	Plug-in Center Jumper — 10-Pole		1492-CJK5-10		20		1492-CJK5-10		20		1492-CJK5-10		20	
	Plug-in Center Jumper — 9-Pole		1492-CJK5-9		20		1492-CJK5-9		20		1492-CJK5-9		20	
	Plug-in Center Jumper — 8-Pole		1492-CJK5-8		20		1492-CJK5-8		20		1492-CJK5-8		20	
	Plug-in Center Jumper — 7-Pole		1492-CJK5-7		20		1492-CJK5-7		20		1492-CJK5-7		20	
	Plug-in Center Jumper — 6-Pole		1492-CJK5-6		20		1492-CJK5-6		20		1492-CJK5-6		20	
	Plug-in Center Jumper — 5-Pole		1492-CJK5-5		20		1492-CJK5-5		20		1492-CJK5-5		20	
	Plug-in Center Jumper — 4-Pole		1492-CJK5-4		60		1492-CJK5-4		60		1492-CJK5-4		60	
	Plug-in Center Jumper — 3-Pole		1492-CJK5-3		60		1492-CJK5-3		60		1492-CJK5-3		60	
	Plug-in Center Jumper — 2-Pole		1492-CJK5-2		60		1492-CJK5-2		60		1492-CJK5-2		60	
Other Accessories	Reducing Sleeves #30...#24 AWG (0.13...0.2 mm ²) White		1492-PSL3-2		100		1492-PSL3-2		100		1492-PSL3-2		100	
	Reducing Sleeves #22...#20 AWG (0.25...0.5 mm ²) Grey		1492-PSL3-5		100		1492-PSL3-5		100		1492-PSL3-5		100	
	Reducing Sleeves #18 AWG (0.75...1.0 mm ²) Dark Grey		1492-PSL3-10		100		1492-PSL3-10		100		1492-PSL3-10		100	
	Test Plug		1492-TP23		20		1492-TP23		20		1492-TP23		20	
	Test Plug (Stackable)		1492-TPL5		25		1492-TPL5		25		1492-TPL5		25	
	Electrical Warning Plate		1492-EWPL5		20		1492-EWPL5		20		1492-EWPL5		20	
Marking Systems	Snap-In Marker Cards		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5		1492-M5X10 (144/card)		5	
	Snap-In Marker Cards		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5		1492-M5X5 (200/card)		5	
	Hinged Marker Cards		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5		1492-MH5X10 (96/card)		5	
	Hinged Marker Cards		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5		1492-MH5X15 (96/card)		5	

Spring-Clamp Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks

	1492-LD2			1492-LD3			1492-L3QS		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-circuit feed-through terminal block			Two-circuit feed-through terminal block			Side-by-side two circuit terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC	600V AC/DC	800V AC/DC	550V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	20 A	25 A	27 A
Wire Range (Rated Cross Section)	#28... 16 AWG		1.5 mm ²	#30... 12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)		2.5 mm ² (20... 12 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Color	Grey	1492-LD2	50	1492-LD3	25	1492-L3QS	50	1492-L3QS	50
	Red	1492-LD2-RE	50	1492-LD3-RE	25	1492-L3QS-RE	50	1492-L3QS-RE	50
	Blue	1492-LD2-B	50	1492-LD3-B	25	1492-L3QS-B	50	1492-L3QS-B	50
	Black	1492-LD2-BL	50	1492-LD3-BL	25	1492-L3QS-BL	50	1492-L3QS-BL	50
	Green	1492-LD2-G	50	1492-LD3-G	25	1492-L3QS-G	50	1492-L3QS-G	50
	Yellow	1492-LD2-Y	50	1492-LD3-Y	25	1492-L3QS-Y	50	1492-L3QS-Y	50
	Orange	1492-LD2-OR	50	1492-LD3-OR	25	1492-L3QS-OR	50	1492-L3QS-OR	50
	Brown	1492-LD2-BR	50	1492-LD3-BR	25	1492-L3QS-BR	50	1492-L3QS-BR	50
	White	1492-LD2-W	50	1492-LD3-W	25	1492-L3QS-W	50	1492-L3QS-W	50
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10	199-DR1	10	199-DR1
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10	1492-DR5	10	1492-DR5
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2	1492-DR6	2	1492-DR6
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2	1492-DR7	2	1492-DR7
End Barriers	Grey	1492-EBLD2	50	1492-EBLD3	20	1492-EBL3Q	50	1492-EBL3Q	50
	Blue	1492-EBLD2-B	20	1492-EBLD3-B	20	1492-EBL3Q-B	50	1492-EBL3Q-B	50
	Yellow	1492-EBLD2-Y	20	1492-EBLD3-Y	20	1492-EBL3Q-Y	50	1492-EBL3Q-Y	50
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20	1492-ERL35
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35
Jumpers									
Plug-in Center Jumper — 50-Pole	—	—	1492-CJK5-50	10	—	—	—	—	—
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20	1492-CJK5-10	20	—	—	—	—	—
Plug-in Center Jumper — 9-Pole	—	—	1492-CJK5-9	20	—	—	—	—	—
Plug-in Center Jumper — 8-Pole	—	—	1492-CJK5-8	20	—	—	—	—	—
Plug-in Center Jumper — 7-Pole	—	—	1492-CJK5-7	20	—	—	—	—	—
Plug-in Center Jumper — 6-Pole	—	—	1492-CJK5-6	20	—	—	—	—	—
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60	1492-CJK5-5	20	—	—	—	—	—
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60	1492-CJK5-4	60	—	—	—	—	—
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60	1492-CJK5-3	60	—	—	—	—	—
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60	1492-CJK5-2	60	—	—	—	—	—
Other Accessories									
Reducing Sleeves #28...24 AWG (0.13...0.2 mm ²)	1492-PSL2-2	100	1492-PSLS2-2	100	1492-PSL3-2	100	1492-PSL3-2	100	1492-PSL3-2
Reducing Sleeves #22...20 AWG (0.25...0.5 mm ²)	1492-PSL2-5	100	1492-PSLS2-5	100	1492-PSL3-5	100	1492-PSL3-5	100	1492-PSL3-5
Reducing Sleeves #18 AWG (0.75...1.0 mm ²)	—	—	—	—	1492-PSL3-10	100	1492-PSL3-10	100	1492-PSL3-10
Test Plug	1492-TPL4	25	—	—	1492-TP23	20	1492-TP23	20	1492-TP23
Electrical Warning Plate	1492-EWPL4	20	—	—	1492-TPL5	25	1492-TPL5	25	1492-TPL5
	1492-M3X12 (120/card)*	5	1492-M5X10 (144/card)	5	1492-EWPL5	20	1492-EWPL5	20	1492-EWPL5
Marking Systems									
Snap-In Marker Cards	1492-M3X5 (100/card)	5	1492-M5X5 (200/card)	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)
Hinged Marker Cards	—	—	—	—	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)
	—	—	—	—	1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)	5	1492-MH5X10 (96/card)

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks



Multi-Circuit Feed-Through Blocks

1492-LD4

1492-LTF3

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.

**Specifications**

Two-circuit feed-through terminal block

Three-circuit feed-through terminal block with multiple cross connection points

		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		800V AC/DC	300V AC/DC		500V AC/DC
Maximum Current	25 A	30 A	32 A	15 A		20 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	#26...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		

Terminal Blocks

		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Color	Grey	1492-LD4	20		1492-LTF3	25
	Red	1492-LD4-RE	20		—	—
	Blue	1492-LD4-B	20		—	—
	Black	1492-LD4-BL	20		—	—
	Green	1492-LD4-G	20		—	—
	Yellow	1492-LD4-Y	20		—	—
	Orange	1492-LD4-OR	20		—	—
	Brown	1492-LD4-BR	20		—	—
	White	1492-LD4-W	20		—	—




Accessories

		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Mounting Rails						
1 m Symmetrical DIN (Steel)		199-DR1	10		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2		1492-DR7	2
End Barriers	Grey	1492-EBLD4	20		1492-EBLTF3	20
	Blue	1492-EBLD4-B	20		—	—
	Yellow	1492-EBLD4-Y	20		—	—
End Anchors and Retainers						
Screwless End Retainer		1492-ERL35	20		1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100		1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50		1492-EAHJ35	50
Jumpers						
Plug-in Center Jumper — 50-Pole		—	—		1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK6-10	20		1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK6-9	20		1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK6-8	20		1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK6-7	20		1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK6-6	20		1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK6-5	20		1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK6-4	60		1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK6-3	60		1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK6-2	60		1492-CJK5-2	60
Vertical Cross Connector*		—	—		1492-CJL5D	20
Other Accessories						
Reducing Sleeves 26...24 AWG (0.13...0.2 mm ²)		—	—		1492-PSLTF3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²)		—	—		1492-PSLTF3-5	100
Test Plug		1492-TP23	20		—	—
Electrical Warning Plate		1492-EWPL6	20		—	—
Marking Systems						
Snap-In Marker Cards		1492-M6X10 (120/card)	5		1492-SM5X10 (144/card)	5
Snap-In Marker Cards		1492-M6X5 (200/card)	5		1492-M5X5 (200/card)	5

* Used to electrically connect 2 levels of 1492-LTF3

Spring-Clamp Connection Terminal Blocks

Specialty Feed-Through Blocks

	1492-LD2C			1492-LD3C				1492-LD4C		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.										
Specifications	Two-level feed-through terminal block with commoning bar			Two-level feed-through terminal block with commoning bar				Two-level feed-through terminal block with commoning bar		
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	22 A	25 A	30 A	32 A
Wire Range (Rated Cross Section)	#28...16 AWG		1.5 mm ²	#30...12 AWG		2.5 mm ²	0.5...2.5 mm ² (#20...14 AWG)	#26...10 AWG		4 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)		
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Grey	1492-LD2C	50		1492-LD3C	25			1492-LD4C	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:										
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2			1492-DR7	2	
End Barriers Grey	1492-EBLD2	50		1492-EBLD3	20			1492-EBLD4	20	
End Anchors and Retainers Screwless End Retainer	1492-ERL35	20		1492-ERL35	20			1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50			1492-EAHJ35	50	
Jumpers:										
Plug-in Center Jumper — 50-Pole	—	—		1492-CJK5-50	10			—	—	
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20		1492-CJK5-10	20			1492-CJK6-10	20	
Plug-in Center Jumper — 9-Pole	—	—		1492-CJK5-9	20			1492-CJK6-9	20	
Plug-in Center Jumper — 8-Pole	—	—		1492-CJK5-8	20			1492-CJK6-8	20	
Plug-in Center Jumper — 7-Pole	—	—		1492-CJK5-7	20			1492-CJK6-7	20	
Plug-in Center Jumper — 6-Pole	—	—		1492-CJK5-6	20			1492-CJK6-6	20	
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60		1492-CJK5-5	20			1492-CJK6-5	20	
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60		1492-CJK5-4	60			1492-CJK6-4	60	
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60		1492-CJK5-3	60			1492-CJK6-3	60	
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60		1492-CJK5-2	60			1492-CJK6-2	60	
Other Accessories:										
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL2-2	100		1492-PSLS2-2	100			—	—	
Reducing Sleeves 22...20 AWG (0.13...0.2 mm ²) Grey	1492-PSL2-5	100		1492-PSLS2-5	100			—	—	
Test Plug	1492-TPL4	25		—	—			1492-TP23	20	
Electrical Warning Plate	1492-EWPL4	20		—	—			1492-EWPL6	20	
Marking Systems:										
Snap-In Marker Cards	1492-M3X12 (120/card)*	5		1492-M5X10 (144/card)	5			1492-M6X10 (120/card)	5	
Snap-In Marker Cards	1492-M3X5 (100/card)	5		1492-M5X5 (200/card)	5			1492-M6X5 (200/card)	5	

* May only be mounted in terminal block corner marking positions.

Spring-Clamp Connection Terminal Blocks

Sensor Blocks — 3-Wire




1492-LS2-3*
1492-LS2-3L*

1492-LSG2-3*

1492-LS2-BR
1492-LS2-B
1492-LSG2

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	3 conductor sensor block base for plug in distribution blocks			3 conductor sensor ground block base for plug in distribution blocks			Plug in Distribution blocks — internally jumpered		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating (without LED)	300V AC/DC			300V AC/DC			300V AC/DC		
Voltage Rating (with LED)	5...30V AC/DC			—			5...30V AC/DC		
Maximum Current	10 A			10 A			10 A		
Wire Range (Rated Cross Section)	#26...14 AWG			#26...14 AWG			#26...14 AWG		
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey (Without LED)	1492-LS2-3	50		—	—		—	—	
Grey (With LED)	1492-LS2-3L	50		—	—		—	—	
Green/Yellow	—	—		1492-LSG2-3	20		1492-LSG2	100	
Brown	—	—		—	—		1492-LS2-BR	100	
Blue	—	—		—	—		1492-LS2-B	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		—	—	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		—	—	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		—	—	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		—	—	
End Barriers Grey	1492-EBLS2-3	50		1492-EBLS2-3	50		Not required	—	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		—	—	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		—	—	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		—	—	
Jumpers:									
Plug-in Center Jumper — 50-Pole	1492-CJK5-50	10		—	—		—	—	
Plug-in Center Jumper — 10-Pole	1492-CJK5-10	20		—	—		—	—	
Plug-in Center Jumper — 9-Pole	1492-CJK5-9	20		—	—		—	—	
Plug-in Center Jumper — 8-Pole	1492-CJK5-8	20		—	—		—	—	
Plug-in Center Jumper — 7-Pole	1492-CJK5-7	20		—	—		—	—	
Plug-in Center Jumper — 6-Pole	1492-CJK5-6	20		—	—		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJK5-5	20		—	—		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJK5-4	60		—	—		—	—	
Plug-in Center Jumper — 3-Pole	1492-CJK5-3	60		—	—		—	—	
Plug-in Center Jumper — 2-Pole	1492-CJK5-2	60		—	—		—	—	
Other Accessories:									
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSLS2-2	100		—	—		1492-PSLS2-2	100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSLS2-5	100		—	—		1492-PSLS2-5	100	
Marking Systems:									
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		—	—	

* A combination of two distribution blocks must be used with each base block.

Spring-Clamp Connection Terminal Blocks

Sensor Blocks — 4-Wire




1492-LS2-4*
1492-LS2-4L*

1492-LSG2-4*

1492-LS2-BR
1492-LS2-B
1492-LSG2

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.




Specifications	4 conductor sensor block base for plug in distribution blocks			4 conductor sensor ground block base for plug in distribution blocks			Plug In Distribution blocks — internally jumpered		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating (without LED)	300V AC/DC			300V AC/DC			300V AC/DC		
Voltage Rating (with LED)	5...30V AC/DC			—			5...30V AC/DC		
Maximum Current	10 A			10 A			10 A		
Wire Range (Rated Cross Section)	#26...14 AWG			#26...14 AWG			#26...14 AWG		
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.28 in. (7 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey (Without LED)	1492-LS2-4	50		—	—		—	—	
Grey (With LED)	1492-LS2-4L	50		—	—		—	—	
Green/Yellow	—	—		1492-LSG2-4	20		1492-LSG2	100	
Brown	—	—		—	—		1492-LS2-BR	100	
Blue	—	—		—	—		1492-LS2-B	100	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		—	—	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		—	—	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		—	—	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		—	—	
End Barriers Grey	1492-EBLS2-4	50		1492-EBLS2-4	50		Not required	—	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		—	—	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		—	—	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		—	—	
Jumpers:									
Plug-in Center Jumper — 50-Pole	1492-CJK5-50	10		—	—		—	—	
Plug-in Center Jumper — 10-Pole	1492-CJK5-10	20		—	—		—	—	
Plug-in Center Jumper — 9-Pole	1492-CJK5-9	20		—	—		—	—	
Plug-in Center Jumper — 8-Pole	1492-CJK5-8	20		—	—		—	—	
Plug-in Center Jumper — 7-Pole	1492-CJK5-7	20		—	—		—	—	
Plug-in Center Jumper — 6-Pole	1492-CJK5-6	20		—	—		—	—	
Plug-in Center Jumper — 5-Pole	1492-CJK5-5	20		—	—		—	—	
Plug-in Center Jumper — 4-Pole	1492-CJK5-4	60		—	—		—	—	
Plug-in Center Jumper — 3-Pole	1492-CJK5-3	60		—	—		—	—	
Plug-in Center Jumper — 2-Pole	1492-CJK5-2	60		—	—		—	—	
Other Accessories:									
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSLS2-2	100		—	—		1492-PSLS2-2	100	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSLS2-5	100		—	—		1492-PSLS2-5	100	
Marking Systems:									
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		—	—	

* A combination of three distribution blocks must be used with each base block.

1492-LKD3

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	<i>Knife disconnect feed-through terminal block</i>		
Certifications	UL	CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC
Maximum Current	20 A		24 A
Wire Range (Rated Cross Section)	#30...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)		
Density	59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		

Terminal Blocks		Cat. No.	Pkg Qty.
Color	Grey	1492-LKD3	25
Accessories		Cat. No.	Pkg Qty.
Mounting Rails			
1 m Symmetrical DIN (Steel)		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2
End Barriers	Grey	1492-EBL3	50
End Anchors and Retainers			
Screwless End Retainer		1492-ERL35	20
DIN Rail — Normal Duty		1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50
Jumpers			
Plug-in Center Jumper — 50-Pole		1492-CJK5-50	10
Plug-in Center Jumper — 10-Pole		1492-CJK5-10	20
Plug-in Center Jumper — 9-Pole		1492-CJK5-9	20
Plug-in Center Jumper — 8-Pole		1492-CJK5-8	20
Plug-in Center Jumper — 7-Pole		1492-CJK5-7	20
Plug-in Center Jumper — 6-Pole		1492-CJK5-6	20
Plug-in Center Jumper — 5-Pole		1492-CJK5-5	20
Plug-in Center Jumper — 4-Pole		1492-CJK5-4	60
Plug-in Center Jumper — 3-Pole		1492-CJK5-3	60
Plug-in Center Jumper — 2-Pole		1492-CJK5-2	60
Other Accessories			
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White		1492-PSL3-2	100
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey		1492-PSL3-5	100
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey		1492-PSL3-10	100
Test Plug		1492-TP23	20
Test Plug (Stackable)		1492-TPL5	25
Electrical Warning Plate		1492-EWPL5	20
Marking Systems			
Snap-In Marker Cards		1492-M5X10 (144/card)	5
Snap-In Marker Cards		1492-M5X5 (200/card)	5

Spring-Clamp Connection Terminal Blocks

Plug-In Style Blocks & Analog Loop Control Block

	1492-L3P			1492-LDG3P			1492-LDAG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single circuit plug-in component block for a variety of components			Terminal block with slot for plug-in component, feed-through circuit and 1 ground connection			Analog Loop Control Terminal Block with 2 Feed-Through Circuits and 1 Ground Connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC			300V AC/DC			300V AC/DC		
Maximum Current	20 A			10 A			10 A		
Wire Range (Rated Cross Section)	#30...12 AWG			#26...12 AWG			#26...12 AWG		
Wire Strip Length	0.39 in. (10 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-L3P	25	1492-LDG3P	25		1492-LDAG3	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	1492-EBL3	50		1492-EBLDAG3	20		1492-EBLDAG3	20	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-In Center Jumper — 50-pole	1492-CJK5-50	10		1492-CJLJ5-50	10		1492-CJLJ5-50	10	
Plug-In Center Jumper — 10-pole	1492-CJK5-10	20		1492-CJLJ5-10	20		1492-CJLJ5-10	20	
Plug-In Center Jumper — 9-pole	1492-CJK5-9	20		1492-CJLJ5-9	20		1492-CJLJ5-9	20	
Plug-In Center Jumper — 8-pole	1492-CJK5-8	20		1492-CJLJ5-8	20		1492-CJLJ5-8	20	
Plug-In Center Jumper — 7-pole	1492-CJK5-7	20		1492-CJLJ5-7	20		1492-CJLJ5-7	20	
Plug-In Center Jumper — 6-pole	1492-CJK5-6	20		1492-CJLJ5-6	20		1492-CJLJ5-6	20	
Plug-In Center Jumper — 5-pole	1492-CJK5-5	20		1492-CJLJ5-5	20		1492-CJLJ5-5	20	
Plug-In Center Jumper — 4-pole	1492-CJK5-4	60		1492-CJLJ5-4	60		1492-CJLJ5-4	60	
Plug-In Center Jumper — 3-pole	1492-CJK5-3	60		1492-CJLJ5-3	60		1492-CJLJ5-3	60	
Plug-In Center Jumper — 2-pole	1492-CJK5-2	60		1492-CJLJ5-2	60		1492-CJLJ5-2	60	
Other Accessories									
Disconnect Plug	1492-DPL	50		1492-DPL	50		—	—	
Component Plug	1492-CPL	50		1492-CPL	50		—	—	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		—	—	
10...36V Blown Fuse Indicator	1492-FPK224	20		* 1492-FPK224	20		—	—	
35...70V Blown Fuse Indicator	1492-FPK248	20		* 1492-FPK248	20		—	—	
60...150V Blown Fuse Indicator	1492-FPK2120	20		* 1492-FPK2120	20		—	—	
140...250V Blown Fuse Indicator	1492-FPK2250	20		* 1492-FPK2250	20		—	—	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL3-2	100		—	—		—	—	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL3-5	100		—	—		—	—	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL3-10	100		—	—		—	—	
Test Plug	1492-TPL5	25		1492-TP23	20		—	—	
Electrical Warning Plate	1492-EWPL5	20		—	—		—	—	
Marking Systems									
Snap-In Marker Cards	1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5	
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	

* When using Cat. No. 1492-LDG3P with a fuse plug, a center jumper cannot be used on the top level. The only jumper option to use in combination with a fuse plug is a 2-pole side jumper: Cat. No. 1492-SJLM5-2.

Screwless Center Jumpers



For Use With	Color	Pkg Qty.	Cat. No.
1492-L2..., L2T, L2Q, LD2, LD2C	Yellow	60	1492-CJL4-2
		60	1492-CJL4-3
		60	1492-CJL4-4
		60	1492-CJL4-5
		20	1492-CJL4-10
1492-LM3, LC3, LDC3, LDAG3, LDG3P, JKD3..., J3P..., J3, J3TW (see Note)	Yellow	60	1492-CJLJ5-2
	Red	60	1492-CJLJ5-2-R
	Blue	60	1492-CJLJ5-2-B
	Black	60	1492-CJLJ5-2-BL
	Yellow	60	1492-CJLJ5-3
	Red	60	1492-CJLJ5-3-R
	Blue	60	1492-CJLJ5-3-B
	Black	60	1492-CJLJ5-3-BL
	Yellow	60	1492-CJLJ5-4
		20	1492-CJLJ5-5
		20	1492-CJLJ5-6
		20	1492-CJLJ5-7
		20	1492-CJLJ5-8
		20	1492-CJLJ5-9
		20	1492-CJLJ5-10
	Red	20	1492-CJLJ5-10-R
	Blue	20	1492-CJLJ5-10-B
	Black	20	1492-CJLJ5-10-BL
	White	20	1492-CJLJ5-10-W
	Yellow	10	1492-CJLJ5-50
	Red	10	1492-CJLJ5-50-R
	Blue	10	1492-CJLJ5-50-B
	Black	10	1492-CJLJ5-50-BL
	White	10	1492-CJLJ5-50-W

For Use With	Pkg Qty.	Cat. No.
1492-RFB4	10	1492-CJR8-2
	10	1492-CJR8-3
	10	1492-CJR8-4
	10	1492-CJR8-5
	10	1492-CJR8-6
	10	1492-CJR8-7
	10	1492-CJR8-8
	10	1492-CJR8-9
	10	1492-CJR8-10
	10	1492-CJRA10-2
1492-RAFB4	10	1492-CJRA10-3
	10	1492-CJRA10-4
	10	1492-CJRA10-5

For Use With	Color	Pkg Qty.	Cat. No.
1492-J4, J4M (see Note)	Yellow	60	1492-CJLJ6-2
	Red	60	1492-CJLJ6-2-R
	Blue	60	1492-CJLJ6-2-B
	Black	60	1492-CJLJ6-2-BL
	Yellow	60	1492-CJLJ6-3
	Red	60	1492-CJLJ6-3-R
	Blue	60	1492-CJLJ6-3-B
	Black	60	1492-CJLJ6-3-BL
	Yellow	60	1492-CJLJ6-4
	Yellow	20	1492-CJLJ6-10
	Red	20	1492-CJLJ6-10-R
	Blue	20	1492-CJLJ6-10-B
	Black	20	1492-CJLJ6-10-BL
	Yellow	10	1492-CJLJ6-41
	Red	10	1492-CJLJ6-41-R
	Blue	10	1492-CJLJ6-41-B
	Black	10	1492-CJLJ6-41-BL
1492-L6, L6T, L16D	Yellow	60	1492-CJL8-2
		60	1492-CJL8-3
		60	1492-CJL8-4
		10	1492-CJL8-32
1492-L10	Yellow	25	1492-CJL10-2
1492-L16	Yellow	25	1492-CJL12-2
1492-L35	Yellow	10	1492-CJL16-2
1492-L3, L3T, L3Q, L3P, LD3, LD3C, LKD3, LTF3, LS2..., L16D	Yellow	60	1492-CJK5-2
		60	1492-CJK5-3
		60	1492-CJK5-4
		20	1492-CJK5-5
		20	1492-CJK5-6
		20	1492-CJK5-7
		20	1492-CJK5-8
		20	1492-CJK5-9
		20	1492-CJK5-10
		10	1492-CJK5-50
		60	1492-CJK6-2
1492-L4, L4T, L4Q, LD4DF, LD4DR, LD4SS, LD4, LD4C, L16D	Yellow	60	1492-CJK6-3
		60	1492-CJK6-4
		20	1492-CJK6-5
		20	1492-CJK6-6
		20	1492-CJK6-7
		20	1492-CJK6-8
		20	1492-CJK6-9
		20	1492-CJK6-10
		20	1492-CJK6-20