Pinout and Color Code

Face View Pinout			
3-Pin	4-Pin		
Female Male	Female Male		
1 Brown 2 NA 3 Blue 4 Black	1 Brown 2 White 3 Blue 4 Black		

Product Selection

Snap-On Cordsets

		Cat. No.		Cat.	No.
Pin Count	Jacket Material o	Straight Female 0	Right Angle Female ⊙	Straight Male 0	Right Angle Male 0
3-Pin	Yellow PUR Flex 	889P-S3UB- ⊘	889P-Z3UB- ⊘	889P-G3UB- ⊘	889P-H3UB- ⊘
4-Pin		889P-S4UB- ❹	889P-Z4UB- ⊘	889P-G4UB- ⊘	889P-H4UB- ❹

Screw-On Cordsets

		Cat. No.		Cat.	No.
Pin Count	Jacket Material@	Straight Female ⊘	Right Angle Female⊘	Straight Male ⊘	Right Angle Male❷
3-Pin	Yellow PVC 2	889P-F3AB- ⊙	889P-R3AB- ⊙	889P-M3AB- ⊘	889P-E3AB- ⊘
4-Pin		889P-F4AB- ⊘	889P-R4AB- ⊘	889P-M4AB- ④	889P-E4AB- ❹

Screw-On Patchcords	[<u>a</u>	
---------------------	------------	--

		Cat. No.		Cat.	No.
Pin Count	Jacket Material	Straight Female Straight Maleூ	Straight Female Right Angle Maleூ	Right Angle Female Straight Male⊖	Right Angle Female Right Angle Maleூ
Male: Pico 3-Pin Female: Pico 3-Pin		889P-F3ABPM- ⊙	889P-F3ABPE-ூ	889P-R3ABPM- ⊙	889P-R3ABPE- ⊙
Male: Pico 3-Pin Female: Pico 4-Pin	Yellow AB PVC 	889P-F4ABP3M- 	889P-F4ABP3E- 	889P-R4ABP3M -⑤	889P-R4ABP3E- ⊕
Male: Pico 4-Pin Female: Pico 4-Pin		889P-F4ABPM- 	889P-F4ABPE- ⊙	889P-R4ABPM- ⊙	889P-R4ABPE- ⊙

- Replace UB with JB for black Halogen free PUR.
 Replace AB with BB for black PVC, FB for yellow PVC/foil shield and drain; UB for yellow PUR, flex cable, JB for black Halogen-free PUR, HB for yellow TPE flex.
- Replace AB with BB for black PVC, UB for yellow PUR, flex cable, JB for black Halogen-free PUR, HB for yellow TPE flex cable.
- Replace symbol with 2 (2 m), 5 (5 m) or 10 (10 m) for standard cable lengths.
 Replace symbol with 0M3 (0.3 m), 1 (1 m), 2 (2 m), 3 (3 m), 5 (5 m) or 10 (10 m) for standard cable lengths.



Pico Style



3-Pin Pico Female


Features


- · Field installable
- 3- or 4-pin DC micro style
- · Straight connectors
- Screw terminals provide simple and secure installation
- Allows easy modification of existing cable installations


Specifications


Certifications	UL Recognized and CSA Certified	
Mechanical		
Coupling Nut	Nickel-plated brass	
Connector Shell Material	PBT	
Contacts	Gold-plated palladium nickel	
Cable	20 AWG (0.5 mm ²) max.	
Electrical		
Assembly Rating	3- or 4-pin: 60V, 4 A	
Environmental		
Enclosure Type Rating	IP67	
Operating Temperature [C (F)]	-40+88° (-40+185°)	

Approximate Dimensions [mm (in.)]









Dimensions are approximate. Illustrations are not drawn to scale.