

Cordsets & Field Attachables
Terminal Chambers, Mini Style
 Screw-Type, Field Attachable Connector

Pinout

Face View Pinout					
3-Pin		4-Pin		5-Pin	
					
Female	Male	Female	Male	Female	Male

Product Selection

Terminal Chambers

No. of Pins	Cable Diameter [mm (in.)]	Assembly Rating	Thread Size	Cat. No.					
				Straight Female Internal Threads		Straight Male Internal Threads		Straight Male External Threads	
3-Pin	6.0...8.0 (0.23...0.31)	250V, 12 A	PG9	*	871A-TS3-N2	*	871A-TS3-NU2	*	871A-TS3-NM2
	10.0...12.0 (0.39...0.47)		PG13.5		871A-TS3-N1		871A-TS3-NU1		871A-TS3-NM1
4-Pin	6.0...8.0 (0.23...0.31)	250V, 9 A	PG9	*	871A-TS4-N1	*	871A-TS4-NU1	*	871A-TS4-NM1
	10.0...12.0 (0.39...0.47)		PG13.5		871A-TS4-N2		871A-TS4-NU2		871A-TS4-NM2
	12.0...14.0 (0.47...0.55)		PG16		871A-TS4-N3		871A-TS4-NU3		871A-TS4-NM3
5-Pin	6.0...8.0 (0.24...0.32)	250V, 9 A	PG9	*	871A-TS5-N1	*	871A-TS5-NU1	*	871A-TS5-NM1
	10.0...12.0 (0.39...0.47)		PG13.5		871A-TS5-N2		871A-TS5-NU2		871A-TS5-NM2
	12.0...14.0 (0.47...0.55)		PG16		871A-TS5-N3		871A-TS5-NU3		871A-TS5-NM3

* Available in right angle. Replace the **S** in the cat. no. with an **R** (i.e. 871A-TR3-N2)

Note: Stainless steel connector versions may be ordered by adding an **S** to the cat. no., e.g., 871A**S**-TS3-N2.