PowerFlex 7-Class Options

Human Interface Modules















Blank Plate

20-HIM-A3

20-HIM-A5

20-HIM-A6

20-HIM-C3S

20-HIM-C5S

20-HIM-C6

Description	Cat. No.	Used with PowerFlex Drive							
		70	700	700H	700S	700L	753/755		
No HIM (Blank Plate), Handheld/Local (Drive Mount)	20-HIM-A0	1	1	/	/	1	1		
LCD Display, Full Numeric Keypad, Handheld/Local (Drive Mount)	20-HIM-A3	1	1	1	/	1			
LCD Display, Programmer Only, Handheld/Local (Drive Mount)	20-HIM-A5	1	1	/	/	1			
Enhanced, LCD, Full Numeric Keypad, Handheld/Local (Drive Mount)	20-HIM-A6	1	1	/	/	1	1		
Remote (Panel Mount) LCD Display, Full Numeric Keypad ★‡	20-HIM-C3S	1	1	1	/	/			
Remote (Panel Mount) LCD Display, Programmer Only★‡	20-HIM-C5S	1	1	/	/	/			
Enhanced, LCD, Full Numeric Keypad★‡	20-HIM-C6S	1	1	/	/	/	1		

[★] IP66, NEMA Type 4X/12—for indoor use only.

Human Interface Module (HIM) Accessories

Description		Used with PowerFlex Drive							
	Cat. No.	70	700	700H	700S	700L	753/755		
Bezel Kit for LCD HIMs, NEMA Type 1‡	20-HIM-B1	1	1	1	/	1	1		
PowerFlex HIM Interface Cable, 1 m (3.3 ft) ♣	20-HIM-H10	1	1	1	/	1	1		
Comm Option Cable Kit (Male-Male)									
0.33 m (1.1 ft)	1202-C03	1	1	1	/	1	1		
1 m (3.3 ft)	1202-C10	1	/	1	/	1	1		
3 m (9.8 ft)	1202-C30	1	1	1	/	1	1		
9 m (29.5 ft)	1202-C90	1	1	1	/	1	1		
Cable Kit (Male-Female) Δ									
0.33 m (1.1 ft)	1202-H03	1	1	1	/	1	1		
1 m (3.3 ft)	1202-H10	1	1	1	/	1	1		
3 m (9.8 ft)	1202-H30	1	/	1	/	1	1		
9 m (29.5 ft)	1202-H90	1	/	1	/	1	1		
DPI™ Cable Kit with Connectors, Tools and 100 m (328 ft) Cable	1202-CBL-KIT-100M	1	1	1	/	1	1		
DPI Cable Connector Kit	1202-TB-KIT-SET	/	1	1	/	1	1		
DPI/SCANport™ One to Two Port Splitter Cable	1203-S03	1	1	1	/	1	1		

[‡] Includes a 1202–C30 interface cable (3 m/9.8 ft) for connection to drive.

[‡] Includes a 1202-C30 interface cable (3 m/9.8 ft) for connection to drive.

Required only when HIM is used as handheld or remote.

 $[\]Delta$ Required in addition to 20-HIM-H10 for distances up to a total maximum of 10 m (32.8 ft).