




Screw Connection Terminal Blocks

Space-Saver Grounding Blocks

	1492-WG4				1492-WG6				1492-WG10S		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
	Single-circuit grounding terminal block.				Single-circuit grounding terminal block.				Single-circuit grounding terminal block.		
Certifications		IEC	CSA	ATEX		IEC	CSA	ATEX		CSA	IEC
Voltage Rating	—	—	—	—	—	—	—	—	—	—	—
Maximum Current	Grounding				Grounding				Grounding		
Wire Range (Rated Cross Section)	#22...12 AWG	4 mm ²	#22...12 AWG	4 mm ²	#22...10 AWG	6 mm ²	#22...10 AWG	6 mm ²	#22...8 AWG	#22...8 AWG	10 mm ²
Wire Strip Length	0.43 in. (11 mm)				0.47 in. (12 mm)				0.43 in. (11 mm)		
Recommended Tightening Torque	5.6...6.8 lb•in (0.7 N•m)				5.6...6.8 lb•in (0.7 N•m)				7.1 lb•in (0.8 N•m)		
Density	50 pcs/ft (166 pcs/m)				43 pcs/ft (142 pcs/m)				38 pcs/ft (125 pcs/m)		
Housing Temperature Range	-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)				-40...+195 °F (-40...+90 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color: Green/Yellow	1492-WG4	50			1492-WG6	50			1492-WG10S	10	
Accessories	Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Mounting Rails:											
1 m Symmetrical DIN (Steel)	199-DR1	10			199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10			1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2			1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2			1492-DR7	2			1492-DR7	2	
End Barrier	1492-EB3-Y	50			1492-EB10-Y	50			1492-EB10-Y	50	
End Anchors:											
DIN Rail — Normal Duty	1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50	
Marking Systems:											
Snap-in Marker Card	1492-MS6X12 (80/card)	5			1492-MS6X12 (80/card)	5			1492-MS6X12 (80/card)	5	