





22.5 mm Push Buttons

Product Selection

Back of Panel Components, Continued

Other

	Description	Volts	Pkg. Quantity	Cat. No.
 Cat. No. 800F-D3C	Incandescent Module For use with pilot lights, push buttons, and momentary mushroom operators. Note: Sold in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	No bulb	10	800F-D0C
		6V AC/DC		800F-D1C
		12V AC/DC		800F-D2C
		24V AC/DC		800F-D3C
		48V AC/DC		800F-D4C
		120V AC/DC		800F-D5C
 Cat. No. 800F-N3G	Integrated LED Module For use with all illuminated devices. For best results, LED should match lens color. For amber operators, use yellow LED. Note: Sold in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	24...120V AC/DC	10	* 800F-NUx
		24V AC/DC		* 800F-N3x
		120V AC		* 800F-N5x
		240V AC		* 800F-N7x
		24V AC/DC spring-clamp		* 800F-Q3x
		120V AC spring-clamp		* 800F-Q5x
		240V AC spring-clamp		* 800F-Q7x
		24V AC/DC ring lug		*† 800F-R3x
	Description	Contact Material	Pkg. Quantity	Cat. No.
 Cat. No. 800F-BX01	Base Mounted Contact Block Base mounted contact blocks can be used in plastic or metal enclosures. Note: Sold only in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	N.O.	10	800F-BX10
		N.C.		800F-BX01
		N.O. low voltage — QuadConnect™		800F-BX10V
		N.C. low voltage — QuadConnect™		800F-BX01V
		N.O.E.M.		800F-BX10E
		N.C.L.B.		800F-BX01L
		N.O. spring-clamp		800F-BQ10
		N.C. spring-clamp		800F-BQ01
	Description	Volts	Pkg. Quantity	Cat. No.
 Cat. No. 800F-BN3R	Base Mounted Integrated LED Module Base mounted modules can be used in plastic or metal enclosures. For best illumination results, LED should match lens color. Note: Sold in multiples of 10. Order (quantity of) 10 to receive one package of 10 pieces. Latch not included.	24V AC/DC	10	* 800F-BN3x
		120V AC		* 800F-BN5x
		240V AC		* 800F-BN7x

* To complete the cat. no., replace the x with one of the following letters for the desired color: **Y** = Amber, **R** = Red, **G** = Green, **B** = Blue, **W** = White.

* Cannot be used in a composite catalog number.

† Replacement screws are available (Cat. No. 800F-ARS1)