

Product Selection
Assembled Stations



Die Cast Aluminum
Cat. No. 800T-2TAR



Booted Operator – Stainless Steel
Cat. No. 800H-1HA4T



Booted Operator – Glass Polyester
Cat. No. 800H-1HA4R

Operator	Contact Symbol	Contact Action	Button Type	Button Color	Legend Marking	Type 4/13	Type 4/4X/13	
						Die Cast Aluminum	Booted Operator – Stainless Steel	Booted Operator – Glass Polyester
						Cat. No.	Cat. No.*	Cat. No.*
One Push Button		Momentary	Extended	Red	STOP	800T-1TA	800H-1HA4T	800H-1HA4R
		Momentary	Flush	Green	START	800T-1TB	800H-1HB4T	800H-1HB4R
		Momentary	Flush	Black	No Legend	800T-1TX	800H-1HX4T	800H-1HX4R
Two Push Buttons		Momentary	Flush Extended	Green Red	START STOP	800T-2TA	800H-2HA4T	800H-2HA4R
		Momentary	Flush Flush	Black Black	No Legend	800T-2TX	800H-2HX4T	800H-2HX4R
One Pilot Light, Two Push Buttons		Momentary	120V AC Flush Extended	Red Green Red	No Legend START STOP	800T-2TAR	800H-2HAR4T	800H-2HAR4R
		Momentary	120V AC Flush Flush	Red Black Black	No Legend	800T-2TXR	800H-2HXR4T	800H-2HXR4R
3-Position Selector Switch		Maintained	Knob Lever	Black with white insert	HAND-OFF-AUTO	800T-R3TA	—	—
		Maintained	Knob Lever	Black with white insert	No Legend	800T-R3TX	—	—
One Push Button		Maintained	Push-Pull/Twist	Red	EMERG STOP	800T-1TYM*	—	—
Two Push Buttons		Maintained	Flush Extended	Green Red	START STOP	800T-2TAM	800H-2HAM4T	800H-2HAM4R
		Maintained	Flush Flush	Black Black	No Legend	800T-2TXM	800H-2HXM4T	800H-2HXM4R

* Boot material is chlorosulfonated polyethylene. Add suffix **L** to the cat. no. for station with bootless operators. Example: **Cat. No. 800H-1HB4T** becomes **Cat. No. 800H-1HB4TL**.

* Supplied with yellow legend plate to comply with IEC 60947-5-5 and NFPA79 E-Stop standards that require yellow background.