



440G Guard Locking Switches

[440G-EZS21STL05J](#)



Representative Rendering, Not The Actual Product

Guard Locking Switch - 440G-EZ: Power to Lock, Solenoid Voltage: N/A, Solenoid Contacts: None, Contacts(Safety and Aux): 2 x PNP, (0.2 max.) - Door Position (Safety and Aux both provide the door position), Actuator: Magnetic Actuator,500N Holding Force, Conduit Entry: 6-in. (150mm) Pigtail with M12 male 5-Pin QD

Product Details

PRODUCT SELECTION	
Product Family	440G-EZ
Model Type	Power to Lock
Contacts (Safety/Auxiliary)	2 x PNP, (0.2 max.) - Door Position (Safety and Aux both provide the door position)
Solenoid Contacts	None
Solenoid Voltage	N/A
Actuator	Magnetic Actuator,500N Holding Force
Conduit Entry / Connection Type	6-in. (150mm) Pigtail with M12 male 5-Pin QD
Holding Force (Fzh)	500N (112.5 lbs)
ACCESSORIES	
Cordsets	DC Micro (M12), Female, Straight, 5-Pin, PVC Cable, Yellow, Unshielded, IEC Color Coded, No Connector, 5 meter (16.4 feet), 22AWG

Supporting Documentation and Downloads

- [Photo](#)