



Switch body	Operating handle	NFPA Handle and shaft
-------------	------------------	-----------------------

194R – J 30 – 1753 SA – TY N1
a b c d e f

a		b			c		d		e		f	
Fuse Type		Load Size♣			No. of Poles		Fuse Indication		External Handle		Shaft & NFPA79 Handle	
Code	Description	Code	Description	Dimensional Ref.★	Code	Description	Code	Description	Code	Description	Code	Description
C	UL Class CC, CSA Type HRCI-MISC (30 A)	20	20 A (BS88)	A1	1753	3-pole switch	Blank	Fixed Thermal/Fixed Magnetic	PY	Std/pistol red/yellow handle, 4/4X, IP66 (Cat. No. 194R-HS4E)	R1	Cat. No. 194R-R1 shaft (10.3 in.)
J	UL Class J, CSA Type HRCI-J (30 A or 60 A)	25	25 A (NFC)	A1			S	Fuse status indication	PB	Std/pistol black handle, 4/4X, IP66 (Cat. No. 194R-HS4)	R2	Cat. No. 194R-R2 shaft (18.0 in.)
H	CSA Type HRCII-C (30 A or 60 A)	30	30 A (CC, J, HRCI-J)	A1			Δ Class C and J fuses only.		TY	Test mode red/yellow handle, 4/4X, IP66 (Cat. No. 194R-HST4E)	N1	Cat. No. 194R-NHR1 NFPA79 handle with 12 in. shaft and guard tube
B	BS88 (20 A, 32 A, or 63 A)♣		30 A (Non-Fused) ‡	A2				TB	Test mode black handle, 4/4X, IP66 (Cat. No. 194R-HST4)	N2	Cat. No. 194R-NHR2 NFPA79 handle with 21 in. shaft and guard tube	
D	DIN (32 A or 63 A)♣		30 A (HRCII-C)	B1				LY	Extended length red/yellow handle, 4/4X, IP66 (Cat. No. 194R-HS4EL)			
F	NFC (25 A, 32 A, or 63 A)♣		32	32 A (BS88, NFC)				A1	LB		Extended length black handle, 4/4X, IP66 (Cat. No. 194R-HS4L)	
N	Non-fused (30 A or 60 A)	32 A (DIN)		B1								
		60	60 A (J, HRCI-J, HRCII-C)	B1								
			60 A (Non-Fused) ‡	B2								
			63	63 A (BS88, DIN, NFC)				B1				
			★ See Disconnect Switch Dimension References A1, A2, B1, and B2 (30 A and 60 A) for dimensional reference data. ‡ Non-fused disconnect switches must use separately installed fuses for upstream short-circuit protection. ♣ Fuse classes BS88, DIN, and NFC are not suitable for use in North American applications									

UL Enclosed Disconnect Switches (Fused and Non-Fused)

Catalog Number Explanation

194R-K Non-Metallic Enclosure UL Type 3/4/4X, IP66	194R-F Painted Steel Enclosure UL Type 3/4/12, IP66	194R-C Stainless Steel Enclosure UL Type 4/4X, IP66

194R – C J 30 – 1753 SA – TB – P
a b c d e f g